

Douglas County Surveyor's Record of
Government Corners Renewed

T. 31 S. T. S. R. 9 W. R. W. W. M.

ROKE-CHAPMAN CO., EUGENE, ORE., 21881

See M 159-23 = 5/2009 78

Section Corner to Sections 25 - 26 - 35 - 36. *for D. Edwards Survey*
Found - $\frac{1}{2}$ " Iron Rod at Corner, See Ren. #1. *unrecorded BT bears N41°W 15.2 ft*
30" D. Fir N. 72 3/4° E. 44.9 ft., good pitched over face. *Set w Fence*
30" D. Fir S. 70° E. 66.8 ft. good pitched over face. *Post 2' East*
40" D. Fir S. 14 1/2° W. 45.2 ft. good pitched over face.
6", now 8" D. Fir N. 42° W. 41.8 ft., shows good face.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 31 S R 9 W
Office S 26 S 25
1967 S 35 S 36

Do not mark any new BT's. All BT's. in good condition.

$\frac{1}{4}$ Corner to Sections 35 and 36. 79
Found - Orig. 14", now 18" Cedar, S. 68° W. 6.6 ft., has burnt face.
8", now 10" D. Fir, N. 28° W. 54.5 ft., scribe visible "S". Ren. #10.
No trace of S.E. BT. nor 7/8" corner rod, taken out by skid road.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 31 S R 9 W
Office, 1967 $\frac{1}{4}$ S 35 S 36
New BT: 8" D. Fir S. 69 1/2° E. 53.2 ft. mkd. $\frac{1}{4}$ S36 CS BT.
Note - also found stump with good BT. face, but could not determine where it came out of the ground.

Section Corner to Sections 26 - 27 - 34 - 35. 80
Found - 24", now 36" D. Fir, S. 2° E. 24.4 ft., shows good scar.
12", now 20" D. Fir, S. 65° W. 31.7 ft., shows good scar.
8", now 13" Chinq., N. 2° W. 43.6 ft., opened for scribe "T", center rotten.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 31 S R 9 W
Office, 1967 S 27 S 26
S 34 S 35
New BT's: 7" Cedar N. 84° E. 12.0 ft. mkd. T31S R9W S26 CS BT.
7" Cedar N. 12° W. 12.5 ft. mkd. T31S R9W S27 CS BT.

$\frac{1}{4}$ Corner to Sections 27 and 26. 81
Found - 10" D. Fir, now Stump, S. 85° E. 28.4 ft., opened for scribe "B".
12" Oak S. 75° W. 16.5 ft., this tree down & burnt.
Set = Brass Cap at Cor. Mkd: County Surveyor's T 31 S R 9 W
Office, 1967 $\frac{1}{4}$ S 27 S 26
New BT's: 11" D. Fir S. 81 1/2° E. 35.3 ft. mkd. $\frac{1}{4}$ S26 CS BT.
8" D. Fir S. 47 1/2° W. 12.2 ft. mkd. $\frac{1}{4}$ S27 CS BT.

$\frac{1}{4}$ Corner to Sections 19 and 30. 82
Found - Orig. 14" Hemlock, now dead, N. 55° W. 15.6 ft. (This tree is Fir)
Opened for scribing "S19 $\frac{1}{4}$ BT". By ring count, places tree approx. 1900, very fine rings.
No trace of Corner tree nor S.E. BT. (Heavy Logging)
Set - Brass Cap at Cor. Mkd: County Surveyor's T 31 S R 9 W
Office S 19 S 30
1967
New BT's: 6" W. Fir N. 61° E. 50.2 ft. mkd. $\frac{1}{4}$ S19 CS BT.
12" Hemlock S. 40° E. 68.9 ft. mkd. $\frac{1}{4}$ S30 CS BT.

$\frac{1}{4}$ Corner to Sections 7 and 18. 83
Found - 12" D. Fir, now Stump, N. 12° E. 44.2 ft., opened for scribe "BT".
36" D. Fir, now Stump, S. 64° E. 19.0 ft., scribe visible "BT". (Ren. #3)
Set - Brass Cap at Cor. Mkd: County Surveyor's T 31 S R 9 W
Office S 7 S 18
1967
New BT: 12" Cedar S. 84° W. 92.0 ft. mkd. $\frac{1}{4}$ S18 CS BT.
No other trees available.

John M. Powell
Frank Jones & J. Brady
March, 1967
C. S. File No. 54/32