

Douglas County Surveyor's Record of
Government Corners Renewed

T. 31 S. T. S. R. 9 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21891

FO. OK BY D. EDWARDS, JAN. 2003 CS 6546-189

1/4 Corner to Sections 33 and 34.
Found - Orig. 8" Yew Corner Tree, scribe visible "S33" S34".
Orig. 18", now 22" D. Fir, S. 42° W. 44.8 ft., burnt face.
Orig. 8" D. Fir, now down & tree rotted, N. 38° E. 21.1 ft.
Set - Brass Cap on N. Side of Corner Tree Mkd: T. 31 S R. 9 W.
County Surveyor's Office, 1967 1/4 S 33 | S 34
New BT's: 7" Tan Oak S. 21° E. 19.5 ft. mkd. 1/4 S34 CS BT.
12" Laurel S. 84° W. 15.8 ft. mkd. 1/4 S33 CS BT.

Sec. Cor. to Secs. 4 and 3 only, T32S-R9W. 90
Found - 1917 Cadastral Brass Cap mkd. properly.
20" D. Fir, now stump washed out, S. 81° W. 55.4 ft.
20" D. Fir, now Snag, S. 70° E. 29.0 ft., shows good scar.
New BT's: 5" D. Fir S. 45° W. 5.6 ft. mkd. S 4 CS BT.
8" D. Fir N. 37° W. 37.6 ft. mkd. T31S R9W S34 CS BT.
No other trees available.

Note - This corner lies West of A. P., see below, 141.2 ft.

Angle Point, T.31S.-9W. and T.32S.-9W. 91
Found - Brass Cap Mkd: U. S. General Land Office

A P
1917

60" D. Fir, now Stump, N. 61° E. 30.4 ft., opened for scribing. "BT".
24", D. Fir, now Snag, S. 76° W. 16.5 ft., shows scar.
New BT's: 8" Yew S. 61° W. 77.8 ft. mkd. "A P CS BT."
9" D. Fir N. 30° W. 59.7 ft. mkd. "A P CS BT".
Note - Logging Road bears North 65.0 ft.
This corner is 141.2 ft. East of Sec. Cor. to Secs. 4 & 3 only. (See Above)

1/4 Corner to Sec. 13, T31-9W. & Sec. 18, T31-8W. 92

Found - GLO Brass Cap Mkd: 1962
R9W S13 | S18 R8W

37" D. Fir, now broken Snag, N. 53 3/4° E. 11.9 ft., bark scribed,
1/4 S18" "BT".
31" D. Fir, now Stump which is out of ground, S. 48 3/4° W. 9.2 ft.,
scribe visible "1/4 S18 BT".
New BT's: 14" D. Fir N. 77° E. 18.8 ft. mkd. 1/4 S18 CS BT.
6" Live Oak S. 14° W. 56.6 ft. mkd. 1/4 S13 CS BT.
Note - This corner lies east of Elk Valley Road approx. 150.0 ft.

Section Corner to Sections 8 - 9 - 16 - 17. 93

Found - Iron Pipe at Corner, See Ren. #12.
Orig. 16" D. Fir, now stump, has been opened, N. 42° E. 6.6 ft., "S9T31R9W".
Orig. 24" D. Fir, now stump, S. 40° E. 23.2 ft., shows good scar.
No trace of S.W. Bearing Tree.
Set - Brass Cap alongside I. Pipe & Mkd: County Surveyor's T 31 S R 9 W
Office S 8 | S 9
1967 S 17 | S 16
New BT's: 9" W. Fir N. 67° E. 55.1 ft. mkd. T31S R9W S9 CS BT.
9" W. Fir S. 2" E. 48.3 ft. mkd. T31S R9W S16 CS BT.

Section Corner to Sections 9 - 10 - 15 - 16. 94

Found - 3/4" Iron Pipe at Corner, See Ren. #22. #176
Orig. 32", now 38" D. Fir, S. 39° E. 52.8 ft., shows good scar.
(Find Hart Dist. to be 43.5')
Orig. 30" D. Fir, now Stob, S. 35° W. 30.7 ft., shows good scar.
40" D. Fir Uproot, S. 71° W. 25.8 ft., scribe visible "T31S S16".
Set - Brass Cap alongside I. Pipe Mkd: County Surveyor's T31S R9W
Office S 9 | S 10
1967 S 16 | S 15
New BT's: 48" D. Fir S. 2° W. 34.9 ft. mkd. T31S R9W S16 CS BT.
48" D. Fir N. 42° E. 45.0 ft. mkd. T31S R9W S10 CS BT.
6" W. Fir N. 19° W. 79.6 ft. mkd. T31S R9W S9 CS BT.

Note - Creek bears North 100.0 ft.

John M. Powell
Frank Jones & Joe Brady
March, 1967
C. S. File No. 54/32

RE-RENEWED