

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 31 S. T. S. R. 9 W. R.W.W.M.

ROKE-CHAPMAN CO., EUGENE, ORE. 21881

95

1/4 Corner to Sections 7 and 8.  
Found - No trace of corner stone.  
24" D. Fir, now 24" Stump, N. 36° E. 7.3 ft., scribe partly  
overgrown, Partly visible "1/4 B".  
S.W. BT., now stump hole.  
40" D. Fir Stump N. 73° E. 9.7 ft. (unrecorded) scribed,  
"BT" 1/4 S8 T31 R9W".  
Set - Brass Cap at Cor. Mkd: County Surveyor's T 31 S R 9 W  
1/4 Office, 1967 1/4 S 7 | S 8  
New BT's: 18" D. Fir Stump N. 65° W. 47.3 ft. mkd. 1/4 S 7 CS BT.  
No trees available.  
Note - This corner lies on steep, south slope, approx. 80 ft. E. of  
small ridge & 250 ft. W. of ravine. N.E. of corner in head  
of ravine is a rock bluff.

96

1/4 Corner to Sections 8 and 17.  
Found - 3/4" Iron Pipe at 1/4 corner, See Ren. #15.  
24" D. Fir, now stump, S. 40° E. 15.0 ft., scribe visible,  
"BT" 1/4 S17 T31S".  
12" D. Fir, now rotten stump, N. 51° E. 9.2 ft.  
Set - Brass Cap alongside I.P. Mkd: County Surveyor's T31S R9W  
Office 1/4 S 8  
1967 1/4 S 17  
New BT's: 9" Hemlock S. 77° W. 41.0 ft. mkd. 1/4 S17 CS BT.  
No other trees available.  
Note - This corner lies about 150.0 ft. S. of road on Gold Creek.  
Location tag on road.

97

1/4 Corner to Sections 12 and 13. *FO. OK-K. DeGroot 6/01 M137-13*  
Found - 60" D. Fir, now stump, N. 75° E. 10.6 ft., shows good scars.  
24" W. Fir, now dead, S. 45° W. 6.6 ft., scribe visible "1/4".  
Set - Brass Cap at 1/4 Cor. Mkd: County Surveyor's T31S R9W  
Office 1/4 S 12  
1967 1/4 S 13  
New BT's: 9" W. Fir N. 54° E. 52.4 ft. mkd. 1/4 S12 CS BT.  
7" D. Fir S. 18° E. 19.7 ft. mkd. 1/4 S 13 CS BT.

98

1/4 Corner to Sections 13 and 24. *Reset BC from 3 FD BTs*  
Found - 36" D. Fir, now stump, N. 50° E. 52.8 ft., opened for scribe "T".  
*Coray Woodruff - 2/2007 MISS-17 (Type)*  
No trace of S. W. B.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T31S R9W  
Office 1/4 S 13  
1967 1/4 S 24  
New BT's: 14" W. Fir S. 21 1/2° E. 49.5 ft. mkd. 1/4 S24 CS BT.  
12" W. Fir N. 70° W. 47.8 ft. mkd. 1/4 S13 CS BT.

99

Sec. Cor. to Secs. 6 & 7, R9W, and Secs. 1 & 12, R10W.  
Found - 48" D. Fir, now stump, N. 20° E. 115.5 ft., shows BT scar.  
36" D. Fir, now stump, S. 55° W. 9.0 ft., opened for scribe,  
"12 T31S R10W".  
No trace of S.E., N.W. BT's., nor Original corner stone.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T 31 S  
Office R10W S 1 | S 6 R9W  
1967 S 12 | S 7  
New BT's: 8" Hemlock S. 27° W. 25.7 ft. mkd. T31S R10W S12 CS BT.  
12" Hemlock South 29.0 ft. mkd. T31S R9W S7 CS BT.  
16" Fir Stump N. 19° W. 28.4 ft. mkd. T31S R10W S1 CS BT.  
10" Cedar N. 41° E. 53.9 ft. mkd. T31S R9W S6 CS BT.

John M. Powell  
Frank Jones & Joe Brady  
March, 1967  
C. S. File No. 54/32

*Handwritten notes:*  
1-11-1967  
L-11-1967  
C Woodruff