

Douglas County Surveyor's Record of
Government Corners Renewed

T. 31 S. T. S. R. 9 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

100

1/4 Corner to Sec. 6, T31-9W. & Sec. 1, T31-R10W.
Found - 6" Hemlock, now Snag, N. 62° E. 5.9 ft. mkd. scribe visible, "1/4 S BT".
24" D. Fir, now stump, N. 45° W. 13.2 ft., scribe visible "1/4".
Also unrecorded I. Pipe at 1/4 corner.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1967 T 31 S R10W S 1 | S 6 R9W
New BT's: 10" Cedar N. 47 1/2° E. 23.7 ft. mkd. 1/4 S6 CS BT.
13" Cedar S. 53° W. 79.4 ft. mkd. 1/4 S 1 CS BT.

101

1/4 Corner to Sections 17 and 18.
Found - 1 1/2" Iron Pipe & Corner Tree. REN. #19
Orig. 22" D. Fir, now Stump, S. 54° E. 22.3 ft., scribe visible "1/4 S".
No trace of S.W. Bearing Tree/
Set - Brass Cap alongside I.P. on South Side of Corner Tree, mkd:
County Surveyor's Office, 1967 T 31 S R 9 W 1/4 S 18 | S 17
New BT's: 12" Hemlock S. 83° E. 73.0 ft. mkd. 1/4 S17 CS BT.
10" W. Fir N. 32° W. 45.0 ft. mkd. 1/4 S18 CS BT.

102

~~Found - Sec. Corner R10WS 24 | S 19 R9W Found Only.
S 25 | S 30 T 31 S~~
~~Found - Post, No trace of Original Trees.
40" D. Fir N. 12° E. 47.3 ft., scribed S19 "BT", pitched over.
Cedar S. 28° E. 26.8 ft. mkd. S30 BT. (Scribing done with pocket knife)~~

103

~~Found only: 1/4 Corner to R10S S12/S 7 R9W
Found - 2" Iron Pipe - No trace of Original Bearing Trees.
60" Fir Stump S. 72° W. 33.1 ft., scribed "1/4 BT", knife scribed.~~

104

1/4 Corner to Sections 31 and 32.
Found - 12", now 13" Laurel, N. 35° E. 21.8 ft., face rotten.
6", now 10" D. Fir, N. 82° W. 32.3 ft., opened for scribe "BT".
No trace of corner stone.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1967 T 31 S R 9 W 1/4 S 31 | S 32
New BT's: 12" Live Oak N. 32° W. 27.6 ft. mkd. 1/4 S31 CS BT.
12" Laurel N. 35° E. 26.0 ft. mkd. 1/4 S32 CS BT.
Note - This corner lies approx. 260.0 ft. north of small creek on Steep S. slope

105

1/4 Corner to Sections 30 and 29.
Found - Stone at 1/4 corner, right size, but no marks visible.
30" D. Fir, now 32" Snag, East 12.5 ft., opened for scribe "1/4".
40", now 43" D. Fir, S. 45° W. (Record S. 50° W.) 29.0 ft., shows good scribe
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1967 T 31 S R 9 W 1/4 S 30 | S 29
New BT: 30" D. Fir N. 16° E. 8.9 ft. mkd. 1/4 S29 CS BT.

106

Section Corner to Sections 15 - 16 - 21 - 22.
Found - Orig. 72" Fir, now snag, N. 50° E. 21.8 ft.
Orig. 60" Fir, now snag, S. 70° W. 59.4 ft.
Orig. 60" Fir, now stump, N. 40° W. 72 ft. (Record 66'), found "S" on burnt face.
Orig. 18" W. Fir, now rotten stump, S. 45° E. 85.0 ft.
Set - Brass Cap at Cor. Mkd: County Surveyors Office, 1967 T 31 S R 9 W S 16 | S 15 S 21 | S 22
New BT's: 15" D. Fir N. 13° E. 5.4 ft. mkd. T31S R9W S15 CS BT.
6" D. Fir N. 75° W. 13.6 ft. mkd. T31S R9W S16 CS BT.
12" D. Fir S. 67° W. 21.7 ft. mkd. T31S R9W S21 CS BT.
14" D. Fir S. 40° E. 6.0 ft. mkd. T31S R9W S22 CS BT.

John M. Powell
Frank Jones & Joe Brady
March, 1967
C. S. File No. 54/32

April, 1967

RE-REVIEWED
#180