

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 31 S. T. S. R. 9 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

107  
 $\frac{1}{4}$  Corner to Sections 29 and 32.  
 Found - No trace of 4" Live Oak Corner Tree.  
 8" Live Oak, now 10", N. 20° E. 12.5 ft., 2 good faces.  
 18" D. Fir, now 24" Stump, S. 48° W. 29.0 ft., opened & found  
 good "BT" scribe.  
 Set - Brass Cap at Cor. Mkd: County Surveyor's T 31 S R 9 W  
 Office 1967  $\frac{1}{4}$  S 29  
 S 32  
 New BT: 7" Live Oak S. 32° W. 16.8 ft. mkd.  $\frac{1}{4}$  S32 CS BT.  
 Note - Corner lies on steep, west slope.

108  
 Section Corner to Sections 28 - 29 - 32 - 33.  
 Found - No trace of Corner Stone.  
 28" D. Fir S. 10° W. 13.9 ft., shows 2 good faces.  
 10" live Oak, now 11", S. 65° E. 35.0 ft., shows scribing.  
 Set - Brass Cap at Cor. Mkd: County Surveyor's T 31 S R 9 W  
 Office 1967 S 29 S 28  
 S 32 S 33  
 Rescribed: 10" Live Oak, now 11" S. 65° E. 35.0 ft., scribed:  
 "T31S R9W S33 CS BT".  
 New BT's: 36" D. Fir N. 4° W. 40.4 ft. mkd. T31S R9W S28 CS BT.  
 26" D. Fir N. 75° W. 30.0 ft. mkd. T31S R9W S28 CS BT.

RE-RENEWED, SEE CORNER NO. #173

Pd. B.C.  
 BT's Down on Dead  
 11/89 S. Riley  
 C.S. 63/61

109  
 $\frac{1}{4}$  Corner to Sections 19 and 20.  
 Found - 6" D. Fir Corner Tree, now 12", shows good scar.  
 8" L. O., now 9", N. 45° W. 7.9 ft., scribe visible "S19  $\frac{1}{4}$ ".  
 Set - Brass Cap on N. edge of Corner Tree Mkd:  
 County Surveyor's T 31 S R 9 W  
 Office, 1967  $\frac{1}{4}$  S 19 S 20  
 New BT: 27" D. Fir S. 42° E. 21.6 ft. mkd.  $\frac{1}{4}$  S20 CS BT.

110  
 Section Corner to Sections 33 and 34 only, T31-9W.  
 Found - Gen. Land Office Brass Cap at Cor., mkd. properly in 1917.  
 Brass Cap badly bent and loose.  
 Reset Brass Cap and try to straighten.  
 30", now 28" D. Fir N. 8° E. 13.2 ft., shows good face.  
 24", now 28" D. Fir, N. 20° W. 61.4 ft., shows good face.  
 New BT: Reblazed & Rescribed: 28" D. Fir N. 8° E. 13.2 ft. scribed  
 "T31S R9W S34 CS BT".

John M. Powell  
 Frank Jones & Joe Brady  
 March and April, 1967  
 C. S. File No. 54/32

111  
 $\frac{1}{4}$  Corner to Section 36 only, T31-9W.  
 Found - 10" D. Fir Corner Tree, now 16", shows good scar on North face.  
 14" Maple, now 17", N. 8° W. 37.6 ft., shows scar.  
 7" Laurel, now 7", N. 55 $\frac{1}{2}$ ° E. 80.2 ft. (Record. 83.2')  
 rotten scribing visible " $\frac{1}{4}$  S".  
 New BT" 7" Laurel N. 54 $\frac{1}{2}$ ° E. 81.8 ft. mkd.  $\frac{1}{4}$  S36 CS BT.  
 Note - This corner lies in very rocky area on north slope approx.  
 110 ft. east of creek.

112  
 Section Corner to Sections 1 & 2 only, T32-9W.  
 Found - Gen. Land Off. Brass Cap at Cor., properly mkd. in 1917.  
 10", now 13" D. Fir, S. 30° W. 5.3 ft., shows good scar.  
 16", now 18" D. Fir, S. 21° E. 7.9 ft., tree opened earlier,  
 scribe visible "T32S R9W S1", face cut.  
 Reblazed & Rescribed: 18" D. Fir S. 21° E. 7.9 ft. mkd. T31S R9W S1 CS BT.  
 Note - This corner lies 10.0 ft. East of very small ravine.

113  
 $\frac{1}{4}$  Corner to Section 5 only, T32-9W.  
 Found - Gen. Land Office Brass Cap at Corner, properly mkd. in 1917.  
 20" Laurel, now 21", S. 58° E. 11.2 ft., rotted face " $\frac{1}{4}$ " visible.  
 40", now 42" D. Fir, S. 46° W. 21.8 ft., shows good scar.  
 New BT: 10" D. Fir S. 37° E. 15.0 ft. mkd.  $\frac{1}{4}$  S 5 CS BT.