

Douglas County Surveyor's Record of
Government Corners Renewed

T. 31 S. T. S. R. 9 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

114

A. P. (Angle Point) T. 31 S., R. 9 W.
(This A. P. 4.8 chains East of N $\frac{1}{4}$ Corner to Sec. 5, See Ren. #113.)
Found - Brass Cap, out of ground, but mkd. by GLO in 1917.
12", now 14" Laurel, S. 17° W. 12.5 ft., tree rotten but found
scribe marks, try to count rings, but too fine.
No trace of N.E. BT.
Reset - Brass Cap which falls in Skid Road.
New BT's: 8" Cedar S. 61° E. 46.4 ft. mkd. AP CS BT.
25" Pine S. 25° W. 34.6 ft. mkd. A@ CS BT.

115

Section Corner to Sections 32 and 33 only, T31-9W.
Found - GLO Brass Cap at Cor. properly marked in 1917.
Orig. 14" D. Fir N. 33° E. 15.0 ft., opened for scribe "T".,
burned face.
18", now 20" D. Fir, N. 29° W. 33.0 ft., shows scar.
New BT's: 13" D. Fir N. 42° W. 30.3 ft. mkd. T31S R9W S32 CS BT.
Reblzd. & Rescrib: 14" D. Fir N. 33° E. 15.8 ft. mkd. T31S R9W S33 CS BT

116

$\frac{1}{4}$ Corner to Sections 26 and 35.
Found = 36" Fir Stump N. 55° W. 19.6 ft. burnt face shows "BT" scribe.
16" Fir, now fragments, down & out of ground, S. 10° E. 5.3 ft.
No trace of Stone at $\frac{1}{4}$ corner.
Set - Brass Cap at $\frac{1}{4}$ Cor. Mkd: County Surveyor's T 31 S R 9 W
Office $\frac{1}{4}$ S 26
1967 S 35
New BT's: 16" D. Fir S. 46° E. 14.5 ft. mkd. $\frac{1}{4}$ S35 CS BT.
5" Live Oak N. 47° W. 32.5 ft. mkd. $\frac{1}{4}$ CS BT.

117

$\frac{1}{4}$ Corner to Sections 20 and 21.
Found - Orig. 6", now 13" Laurel, N. 25° E. 18.5 ft., opened tree
for scribe, " $\frac{1}{4}$ S".
Orig. 6", now 12" Laurel, S. 75° W. 40.3 ft., tree opened
before, scribe visible.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 31 S R 9 W
Office, 1967 $\frac{1}{4}$ S 20 | S 21
New BT's: 9" D. Fir S. 75° E. 13.2 ft. mkd. $\frac{1}{4}$ S21 CS BT.
8" Chinquapin S. 36° W. 12.0 ft. mkd. $\frac{1}{4}$ S20 CS BT.

118

Section Corner to Sections 17 - 16 - 20 - 21.
Found - Orig. 38", now 41" Fir, S. 45° W. 66.0 ft., shows good scar. #169
Orig. 30", now 37" Fir, S. 38° E. 85.0 ft., opened for scribing,
S21 T31S R9W". See Ren. #13.
No trace of N. E. and N. W. Trees.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 31 S R 9 W
Office S 17 | S 16
1967 S 20 | S 21
New BT's: 5" D. Fir S. 21° W. 29.5 ft. mkd. T31S R9W S20 CS BT.
8" D. Fir S. 45° E. 15.3 ft. mkd. T31S R9W S21 CS BT.
10" D. Fir N. 53° W. 18.1 ft. mkd. T31S R9W S17 CS BT.
8" D. Fir N. 26° E. 18.6 ft. mkd. T31S R9W S16 CS BT.

119

Corner to Sections 34 and 35 only, T31-9W.
Found - GLO Brass Cap at Sec. Cor., properly mkd. in 1917.
20", now 33" D. Fir, N. 1 $\frac{1}{2}$ ° E. 330.0 ft., shows good scar.
36", now 40" D. Fir Snag, N. 5 $\frac{1}{2}$ ° W. 329.4 ft., shows good scar.
Note - Did not open these trees, being convinced they are right by
surrounding trees which are small & other badly burnt stumps.
New BT's: 10" D. Fir N. 40° W. 27.0 ft. mkd. T31S R9W S34 CS BT.
10" D. Fir N. 37° E. 32.7 ft. mkd. T31S R9W S35 CS BT.

John M. Powell
Frank Jones & Joe Brady
March and April, 1967
C.S. File No. 54/32

RE-RENEWED, SEE CORNER #169