

Douglas County Surveyor's Record of
Government Corners Renewed

T. 31 S. T. S. R. 9 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

120

~~RE-RENEWED GOVERNMENT CORNER NO. #167~~
 $\frac{1}{4}$ Corner to Section 35 only, T31-9W.
 Found - GLO Brass Cap, properly mkd. in 1917.
 18" D. Fir, now down, N. 62° W. 31.7 ft., tree very rotten.
 8" Maple, now 14", N. 25° E. 27.1 ft., shows good scar.
 Orig. 36", now 40" D. Fir, S. 60° E. 27.1 ft., scribe visible, "S".
 New BT: 11" D. Fir N. 80° W. 78.1 ft. mkd. $\frac{1}{4}$ S35 CS BT.

121

A. P. on South Line of T.31S. R9W.
 Note - This A. P. lies 142.8 ft. East of Cor. to Sections 3 and 2 only,
 (Cor. Secs. 3 & 2 Only, fd. in good condtn) T. 32 S., R. 9 W.
 Found - Corner Tree, now 72" S. Pine Stob, scribe visible,
 "A P BT" on northeast side.
 Orig. 30", now 37" D. Fir, N. 70° E. 38.3 ft., scribe visible.
 30" D. Fir, now splintered Stub, S. 74° W. 20.5 ft.
 Set - Brass Cap on N. Side of S. Pine Stob, mkd: T 31 S R 9 W
 County Surveyor's A.P.
 Office, 1967 T 32 S R 9 W
 New BT: 9" Laurel N. 41° W. 11.0 ft. scribed A. P. CS BT.

122

$\frac{1}{4}$ Corner to Sections 5 and 8.
 Found - 21" Fir, now burnt Stump, N. 33° E. 49.7 ft.
 16" Hemlock, now burnt Snag, S. 15° E. 6.9 ft., shows scar. (Ren. #25)
 LaFlamme's Bearing Trees: (See C.S. 55/23) - Ren. No. 125
 27" Cedar Stump S. 44 $\frac{1}{2}$ ° W. 30.3 ft. mkd. $\frac{1}{4}$ S8 BT.
 30" Cedar Stump N. 42° E. 57.7 ft. mkd. $\frac{1}{4}$ S5 BT.
 (Dist. taken to face of stump which are painted red & tagged)
 Set - Brass Cap in Mound of Stone Mkd: County Surveyor's T31S R9W
 Office $\frac{1}{4}$ S 5
 1967 S 8

No trees in area to scribe.

123

Section Corner to Sections 4 - 5 - 8 - 9.
 Found - 18" Hemlock N. 25° E. 8.6 ft., down & burnt, scribe visible.
 21" Hemlock, now burnt stump, N. 78° W. 29.4 ft. (Ren. #26)
 LaFlamme's Renewal: (See C.S. 55/23) - 1" Iron Pipe at Sec. Corner.
 36" Fir Stump S. 67° W. 63.8 ft. mkd. S8 BT. (Ren. #129)
 39" Fir Stump S. 84° E. 38.1 ft. mkd. S9 BT. (Tagged)
 28" Hemlock Stump N. 7° W. 59.6 ft. mkd. S5 BT. (All)
 29" Cedar Snag N. 53° E. 53.0 ft. mkd. S4 BT. (Stumps)
 Set - Brass Cap at Corner County Surveyor's T 31 S R 9 W
 Alongside I. Pipe: Office S 5 S 4
 1967 S 8 S 9

124

~~RE-RENEWED GOVERNMENT CORNER NO. #148~~
 $\frac{1}{4}$ Corner to Sec. 5, T31S-R9W and Sec. 32.
 Found - Original Stone & 2 Orig. BT's both now snags.
 Scriber 2 BT's: 22" D. Fir S. 12° W. 34.7 ft. $\frac{1}{4}$ S5 BT 473".
 22" D. Fir N. 25° E. 13.5 ft. $\frac{1}{4}$ S32 BT".
 Co. Surv. BRASS CAP SET - SEE COR. #148

125

$\frac{1}{4}$ Corner to Sections 5 and 8.
 Found - Orig. BT., now a Snag.
 Scriber New BT's: Port Orford Cedar Stump 27", S. 44 $\frac{1}{2}$ ° W. 30.3 ft.
 measured to the face $\frac{1}{4}$ S8 BT".
 Port Orford Cedar Stump 30", N. 42° E. 57.7 ft.
 measured to the face $\frac{1}{4}$ S5 BT".
 (See Ren. #122)

126

Center North 1/16 Corner of Section 5
 (on a true N.-S. $\frac{1}{4}$ line & the prop. dist. btwn. center & N. $\frac{1}{4}$ Cor.)
 Set - 4" Square Post for this corner and scribe:
 Port Orford Cedar 38", South 27.7 ft. "1/16 S5 BT 473".
 Douglas fir 46", N. 6° E. 69.3 ft. "1/16 S5 BT".

127

East 1/16 btwn. Sections 5 and 32.
 Set - 4" Square Post for this corner and scribe:
 Incense Cedar 50", S. 32 $\frac{1}{2}$ ° W. 26.5 ft. "1/16 S 5 BT".
 Douglas Fir 24", N. 31 $\frac{1}{2}$ ° W. 17.4 ft. "1/16 S32 BT 473".

John M. Powell
 Frank Jones & Joe Brady
 April, 1967
 C. S. File No. 54/32

#187

Forest J. LaFlamme
 For Georgia Pacific Corp.
 Dec. 2, 1966
 C. S. File No. 55/23