

Douglas County Surveyor's Record of
Government Corners Renewed

T. 31 S. T. S. R. 9 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Forest J.
LaFlamme

12/12/66

C. S.
File
No.

55/23

Northeast 1/16 Corner (Also SE. Corner of Lot 2) (sec. 5)
Set - 1 3/4" pipe and scribe:
Douglas fir, 56", S. 28 3/4° E. 18.9 ft. " 1/16 S5 BT 473".
Douglas fir, 40", N. 28 1/4° W., 11.4 ft. " 1/16 S5 BT."

128

Section Corner to Sections 4 - 5 - 8 and 9.
(See County Surveyor's Ren. #123)

Found -- 1" Pipe and 1 Orig. BT. which is now an uproot.
Scribed BT's: 39" D. Fir Stump S. 83 1/2° E. 36.4 ft. measured to face, @S 9 BT".
38" D. Fir Stump S. 73° W. 62.7 ft. measured to face, "S 8 BT".
25" Hemlock Stump N. 6° W. 58.7 ft. measured to face, "S 5 BT".
29" Cedar Snag, N. 54° E. 51.3 ft. measure to face, "S 4 BT".

129

Sec. Corner to Sections 20 - 21 - 28 - 29.

Found - Stone at Sec. Cor. Mkd: 2 notches on South & the right size.
24", now 32" D. Fir, S. 62° E. 66.0 ft., scribe visible "W"., burnt & rotten face and snag top.
30", now 37" D. Fir, S. 72° W. 30.4 ft., shows good scar.
30", now 39" D. Fir N. 42° W. 22.4 ft., shows good scar.
Could not find 5" Laurel (N.E.) Tree.

Set - Brass Cap alongside Stone Mkd: County Surveyors T 31 S R 9 W
Office S 20 S 21
1967 S 29 S 28

New BT's: 8" Laurel N. 68° E. 11.2 ft. mkd. T31S R9W S21 CS BT.
7" Laurel S. 75° E. 16.5 ft. mkd. T31S R9W S28 CS BT.

Note - This corner lies on top of large ridge, running East.

130

1/4 Corner to Sections 21 and 28.

Found - 60" D. Fir, now 60" Stump Corner Tree, shows scribing "1/4 S" on north side & "1/4 S28" on the south side.
60" D. Fir, now 60" Stump, N. 47° W. 28.4 ft., badly burnt, shows no scribing.
48" D. Fir, now 48" Snag, S. 60° E. 28.4 ft., good bearing and distance but no scribing.

Set - Brass Cap on N. side of the Corner Stump Mkd: T 31 S R 9 W
County Surveyor's 1/4 S 21
Office, 1967 S 28

New BT's: 6" D. Fir S. 7° E. 21.4 ft. mkd. 1/4 S28 CS BT.
50" D. Fir N. 47° W. 44.4 ft. mkd. 1/4 S21 CS BT.

131

1/4 Corner to Sections 21 and 22.

Found - 7/8" Hex. Rod at Corner, See Ren. #8.
Orig. 24", now 26" Fir Snag, S. 57° W. 45.5 ft., shows good scribe "S".
10" D. Fir (Record in Ren. 96") N. 29 1/2° W. 16.8 ft., shows good face.
6", now 10" D. Fir N. 35° E. 41.1 ft., shows good face.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 31 S R 9 W
Office, 1967 1/4 S 21 S 22

Note - Corner lies on steep, south slope.

132

Angle Point E. of 1/4 Corner to Sec. 2 only, T32-9W.

(This A. P. lies 38.0 ft. East of 1/4 Cor. Sec. 2 only, T32-9W. which is a Brass Cap in good condition).

Found - 18", D. Fir Corner Tree, now 21", opened, "AP BT" Visible.
28", now 34" D. Fir, S. 77° E. 9.9 ft., shows good scar.
30", now 36" D. Fir, S. 87° W. 9.9 ft., shows good scar.

Set - 3/4" X 30" Iron Rod on North Side of Corner Tree.

Note - All BT's. tagged and O. K.

133

1/4 Corner to Sections 25 and 30, R. 9 & 10 W.

Found - Old scribed stake "1/4 S" visible & 3/4" I. Pipe, badly rusted.
36" Cedar, now Snag, N. 48° W. 147.8 ft., scribe visible.
N. E. BT. falls in logged area and skid trails.

134

(continued over)

John M. Powell
Frank Jones & Joe Brady
Adpril & May, 1967
C. S. File No. 54/32

Fd. OK
11/89
G. P. Riley
C.S. 63/61