

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 31 S. T. S. R. 9 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

(continued)

Set - Brass Cap at  $\frac{1}{4}$  Corner Mkd: County Surveyor's Office, 1967

R	T 31 S	R
10 $\frac{1}{4}$ S	25   S 30	9
W		W

New BT's: 12" D. Fir S. 29° W. 18.6 ft. mkd.  $\frac{1}{4}$  S25 CS BT.  
10" Cedar N. 51° E. 14.5 ft. mkd.  $\frac{1}{4}$  S30 CS BT.

135

Section Corner to Secs. 30 & 31, R9W. & Secs. 25 & 36, R10W.  
Found - 10", now 28" D.Fir, N. 52 $\frac{1}{2}$ ° E. (Rec. N. 50° E.) 206.6 ft., shows good scar.

10", now 28" D.Fir Snag, S. 45° E. 37.0 ft., opened earlier, "R9" visible.

8", now 19" D.Fir, N. 77° W. 194.7 ft., shows good scar.  
No trace of S.W. BT.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1967

R	T 31 S	R
10 S	25   S 30	9
W	S 36   S 31	W

New BT's: 14" D.Fir N. 63° E. 78.5 ft. mkd. T31S R9W S30 CS BT.  
10" D.Fir S. 67 $\frac{1}{2}$ ° E. 51.1 ft. mkd. T31S R9W S31 CS BT.  
17" Pine S. 43° W. 18.7 ft. mkd. T31S R10W S36 CS BT.

136

Sec. Cor. to Secs. 19 & 30, R9W. & Secs. 24 & 25, R10W.  
Found - 46" D.Fir, now 46", N. 11 $\frac{1}{2}$ ° E. 14.0 ft., scribe visible, "S19 BT". Also 1941 penny nailed to tree.

24" Cedar, now 24", S. 31° E. 26.8 ft., scribe visible, S30 BT,  
Scribing apparently done with knife.

Ireneed this corner by using LaFlamme's 1959 renewal, see copy in file.  
Said surveyor set this corner by using two original trees which are not there at this time, 2 Hemlocks, one was a snag, the other down.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1967

R	T 31 S	R
10 S	24   S 19	9
W	S 25   S 30	W

New BT's: 11" Hemlock S. 74° W. 42.1 ft. mkd. T31S R10W S25 CS BT.  
25" D.Fir N. 50° W. 45.7 ft. mkd. T31S R10W S24 CS BT.

Note - This corner previously renewed & recorded in Coos County.

137

$\frac{1}{4}$  Corner to Sec. 7, R9W. and Sec. 12, R10W.

Found - No trace of original Stone nor Trees.

72" D. Fir, now stump, S. 73° W. 33.0 ft. scribe visible  $\frac{1}{4}$  BT".  
Unrecorded Iron Pipe at corner.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1967

R	T 31 S	R
10 $\frac{1}{4}$ S	12   S 7	9
W		W

New BT's: 5" Hemlock S. 23° W. 30.2 ft. mkd.  $\frac{1}{4}$  S CS BT.  
26" Cedar Stump S. 12 $\frac{1}{2}$ ° E. 37.1 ft. mkd.  $\frac{1}{4}$  S 7 CS BT.

Note - This corner lies in bottom of small ravine, running N. & S.  
This corner prev. renewed & recorded in Coos County.

138

$\frac{1}{4}$  Corner to Sections 19, R9W. & Sec. 24, R10W.

Found - Orig. 8", now 12" D. Fir, N. 62° E. 8.6 ft., shows scar.

Orig. 30", now 34" D. Fir, now down, N. 78° W. 26.4 ft.,  
opened for scribe "4" S".

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1967

R	T 31 S	R
10 $\frac{1}{4}$ S	24   S 19	9
W		W

New BT: 7" Hemlock S. 85° W. 21.6 ft. mkd.  $\frac{1}{4}$  S24 CS BT.

139

$\frac{1}{4}$  Corner to Section 18 and 19.

Found - No trace of Iron Pipe set in 1961, See Ren. #17.

Orig. 24" D. Fir, N. 28° E. 28.4 ft., tree opened earlier,  
scribe marks visible.

26", now 26" D. Fir Snag, S. 24° E. 58.1 ft., tree shows good scar.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1967

T 31 S	R 9 W
$\frac{1}{4}$ S	18
S	19

New BT: 8" Cedar S. 50° E. 14.0 ft. mkd.  $\frac{1}{4}$  S19 CS BT.

Note - This corner lies about 250.0 ft. E. of Standly Creek.

John M. Powell  
 Frank Jones & J. Brady  
 May, 1967  
 C. S. File No. 54/32