

Douglas County Surveyor's Record of
Government Corners Renewed

T. 31 S. T. S. R. 9 W. R. W. W. M.

KOKE-CHARMAN CO., EUGENE, ORE. 97401

146

A. P. on S. Line T.31-9W. which lies 349.8 ft. E. of
Sec. Cor. to Sections 5 & 6 only, T32-9W.
Found - 36", now 38" D. Fir, N. 11° W. 16.5 ft., shows good scar.
36", now 38" D. Fir, S. 45° W. 11.2 ft., bark scribe
visible, "T32 R W", broken in half.
GLO Brass Cap, properly mkd. in 1917.
New BT: 18" D. Fir S. 26° W. 24.0 ft. mkd. "AP CS BT".

147

Angle Point on S. Line of T31S-R9W. 260.7 ft. E. of Sec. Cor. 5 & 4,
T32-9W.
Found - G.L.O. Brass Cap, properly mkd. in 1917.
18" Chinquapin, now 18" Snag, N. 45° E. 38.9 ft., butnt,
no scribe visible.
8" Yew, now 8", S. 27° W. 19.1 ft., faint scribe marks,
not legible.
New BT's: 53" D. Fir mkd. AP CS BT, S. 58° E. 23.9 ft.
8" Chinquapin N. 83° W. 29.8 ft. mkd. AP CS BT.

148

1/4 Corner to Sections 5, T31-9W. & Sec. 32, T30-9W.
This corner renewed by LaFlamme in 1966, See Ren. #124.
(Tagged all BT's. scribed by LaFlamme)
Found - Orig. 24" D. Fir, now Snag, S. 37° E. 17.8 ft., scribe visible.
24" D. Fir S. 10° E. 34.0 ft. mkd. 1/4 S32 BT. (LaFlamme's Tree)
24" D. Fir N. 26° W. 13.5 ft. mkd. 1/4 S32 BT.
Post at 1/4 Corner.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 30 S R 9 W
Office 1/4 S 32
1967 S 5
This Corner in C.S. 53/53 T 31 S R 9 W

RE-RENEWED, SEE CORNER NO. #165

John M. Powell
Frank Jones & J. Brady
May, 1967
C.S. File No. 54/32

149

Sec. Corner to Sections 19 - 20 - 29 - 30.
Found - 8" Pine, now 9" Snag, shows scribing "S19 S20 S29".
10" Pine, now 10" Stob, N. 80° E. 44.8 ft., shows scribing "BT".
8", now 12" Pine, S. 75° E. 8.6 ft., shows scribing.
5", now 10" Pine, S. 45° W. 1.3 ft., shows scribing "3".
5", now 10" Pine, N. 60° W. 51.5 ft., shows scribing "S19".
Set - Brass Cap at Cor. Mkd: County Surveyor's T 31 S R 9 W
Office S 19 | S 20
1967 S 30 | S 29
New BT: 10" D. Fir N. 3° E. 15.2 ft. mkd. T31S R9W S20 CS BT.

150

1/4 Corner to Sec. 31, T31-9W. & Sec. 36, T31-10W.
Found - Stone, no markings. (Stone, 22x14x6, as recorded)
Orig. 8", now 18" D. Fir, N. 82° E. 23/8 ft., shows scar.
Orig. 8", now 20" D. Fir, N. 63° W. 11.9 ft., opened & found
scribe "S".
Set - Brass Cap at Cor. Mkd: County Surveyor's T 31 S
Office, 1967 R10W S 36 S 31 R9W
Rescribed: 18" D. Fir N. 82° E. 23.8 ft. (Orig.) mkd. 1/4 S31 CS BT.
New BT: 14" D. Fir N. 46 1/2° W. 16.8 ft. mkd. 1/4 S36 CS BT.
Note - Corner lies 43 ft. south of creek. 6/6/67

151

Township Corner to Sec. 6, T32-9W. and Sec. 1, T32-10W.
Found - U.S. GLO Brass Cap, 1917, properly marked.
16", now 20" Fir, S. 23° W. 15.7 ft., shows good scar.
16" Fir, found to be Pine Snag, S. 24° E. 39.6 ft.,
opened for scribing "R9".
New BT: 23" Fir S. 43° E. 37.8 ft. mkd. T32S R9W S6 CS BT.
Note - This corner filed in C.S. File No. 54/44 6/6/67