

Douglas County Surveyor's Record of  
Government Corners Renewed

T 31 T. S. R 9 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

FO. OK BY K. DeGroot, 6/01 M 137-13

157

1/4 Corner for Secs. 1 and 2.

Found - A 1" x 36" I.P. with brass cap loosely set 12" above ground and leaning, marked "County Surveyors Office: T31S 1/4 S2, S1 R9W 1964. Ren. #30

A 6" now 7" Chinquapin (20 ft. High snag) bears S.42°E., 28.4 ft. (Rec. S.50°E., 28.4 ft.), opened healed blaze to read scribing "1/4".

A 8" now 10" Fir bears S.42°W., 30.4 ft. (Rec. S.45°W., 30.4 ft.) I use distances to these O.B.T.'s to reset brass cap 1.2 ft. North. R. B. Kimberling  
S. J. Flause  
Doug. Co. Surveyors Office

A 7" now 8" Hemlock bears N.77°E., 19.7 ft. (Rec. N.69°E., 20.4 ft.) with visible scribing "1/4 S1 CS BT" in partially healed blaze. Dec. 8, 1977  
C.S. 59/42

A 8" now 9" Hemlock bears S.74°W., 30.1 ft. (Rec. S.78°W., 29.9 ft.) with visible scribing "1/4 S2 CS BT" in a partially healed blaze.

Set - Reset Brass cap, 2" above ground from O.B.T.'s using distances to control location. Stamped cap to read "T 31 S"

1/4 S2 S1  
R 9 W  
Reset 1977  
1964

No new accessories. Corner is 75 ft. south of a dry creek bed on steep north slope, 50 ft. west of west edge of clearcut unit, 750 ft. north of 12 mile road.

158

1/4 Corner for Secs. 2 and 11.

Found - A 4"x4" squared post 19" above ground with faint scribe marks "11" on north face. A 1" I.P. in west edge of wooden post with brass cap set 12" above ground marked "County Surveyors Office" T31S R9W 1/4 S S2 S11 1967. Ren. #65

A 16" Fir 15 ft. high snag bears N.25°E., 6.6 ft. with an opened blaze and visible scribing "2".

A 16" Fir bears S.22°W., 13.2 ft. with a well healed blaze and 6" high "X" carved in north face, and 6" high "-M carved in west face. R. B. Kimberling  
S. J. Flause  
Doug. Co. Surveyors Office

A 8" now 9" Hemlock is uprooted, orig. position approx. bears N.47°W., 21.4 ft. with partially healed double blaze and visible scribing "1/4 S2 CS BT". Dec. 8, 1977  
C.S. 59/42

New Accessories:

A 9" Cedar bears N.29°W., 28.4 ft. double blazed and marked "1/4 S2 CS BT".

Center 1/4 corner Sec. 3

Set - 5/8" x 30" I. Rod and Aluminum Cap

BT's - 28" Fir bears S.64°W., 15.8 feet

33" Fir bears S.72°E., 44.3 feet

159

Johnstone, H.  
For: Rsbg. Lumber Co.  
Nov. 1979  
M 80 - 55

1/4 Corner for Secs. 2 and Sec. 35 of T.30-9

Set - 5/8" Iron rod with aluminum cap.

BT's - 8" Hemlock bears S.22°W., 13.7 ft. scribed 1/4 S2 BT.

12" Fir bears N.6°E., 9.5 ft. scribed 1/4 S35 BT.

160

1/80

Romanso E. Ware  
For: Roseburg  
Lumber Co.  
Jan. 1980  
M 79 - 18

Section corner for Secs. 2 and 3; and 34 & 35 of T.30-9

Set - Chisled "X" in rock

BT's - 12" Fir bears N.28°E., 43.2 ft. scribed T30S R9W S35 BT.

36" Cedar bears N.40°W., 28.2 ft. scribed T30S R9W S34 BT.

12" Hemlock bears S.16°E., 25.7 ft. scribed T30S R9W S2 BT.

20" Cedar bears S.56°W., 54.3 ft. scribed T30S R9W S3 BT.

161