

Douglas County Surveyor's Record of
Government Corners Renewed

T 31 T. S. R 9 R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

C O N T - - - -

(1/4 Cor. Sec. 5; and 32 of T.30-9)

165

Stephen J. Flause,
Deputy, Doug. Co.
Surveyors Office
T. Plouff; K. Mosely
April 7, 1981
C.S. 61/19

scribing visible.
1893, A fir, 30" now the remains of a large burned & rotted fir stump bears N. 14 1/4°W., 84.5 ft. No blazes or scribing apparent (rotted away).
A D. Fir, 22" now a dead 26" DBH D. fir bears S.10°W., 34.7 ft (rec. S.12°W., 34.7 ft.) Tree has burned open blaze with no legible scribing. Ren. #124
A D. fir, 22" now a 38" DBH D fir, dean, bears N.25°E., 13.5 ft. An opened blaze has the scribing 1/4 S32 visible. Ren. #124

Monument location is accepted as found.

New accessories:

A boat spike in a 12" diam., 12" tall burled fir stump bears N.06 3/4°W., 9.3 ft. Boat spike driven into the top of said stump is stamped BO 2.
A spike in a D. fir stump 20" diam., and 21" tall bears S.59 1/2°W. 42.1 ft. Spike stamped BO 1.
A 8" DBH madrone bears N.16°W., 81.9 ft. & is bark scribed 1/4 S32 CS BT.

All accessories are tagged with DCSO BT tags.

4/7/81

1/4 Corner for Secs. 3 and 2

166

Found - 1" x 30" I.P. with brass cap properly marked attached, lying alongside root wad of a large fir windfall. Ren. #58
Orig. 10" madrone, now 12" stump hole with small portion of the eastern edge of the stump remaining.
Orig. 16" madrone, now 16" stump with center and face areas gone.
6" madrone, now 6" snag 4 ft. tall with scribed "1/4 S2 CS BT" visible in double blaze. Ren. #58
8" madrone now 10" stump with portion of healed over blaze visible. Ren. #58
Set - I reset the found brass cap using all four found BTs. Stamped "1982" on brass cap.
Bearings and distances used are as follows:
Orig. 10" madrone, now stump hole bears N.32°E., 22.2 ft. (rec. 22.4 ft.)
Orig. 16" madrone, now 16" stump bears N.29°W., 17.4 ft. (17.8')
6" madrone bears N.50°E., 14.4 ft. (Rec. N.51°E.)
8" madrone now 10" stump bears N.75°W., 29.9 ft. (Rec. N.77°W.)
Brass cap protrudes approx. 8" out of ground.

New Accessories:

7" fir scribed "1/4 S3 CS BT" in double blaze bears N.10°W., 39.5 ft.
Set spike in top of 8" madrone now 10" stump bears N.75°W., 29.8 ft. to spike.
48" fir scribed "1/4 S2 CS BT" in double blaze bears S.87°E., 25.1'

5/17/82

1/4 Corner for Section 35 only. (south)

167

Found - Orig. 18" x 12" x 6" basalt stone with "1/4" on the north face, now 18" x 11" x 6" iwth "1/4 on a face, lying at the approx. corner location. The stone was found earlier by a BLM crew somewhere in a slide area below the corner locat. and moved to the approx. correct location. The 1917 brass c appears to have been buried by slide.
Orig. 36" fir, now 42" with good scar.
11" fir per Ren. #120, now 11" snag approx. 30 ft. tall with scribed "1/4 S35 CS BT" visible in unhealed blaze.
Set - At record bearing and distance from both remaining BTs, I set a 1" x 30" iron pipe with brass cap attached marked: Douglas Co Surveyor T31S 1/4 S35 R9W 1982.
Orig. 36" now 42" fir bears S.60°E., 27.1 ft.
11" fir, now 11" snag bears N.80°W., 78.1 ft.

Corner is set in a steep bank and original stone was placed on east side of new monument.

New BTs - 10" maple scribed "1/4 S35 CS BT" in double blaze bears N.22°E. 73.5 ft.

21" fir, scribed "1/4 S CS BT" in single blaze bears S.88°W., 52.8

Douglas Co Surveyor Office bearing tree tags on all trees.

Gregory Quibell, Deputy
Doug. Co. Surveyors
Office
Karen Reed; John Powell
C.S. 61/36
May 17, 1982

Gregory Quibell, Deputy
Doug. Co. Surveyors Off.
Karen Reed; John Powell
Sept. 16, 1982
C.S. 62/1