

Douglas County Surveyor's Record of
Government Corners Renewed

31 T. S. 9 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 91881

Cor. Secs. 4, 5, 8, & 9

187

Found - County 1967 BCIP (Ren #123)
36" fir stump bears S.67°W., 63.8' w/vis. scrb
39" fir stump bears S.84°E., 38.1' w/vis. scrb
28" hemlock stump, badly rotted, bears N.7°W.,
59.6' w/vis. scrb
29" cedar snag is now blowdown.
New - 13" D.Fir bears N.11°W., 22.9'
10" D.Fir bears N.58°E., 11.2'

Jerry Estabrook
For: Swanson Group

1/4 Cor. Secs. 4 & 5

188

Found - GLO corner tree, vis. scribe E Side (Ren. #64)
County BCIP bears N.68°16'20"E., 3.18'
24" D.Fir stump bears N.53°E., 9.9' (GLO)
New - 15" D.Fir bears N.30°W., 23.5'
15" D.Fir bears S.39°W., 41.2'
17" D.Fir bears S.3°E., 38.5'

6/2005
M148-32

1/4 Cor. Secs. 4 & 10

189

Found - 48" D.Fir corner tree blown down, BCIP set by
County in C. S. 54/32 (Ren #54) destroyed.
Set - 3/4"x36" I.Rod w/3" alum. cap at distance-distance
intersect from GLO BTs.
Note - All found bearings to record BTs per C.S. 54/32
seem to differ from rec bearings by 5°± left
Fd BTs - 36" cedar bears N.85°W., 10.6' W/vis. face (GLO)
(held dist.)
30" cedar bears S.13°W., 26.4' (GLO) (held dist.)
22" cedar bears N.43°E., 43.3' w/vis. face (CS
54/23)
16" cedar bears S.14°W., 21.9' (C.S. 54/23)
New BT - 10" D.Fir bears S.58°E., 28.4'

1/4 Cor. Secs. 25 & 36

See Ren #191

190

Douglas Co. Surveyors Office - Randall W. Smith, Deputy
- Stephen J. Flause - 4/23/2009 - C.S. File 67/28-31

Look for not found.
Found cut line with blazed line searched numerous trees
and looked for corner stone. Nothing found.

1/4 Cor. Secs. 25 & 36

191

David Edwards - For: Plum Creek Timberlands - 5/2009 -
M159-23

Set - 5/8x30" steel rebar w/2 1/2" dia., alum. cap
(properly mkd) at proportionate position.
14" dia., fir bears N.62°E., 21.1 ft.
17" dia., fir bears N.68°W., 8.92 ft.
No trees available in sec. 36
Set 6' steel posts 2' East & 2' West.

Orig. Corner
Searched for
by D.C.S.O. &
D.E.