

Douglas County Surveyor's Record of
Government Corners Renewed

32 T. S. 1 R. W. W. M.

KOYE-CHAPMAN CO., EUGENE, ORE. 97195

September 1949

Witnesses

Herb Northcraft }
Ted Schattenkerk }

C.S. FILE 40/214

Art Boyer - Surveyor

Art Boyer surveyor }
Geo. Hinsdale } Wit.
Don Smith }
July 31, 1952 }
Drawer #41 }
Envelope #59 }

NORTH 1/4 COR. SEC. 3

~~RENEWED~~ Set this cor. mid dist. bet. NW cor. and NE cor. of Sec 3, which falls 218.2 ft. Westerly from sec. cor. 34-35, T 31 S, R 1 W. Set a 4" x 4" oak post in a mound of rocks 18" high for cor. Cor. is on a hillside sloping to the North. Bark blazed and scribed the following trees:

30" Fir which bears S 46° W 8.0 ft., scribed 1/4 S 3 B T 1581 #41

14" Fir which bears S 48° E 37.2 ft., scribed 1/4 S 3 B T 1581.

1/4 COR. BET. SECS. 3-4

Found Orig. Madrone B.T., N 65° W 4.0 ft. and an old decayed Oak, orig. B. T. which bears N 82° E 34 ft.; there is a live oak tree growing out of the decayed Oak B. T. which I scribed

Oak - scribe 1/4 S 3 B T 1581

12" Oak bears N 76° E 4.5 ft. scribed 1/4 S 3 B T 1581.

This cor. is on a 48° slope to the West 300 ft. E of creek and 400 ft. approx. N of a road and on edge of second rocky bluff from the West. There is an old U.S.F.S. tin yellow tag here.

1/4 COR. BET. 3 - 10.

Found orig. maple B.T. in Sec. 10 for this cor. It had been recently knocked downward was still alive; cut out the scribe marks which were plain although the tree had grown very little. Set a mound of rocks here and blazed and scribed the following.

18" White Fir s 70° W 16.5 ft. scribed 1/4 S 10 B T 1581.

11" Fir N 40° E 82 ft. scribed 1/4 S 3 B T 1581.

This cor. is on top of a sloping hill which faces the N and is S 35 ft. from a logging road.

1/4 COR. BET. 2-3

Searched for three days for this cor. which is supposed to be on a hill sloping to the E which is covered with loose rocks and trash, decayed limbs and small trees. There are so many loose rocks around that the orig. rock could not be located and the B. T's which were 4" and 7" fir tree could not be found.

Set this corner by proportional measurement bet. the SE and NE corners of this sec. Raised a mound of rocks, basalt, about 18" high and placed a 3" x 3" fir post for corner, from which

18" Fir bears N 78° W 28 ft. scribed 1/4 S 3 B T 1581

12" Fir bears S 37° E 17.3 ft. scribed 1/4 S 2 B T 1581.

There are many old growth fir trees with a 600 ft. radius of this corner or where it would come if it were 1/2 mi. N of the SE corner of this Sec. so it might seem that the cor. was never set.

This new cor. as set is 18 ft. W of the center of a creek and N 37° E approx. 100 ft. from a rock ledge which is about 10 ft. high and 50 ft. long N and S.

1/4 Cor. Bet. 9-16

Found the original tree, a 4" fir which has not grown since being marked by surveyor, it was properly scribed, the 1/4 S was O. K. the B. T. was very distinct, but was upside down; the figure 16 was not clear. Found the original rock and placed five other rocks the same size as the corner rock in pile around it.

From which

A 24" cedar bears N 63° 30' E 21.0 ft. marked 1/4 S 9-1581 E.T. #45

This corner is 2657.2 ft. from the N.W. cor of section 16 (the recorded distance is 2654.52 ft.) it is at the east side of a flat about 100 ft west of the beginning of a slope up toward the east, the ground at the corner is flat and slopes at about a 7° rise to the south which begins about 200 ft. south. There are old growth trees around this corner that were big when the small wit. was marked. The tree in sec 9 was entirely gone it was a 5" tree.

1

2

3

4

5