

Douglas County Surveyor's Record of
Government Corners Renewed

T. 32 S. T. S. R. 1 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORG. 21881

13

$\frac{1}{4}$ Corner to Sec. 6, T32-1W. & Sec. 1, T32-2W.
Found - Orig. 6", now 14" Cedar N.21 $\frac{1}{2}$ °E. 2.0 ft., shows good scar.
Orig. 40", now 46" Sugar Pine (snag) shows good scar N.84°W. 20.1 ft.
Also find Stone as recorded.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1963
 $\frac{1}{4}$ S 1/S 6 T 32S
R2W RLW
New BT: 6" Cedar bears S.62°W. 56.0 ft. scribed $\frac{1}{4}$ S1 CS BT.

14

Sec. Cor. for Secs. 18 & 19, T32-1W. & Secs. 13 & 24, T32-2W.
Found - Orig. 6", now 8" Yewwood N.50°E. 9.9 ft., shows good scribing.
No other Orig. BT's. Also find Stone as recorded. #59
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1963
S24 | S19 T32S
S13 | S18 RLW
New BT's: 18" Yewwood bears S.40°E. 18.3 ft. scribed S19 T32S RLW CS BT.
19" W.Fir bears N.55°W. 82.7 ft. scribed S13 T32S R3W CS BT.
No trees near to S. W.

15

Sec. Cor. to Secs. 6 & 7, T32-1W. & Secs. 1 & 12, T32-2W.
Found - Stone at Corner as recorded & Orig. 65", now 65" Fir Snag, shows
good bark scribing.
Orig. 15", now 18" Fir N.36°W. 7.3 ft., shows good scar.
Orig. N. E. & S. W. BT's. not found.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1963
S 1 | S 6 T32S
R2W S2 | S 7 RLW
New BT's: 25" Cedar bears N.17°E. 44.0 ft. scribed S6 T32S RLW CS BT.
12" Cedar bears S.57°W. 81.0 ft. scribed S12 T32S R2W CS BT.
5" Fir bears S.86°E. 64.6 ft. scribed S7 CS BT.

16

Sec. Cor. to Secs. 7 & 18, T32-1W. & Secs. 12 & 13, T32-2W.
Found - Orig. 14", now 16" Fir Stump shows good reverse Scribing,
N. 29° W. 20.5 feet.
Orig. 30", now 36" Fir Snag S.50°E. 29.0 ft., shows good scribing.
Orig. S.W. BT., not found. Do find stump of Orig. N.E. BT.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1963
S12 | S 7 T32S
R2W S13 | S18 RLW
Note - Logging Road 75 feet South.
New BT's: 5" Chinquapin bears N.38°W. 48.7 ft. scribed S12 CS BT.
12" Hemlock bears N.22°E. 49.6 ft. scribed S 7 T32S RLW CS BT.
5" W.Fir bears S.86°E. 68.3 feet scribed S18 CS BT.

17

Closing Corner Sections 5 and 6, T32-1W.
Found - Stone Mound at Cor. & BT's., as follows: (Ren. #9)
8" Maple S.1°40'W. 106.9 ft. Mkd: S 5 3683 BT.
5" W.Oak North 55.6 ft. Mkd: 3683 BT.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964
T32S RLW C O S 6/S 5
We did not mark new BT's, as none are close. This corner lies on
small bench between two small creeks, course E.

18

South $\frac{1}{4}$ Corner Section 32 only, T31-1W.
This corner lies 165 ft. East of the C. C. of Sections 5 & 6, T32-1W.
Found - Snag of one BT, in place, other BT. down & out of place.
 $\frac{1}{2}$ " I. P. pulled out & laying at approximatel corner.
10", now 12" W. Fir Snag N.10°W. 16.5 ft., shows scribe. This
snag 6 ft. tall. Recorded in Ren. #5. T31-1
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964
T32S RLW $\frac{1}{4}$ S 32
T32S.
New BT's: 9" W. Fir N.78°E. 54.9 ft. Mkd: S32 CS BT.
12" D.Fir N.48°W. 58.0 ft. Mkd: S32 CS BT.

James W. Byron, Deputy County Surveyor
Mike Darby and Wm. Stoffel
March 1963
C. S. File No. 53/15

Vernon "Ray" Tracy
Mike Darby and Jack Barnett
December 15, 1964
C. S. File No. 53/15

RE-RENEWED, SEE CORNER NO. #92
RE-RENEWED, SEE CORNER NO. #81
MICROFILM TO HERE 10/67