

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 32 S. T. S. R. 1 W. R.W.W.M.

MOKE-CHAPMAN CO., EUGENE, ORE. 97401

John M. Powell  
Frank Jones & W. Penley  
July, 1968  
C. S. File No. 54/71

1/2 Corner to Sections 6 and 7. 25  
Found - C. S. Brass Cap, set & marked in 1963, see Ren. #12.  
14" W. Fir, now 15", N. 60° W. 17.2 ft., scribe visible.  
22" R. Fir, now dead, S. 72° W. 12.0 ft., scribe visible. 123  
New BT: 9" D. Fir S. 53° E. 133.5 ft., mkd: 1/2 S 7 CS BT.

Section Corner to Sections 5 - 6 - 7 - 8. 26  
Found - Stone at corner, no marks found. - No trace of Orig. SW. BT. #94  
Orig. 8", now 16" D. Fir, N. 43° E. 4.0 ft., tree already opened, "5" visible.  
Orig. 12" D. Fir, now down, S. 75° E. 4.6 ft.  
Orig. 14" D. Fir, now stump, N. 45° W. 4.0 ft.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office T 32 S R 1 W  
1968 S 6 | S 5  
S 7 | S 8  
New BT's: 22" D. Fir S. 25° W. 31.2 ft. mkd. T32S R1W S7 CS BT.  
11" D. Fir S. 3° E. 17.5 ft. mkd. T32S R1W S8 CS BT.  
13" D. Fir N. 65° W. 20.6 ft. mkd. T32S R1W S6 CS BT.  
N. E. Bearing Tree O.K. and Tagged.

Section Corner to Sections 7 - 8 - 17 - 18. 27  
Found - Orig. 20", now 24" Laurel N. 16° E. 19.8 ft., shows scar.  
Orig. 18" Laurel, now stob, S. 67° E. 17.2 ft.  
Orig. 14" D. Fir, now stob, S. 51° W. 21.6 ft. (Rec. 18.5) shows good scar.  
Orig. 8" D. Fir, now stob, N. 46° W. 11.2 ft., scribe visible.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office T 32 S R 1 W  
1968 S 7 | S 8  
S 18 | S 17  
New BT's: 5" Live Oak S. 44° W. 12.1 ft. mkd. T32S R1W S18 CS BT.  
18" Cedar N. 58° W. 15.0 ft. mkd. T32S R1W S7 CS BT.  
12" Laurel S. 40° E. 40.2 ft. mkd. T32S R1W S17 CS BT.  
Orig. N.E. BT., O.K. & Tagged.

1/2 Corner to Sections 8 and 17. 28  
Found - 12" Laurel, now stob, N. 60° E. 5.4 ft., shows old face, split tree for faint reverse scribe "B".  
25" D. Fir, now stob, S. 50° W. 26.6 ft. (Rec. 24.4), tree now 24", nothing visible, possible bark scribe, badly burnt.  
This corner lies on top of ridge as called for in original notes. #78  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office T 32 S R 1 W  
1968 1/2 S 8  
S 17  
New BT's: 8" Cedar N. 46° W. 92.0 ft. mkd. 1/2 S8 CS BT.  
22" Laurel S. 78° W. 103.7 ft. mkd. 1/2 S17 CS BT.

Section Corner to Sections 8 - 9 - 16 - 17. 29  
Found - Orig. 3" S. Pine, now 10" Snag, N. 58° W. 27.7 ft., opened tree for scribe. Tree being dangerous, cut down leaving 6' stump.  
Orig. 6" S. Pine, now down, S. 32° E. 9.9 ft., prev. opened, scribe visible.  
No trace of corner stone or N.E. or S.W. BT's.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office T 32 S R 1 W  
1968 S 8 | S 9  
S 17 | S 16  
New BT's: 14" D. Fir S. 50° E. 20.3 ft. mkd. T32S R1W S16 CS BT.  
8" R. Fir East 11.1 ft. mkd. T32S R1W S9 CS BT.  
6" Live Oak N. 5° W. 10.9 ft. mkd. T32S R1W S8 CS BT.  
9" Live Oak S. 80° W. 17.8 ft. mkd. T32S R1W S17 CS BT.

1/2 Corner to Sections 6 and 5. 30  
Found - 12x10x8 Stone mkd: "1/2" on W. face.  
8", now 13" D. Fir N. 20° E. 4.0 ft., shows good scar.  
14" Laurel, now hole, S. 40° E. 5.3 ft.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office T 32 S R 1 W  
1968 1/2 S 6 | S 5  
New BT: 8" Yew S. 63° W. 14.8 ft. mkd. 1/2 S6 CS BT.  
This corner lies on N. W. slope approx. 280.0 ft. south of creek. #93