

Douglas County Surveyor's Record of

Government Corners Renewed

T. 32 S. T. S. R. 1 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

37

1/4 Corner Section 33 only, T31-1W.
 Found - 14x10x8 Corner Stone at 1/4 Cor. Mkd. with 1/4 on N. face.
 40", now 46" Cedar, S. 25° W. 39.0 ft. (Rec. S15W 34.3') shows scribing.
 36", now 38" Fir Stump, N. 3° E. 19.1 ft., opened & found scribing.
 Set - Brass Cap at 1/4 Cor. Mkd: County Surveyor's Office, 1968
 T31S RLW 1/4 S 33
 T32S
 New BT's: 14" Cedar N. 54° W. 41.2 ft. mkd: "1/4 S33 CS BT".
 12" D. Fir N. 42° E. 46.6 ft. mkd: "1/4 S33 CS BT".
 Note - This corner lies on S-W fence corner, 150.1 ft. E. of the Sec.
 Cor. of 4 & 5, T32-1W, see below, and 300' north of a road.

38

Section Corner to Sections 4 & 5, T32-1W.
 Found - Stone at Corner 18x11x8 with 4 grooves.
 10" Fir, now stob, N. 40° W. 4.6 ft., opened & found scribing "BT".
 8" Fir, now pieces of wood & a hole, S. 65° E. 5.3 ft., shows scribing.
 8" Laurel, now a stump hole, S. 18° W. 18.5 ft.
 Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1968
 T31S RLW S 33
 T32S S 5 | S 4
 New BT's: 15" D. Fir S. 21° E. 26.3 ft. mkd. T32S RLW S 4 CS BT.
 10" Y. Pine S. 65° W. 25.1 ft. mkd. T32S RLW S 5 CS BT.
 Note - This corner lies N-W fence 150.1 ft. W. of 1/4 Cor. Sec. 33, T31-1W,
 see above, 300 ft. N. of a road.

8/1/68

39

Section Corner to Sections 1 and 2, T32-1W.
 Found - Stone with 5 notches and CC.
 20", now 37" D. Fir, N. 3° W. 29.7 ft., tree opened, scribe visible.
 10", now 10" D. Fir, S. 10° E. 68.0 ft. (slope dist), shows good scar.
 15", now 20" D. Fir, 65.4 ft. (Rec. 73.3: slope dist., 77.6).
 Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1968
 T31S R S 36
 T32S 1W CC S 2 | S 1
 Doug. Co.
 Jack. Co.

Bearing Trees O. K. and tagged.
 Record Distance from Angle Point, see below, 195.4 ft., I find to be 187.0 ft.

40

Angle Point - This Corner lies 61.4 ft. W. of 1/4 Cor. Sec. 36, T31-1W,
 which is a Brass Cap, 1923, in good condition, tagged BT's.
 Found - No trace of Stone at Corner.
 Orig. 12" D. Fir, now dead, S. 25° E. 13.0 ft. (Rec. S32E 14.5)
 scribe visible "AP BT".
 Orig. 16", now 16" D. Fir N. 71° E. 36.3 ft.
 Set - Brass Cap at Angle Point Mkd: County Surveyor's Office, 1968
 T31S RLW A P
 T32S
 Doug. Co.
 Jack. Co.
 New BT: 38" D. Fir S. 49° E. 22.0 ft. mkd. "AP CS BT".

41

Township Corner -
 Found - 30x15x6 Stone at corner with 6 notches on N-S-E-W sides.
 36" D. Fir, now snag, N. 10° E. 38.3 ft., bark scribe, good face.
 15" D. Fir, now down, N. 32° W. 15.2 ft.
 35" D. Fir, now down, S. 81° W. 51.5 ft., shows good scar.
 35" D. Fir, now stump, S. 45° E. 41.6 ft.
 Set - Brass Cap at Twp. Cor. Mkd: County Surveyor's Office, 1968
 R T 31 S R Doug. Co.
 1 S 1 S 31 1
 W S 6 E
 T 32 S Jack. Co.
 New BT's: 8" Maple N. 8° W. 48.0 ft. mkd. T32S RLW S1 CS BT.
 9" D. Fir N. 75° E. 49.6 ft. mkd. T31S R1E S31 CS BT.
 6" yew S. 23° E. 25.3 ft. mkd. T32S R1E S6 CS BT.
 This corner 20.0 ft. west of ravine.

42

Township Corner - Closing Corner.
 Found 35x15x5 Stone mkd: CC and 6 notches
 60", now 64" D. Fir, S. 30° W. 1.3 ft., shows good scar.
 30" D. Fir, now rotten stob, N. 41° E. 18.5 ft.
 40" D. Fir, now rotten stob, N. 74° W. 27.7 ft.

(Continued over)

John M. Powell
 Frank Jones & W. Penley
 August, 1968
 C. S. File No. 54/71