

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 32 S. T. S. R. 1 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

(continued)

Set - Brass Cap at Twp. Cor. Mkd: County Surveyor's Office 1968  

R	T 31 S	Doug. Co.
	1 S 36	S31 R
	W S 1	CC 1E
	T 32 S Jack. Co.	

New BT's: 9" D. Fir N. 2 $\frac{1}{2}$ ° E. 11.5 ft. mkd. T31S R1E S31 CC CS BT.  
 9" D. Fir N. 26° W. 17.2 ft. mkd. T31S R1W S36 CC CS BT.  
 8/9/68

Section Corner to Sections 35 & 36 only, T31-1W. 43  
 Found - 36", now 39" D. Fir, N. 20° W. 2.6 ft., shows good scar.  
 28", now 32" D. Fir, N. 72° E. 11.9 ft., shows good scar.  
 GLO Brass Cap at Corner, properly marked in 1922.  
 New BT: 25" D. Fir S. 60° W. 24.5 ft. mkd: T32S R1W S 2 CS BT.  
 Note - This corner lies 50.5 ft. E. of Angle Point, See Ren. #44.

Angle Point 50.5 ft. West of Section Corner to Secs. 35 & 36 only, T.31-1W. 44  
 Found - 6x12x6 Stone mkd. with notches and AP on north face.  
 16" D. Fir, now down, N. 40° E. 4.6 ft. scribe visible, "AP BT".  
 24", now 26" D. Fir, N. 36° W. 21.8 ft., shows good scar.  
 Set - Brass Cap at Angle Point Mkd: County Surveyor's Office 1968  

T 31 S R 1 W
A P
T 32 S

New BT: 22" D. Fir N. 41° E. 19.1 ft. scribed "AP CS BT".  
 Note - This corner lies 50.5 ft. west of Sec. Cor., Ren. #63.

$\frac{1}{4}$  Corner to Sections 9 and 16. 45  
 Found - No trace of Corner Stone or S.W. BT.  
 24", now 26" Cedar, N. 63 $\frac{1}{2}$ ° E. 21.0 ft., scribe visible " $\frac{1}{4}$ S6 BT".  
 South of line, old logging. See Ren. #5  
 Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1968  

T 32 S R 1 W
$\frac{1}{4}$ S 9
S 16

New BT: 13" Double Maple S. 50 $\frac{1}{2}$ ° E. 92.5 ft. mkd:  $\frac{1}{4}$  S16 CS BT.  
 Note - This corner lies about 190' E. of small spring branch.

$\frac{1}{4}$  Corner to Sections 19 and 20. 46  
 Found - Orig. 35", now 37" D. Fir, N. 80° E. 7.3 ft., bark scribed " $\frac{1}{4}$  S BT".  
 Orig. 26" D. Fir, now down, N. 60° W. 5.9 ft., found scribe marks.  
 Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1968  

T 32 S R 1 W
$\frac{1}{4}$ S 19   S 20

Reblzd. & Resrbd: 37" D. Fir N. 80° E. 7.3 ft. mkd. " $\frac{1}{4}$  S20 CS BT".  
 New BT: 14" Fir N. 89° W. 8.0 ft. mkd.  $\frac{1}{4}$  S19 CS BT.

$\frac{1}{4}$  Corner to Section 3 only, T32-1W. 47  
 Found - Mound of Stone & Stake at Corner, See Ren. #1, T32-1W.  
 30", now 24" D. Fir, S. 46° W. 8.0 ft., bark scribed " $\frac{1}{4}$  S3 1581BT".  
 14", now 14" D. Fir, S. 48° E. 37.2 ft., shows good scar.  
 Set - Brass Cap at  $\frac{1}{4}$  Cor. Mkd: County Surveyor's Office 1968  

T 31 S R 1 W
$\frac{1}{4}$ S 3
T 32 S

Reblzd. & Resrbd: 24" D. Fir S. 46° W. 8.9 ft. mkd: " $\frac{1}{4}$  S3 CS BT".

$\frac{1}{4}$  Corner to Section 35 only, T31-1W. 48  
 Found - GLO Brass Cap at  $\frac{1}{4}$  corner, properly marked in 1922.  
 10", now 12" Maple, N. 42° E. 7.9 ft., shows good scar.  
 14" D. Fir, now stob, N. 72° W. 23.1 ft., shows good scar.  
 New BT: 26" D. Fir N. 22° W. 20.0 ft. mkd.  $\frac{1}{4}$  S35 CS BT.  
 Note - This corner lies 37.0' E. of A.P. Cor. & about 10' E. of draw.

John M. Powell  
 Frank Jones & W. Penley  
 August, 1968  
 C. S. File No. 54/71