

Douglas County Surveyor's Record of
Government Corners Renewed

T 32 T. S. R 1 R.W.W.M.

MOKE-CHAPMAN CO., EUGENE, ORE. 21881

56

Section Corner for Secs. 16, 15, 21 and 22.

Found - One bearing tree remaining, all other bearing trees and the brass cap have been destroyed by construction of a skid trail. The corner point, located at record bearing and distance from the NE bearing tree marked by Cadastral Engineers in 1955:

A 13" now 16" D. Fir bears N.59 3/4°E., 24.4 ft., with scribing "32S R1W S15 BT" visible on partially healed blaze.

Falls on a steep slope.

We set - Brass cap as a witness corner, 30.0 ft. North of the true corner.

mkd. COUNTY SURVEYORS T 32 S R 1 W
OFFICE Wit. Cor.
1974 S 16 | S 15
S 21 | S 22

30 Ft. South to
Cor.

We mark the following bearing trees for the witness corner:

13" D. Fir bears N.82°W., 9.0 ft. scribed "WC T32S R1W S16 CS BT"

36" D. Fir bears N.53°E., 55.6 ft. scribed "WC T32S R1W S15 CS BT".

1/4 Corner for Secs. 17 and 20.

Set - Brass Cap

New BT's - 56" D. Fir, bears N.7°W., 8.3 ft. scribed 1/4 S17 BT.
8" Incense Cedar, bears S.38°30'W., 6.9 ft. scribed
N 1/4 S20 BT.

RE-RENEWED, SEE CORNER NO. #74

57

Section corner for Secs. 17, 16, 20 and 21.

Set - Brass Cap.

New BT's - 13" D. Fir, bears S.50°30'W., 18.5 ft. scribed
T32S R1W S20 BT.

35" D. Fir, bears S.20°E., 13.7 ft. scribed T32S
R1W S21 BT.

42" D. Fir, bears N.16°E., 27.1 ft. scribed T32S
R1W S16 BT.

6" Incense cedar, bears N.48°W., 15.3 ft. scribed
S17 BT.

RE-RENEWED, SEE CORNER NO. #75

58

Burton W. Holt
for Sun Studs
August 1974
M 49 - 71

Section Corner for Secs. 18 and 19; and Secs. 13 and 24, T32-2.

Found - 1963 County Surveyors Brass cap. Ren. #14

8" Yew, bears N.50°E., 9.9 ft.

18" Yew bears S.40°E., 18.3 ft.

20" W. Fir bears N.50°W., 32.7 ft.

New BT - 6" Fir, bears S.75°W., 22.6 ft. scribed T32S R2W S24 BT.

RE-RENEWED, SEE CORNER NO. #112

59

1/4 Corner for Sec. 19 and Sec. 24 of T.32-2,

Set - 2 1/2" x 30" I.P. with brass cap stamped T32S R2W S24, R1W S19
1/4 S 1976 OLS 536.

BT's - 8" D. Fir bears N.29°W., 18.4 ft. scribed T32S R2W S24 BT.

6" Cedar bears S.2°E., 3.1 ft. scribed T32S R1W S19 BT.

RE-RENEWED, SEE CORNER NO. #100

60

1/4 Corner for Secs. 18 and 19.

Set - 2 1/2" x 30" I.P. with brass cap stamped T32S R1W 1/4 S 18 S 19
OLS 536 1976.

New BT's - 8" Pine bears N.43°W., 28.8 ft. scribed T32S R1W 1/4 S18 BT.

6" Fir, bears S.63°E., 16.9 ft. scribed T32S R1W 1/4 S19 BT.

*FO. OK BY R. WYTCHELEY, MAY 2004
M144-49*

61

Center 1/4 Corner for Sec. 19

Set - 2 1/2" x 30" I.P. with brass cap stamped T32S R1W C 1/4 S19
OLS 536 1976.

BT's - 8" D. Fir bears S.28°W., 17.3 ft. scribed C 1/4 S19 BT.

12" Fir bears N.3°W., 17.4 ft. scribed C 1/4 S19 BT.

62

Gary Langlitz, County Surveyor Office
P. Earle
C.S. 56/51
6/4/74

JAN 75

Glenn S. Baughman
For: U.S. Forest Service
Tiller Land Survey #20
December 1976
M 56 - 69