

Douglas County Surveyor's Record of  
Government Corners Renewed

T 32

T. S.

R 1

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Glenn S. Baughman  
For: U.S. Forest Service  
December, 1976  
M 56 - 69

Sec. Cor For Secs. 19 and 30; and Secs. 24 and 25 of T32-2  
Found - 1970 brass cap set by Shaner Engineering.

- 30" D. Fir bears S.24°W., 54.3 ft.
- 14" W. Fir bears S.30°E., 40.5 ft.
- 10" W. Fir bears S.54°W., 51.3 ft.
- 24" W. Fir bears N.41°W., 29.0 ft.
- 12" W. Fir bears N.24°W., 46.6 ft.
- 5" Yew bears N.10°30' E., 60.0 ft.
- 26" Cedar bears N.25°E., 47.7 ft.

Note: this corner lies in Jackson Co. Found: Sec. Cor by Jackson CSO lies S.64°41'19"W., 0.94 ft. from Shaner corner.

See also: C.S. 63/62 for Jackson Co. DATA

1/4 Corner for Secs. 19 and 30.

- Found - 1964 Jackson Co. brass cap.
- 20" Fir snag bears S.35°W., 9.7 ft.
- 12" Fir bears S.70°W., 24.6 ft.
- 30" Fir (down) bears N.88°E., 28.5 ft.
- 12" Fir bears N.48°W., 34.3 ft.

Note: this corner lies in Jackson Co.

Dec. 1976

Sec. Cor. for 7 and 18; and Secs. 12 and 13 of T32-2.

Found - 1963 Doug. Co. Surveyors brass cap. Ren. #16

- 6" Chinquapin (dead) N.38°W., 48.7 ft.
- 20" W. Fir bears N.22°E., 49.6 ft.
- 36" Fir (snag) bears S.50°E., 29.0 ft.
- 6" W. Fir (stob) bears S.86°E., 68.3 ft.

- New BT's - 10" Fir bears N.85°W., 23.3 ft. scribed T32S R2W S13 BT w/br. washer LS 536.
- 9" Fir bears S.34°E., 21.6 ft. scribed T32S R1W S18 BT w/br. washer LS 536.
- 10" Fir bears N.15°W., 62.3 ft. scribed T32S R2W S12 BT w/br. washer LS 536.

12/76

1/4 Corner for Sec. 18 and Sec. 13 of T32-2.

Set - 2" x 30" I.P. with brass cap stamped T32S R2W 1/4 13/18 R1W OLS 536 1976.

New BT's - 12" Fir bears S.53°W., 31.2 ft. scribed 1/4 S13 BT.

24" Inc. Cedar bears N.35°E., 17.3 ft. scribed 1/4 S18 BT.

12/76

Section Corner for Secs. 10, 11, 15 and 14.

Found - 1955 GLO brass cap on a 2" I.P. firmly set.

- A dead and down Hemlock with scribe visible, the root depression of which bears record N.4 1/2°W., 53.5 ft.
- A douglas Fir, 24", with healed blaze bears N. 83 1/2°E., 51.7 ft. (Rec. N.83 1/2°E., 52.8 ft.)
- A Hemlock, dead and standing with unhealed blaze and scribe visible bears S.41°E., 33.7 ft. (Rec. S.41°E., 35 ft.)
- A Hemlock, dead and standing with scribe visible in unhealed blaze bears S. 74 1/2°W., 63.7 ft. (Rec. S.74 1/2°W., 64 ft.)

I perpetuate the corner position by taking the following new bearing tree and place a brass washer bearing my registration No. in the lower blaze.

- A D. Fir, 6" marked "T32S R1W S10 BT" bears N. 30°W., 8.6 ft.
- A Hemlock 6" marked T32S R1W S 14 BT" bears S. 17 1/2°E 12.3 ft.
- A D. Fir 6" marked "T32S R1W S 15 BT" bears S. 38 1/2°W., 20.9 ft.

1/4 Corner for Sections 16 and 15.

Found - A 1955 GLO brass cap on a 1" I.P. firmly set.

- An orig. BT, a D. Fir snag 8" bears N. 76 1/2°W., 16.9 ft. (Record N.77°W 15.6 ft.)
- A D. Fir stump 33" bears S. 55 1/2°E., 36.2 ft. (Rec. S.55 1/2°E., 36.3 ft.)
- A D. Fir 34" bears N. 56 1/4°W., 17.9 ft. (Rec. N. 55 1/2°W., 17.2')

I perpetuate the corner position by taking the following new tree and place a brass washer bearing my registration no. in the lower blaze:

- A D. Fir, 22", marked 1/4 S BT bears N. 62°E., 23.7 ft.

11/16/78

Glenn S. Baughman  
For: U. S. Forest Service  
December 1976  
M 56 - 68

Kurt C. Weaver, L.S. #1679  
Witnesses: Herb Farber  
Reg Harding  
November 16, 1978  
C.S. 58/176

3/77  
JAN 78

RE-RENEWED, SEE CORNER NO. #108

63

64

65

66

67

68