

Douglas County Surveyor's Record of  
Government Corners Renewed

T 32

T. S.

R 1

R. W. W. M.

YOKE-CHAPMAN CO., EUGENE, ORE. 21881

69

Section Corner for Secs. 9, 10, 16 and 15

Found - 1955 GLO brass cap on a 2" I.P. firmly set  
A D. Fir 14" bears N. 14 1/4°E., 18.4 ft. (Rec. N. 14 1/4°E.,  
18.5 ft.)  
A D. Fir, 9" bears N. 29 1/4°W., 22.7 ft. (Rec. N. 29 1/4°W.,  
23.1 ft.)

I perpetuate the corner position by taking the following new bearing  
trees and place a brass washer bearing my registration No. in the lower  
blaze: A D. Fir, 13", marked "T32S R1W S16 BT" bears S. 34 1/2°W.,  
24.8 ft.  
A D. Fir 12" marked "T32S R1W S15 BT" bears S. 43 1/2°E., 34.1 ft.  
\_ \_ \_ \_ \_ 11/16/78

70

Section Corner for Secs. 15, 14, 22 and 23.

Found - 2" O.D. Pipe by Marvin Ramsey in 1958, firmly set in a mound  
of stone.  
A D. Fir, 30" with healed blaze, bears S. 62 1/4°W., 92.5 ft.  
(Rec. S. 62 1/4°W., 90.4 ft.)  
A D. Fir, 30" with open blaze bears N. 35 1/2°W., 57.8 ft.  
(Rec. N. 35°W., 59.4 ft.)  
A dead standing D. Fir, 24" bears S. 84°E., 33.0 ft. (Rec. #186  
S. 83 1/2°E., 33.7 ft.)  
A dead standing D. Fir 9" bears N. 22 1/4°E., 137.6 ft. (Rec.  
N. 20°E., 139.9 ft.)

I set a 2" x 30" G.I.P. over the found pipe with a 2 1/2" brass cap  
marked: T32S R1W S15 S14 S22 S23 L.S. 1679 1978  
and take the following new bearing trees and place a brass washer  
bearing my registration No. in the lower blaze:  
A D. Fir, 6" marked "T32S R1W S.14 BT" bears N. 70 1/4°E., 26.5 ft.  
A D. Fir, 6" marked "T32S R1W S.23 BT" bears S. 1°E., 25.1 ft.  
\_ \_ \_ \_ \_ 11/17/78

71

1/4 Corner for Secs. 15 and 22.

Found - A 1" pipe with brass cap attached set by H.W. Thielsen, 1955.  
A White fir, 24" bears Record S. 39 1/4°E., 20.5 ft.  
I perpetuate the corner position by taking the following new tree  
and place a brass washer bearing my registration No. in the lower blaze:  
A D. Fir 8" marked 1/4 S BT bears N. 41°E., 70.1 ft.  
\_ \_ \_ \_ \_ 11/17/78

72

Section corner for Secs. 8, 9, 17 and 16.

Found - 1968 County brass cap being exposed 17 ins. in a mound of  
stone and leaning northerly. Ren. #29  
A Sugar pine snag 12 ins. bears N. 57°20'W., 28.2 ft. (Rec.  
N. 58°W., 27.7 ft.)  
A D. Fir snag, 18 ins. bears S. 47°51'E., 20.1 ft. (Rec.  
S. 50°E., 20.3 ft.)  
A Live Oak, 9 ins. bears S. 80°59'W., 17.3 ft. (Rec. S. 80°W., 17.8 ft.)  
A Live Oak 7 ins. bears N. 4°52'W., 10.6 ft. (Rec. N. 5°W., 10.9 ft.)  
A White Fir 9 ins. bears East 11.0 ft. (Rec. East 11.1 ft.)

I perpetuate the corner position by taking the following new tree and place  
a brass washer bearing my registration number in the lower blaze:  
A D. Fir 12" marked T 32 S R1W S 9 BT bears N. 75°30'E., 98.0 ft.  
\_ \_ \_ \_ \_ 2/15/79

73

1/4 Corner for Secs. 4 and 9

Found - A 1 1/2 inch iron pipe with a union and elbow, firmly set and  
exposed 11 inches in a mound of stone. Ren. #8  
A D. Fir 38" bears N. 25°50'W., 11.0 ft. (Rec. N. 25°W., 11.9 ft.)  
A D. Fir, 48 ins. bark scribed 1/4 S 9 BT bears S. 3°40'W.,  
33.5 ft. (Rec. S. 2°W., 33.5 ft.)  
A Maple 10 ins. bears S. 40°23'W., 27.0 ft. (Rec. S. 40°W., 26.5 ft.)  
A dead and down D. Fir, 12 ins. bears record N. 4°E., 35.2 ft. to  
stump depression.  
Set - A 2 inch x 30 inch Galv. I.P. in the exact position of the  
found monument, with a 2 1/2 inch brass cap marked:  
T32S R1W 1/4 S4 S9 LS 1679 1979.  
\_ \_ \_ \_ \_ 2/15/79

Kurt C. Weaver L.S. #1679  
Witnesses: Herb Farber  
Reg Harding  
November 1978  
C.S. 58/176

Kurt C. Weaver LS 1679  
Witnesses: Herb Farber; Reg  
Harding; Bill Trempe  
Feb. 15, 1979  
C.S. 58/176

RE-RENEWED SEE CORNER NO. #186

1-79