

Douglas County Surveyor's Record of
Government Corners Renewed

T 32 T. S. R 1 R. W. W. M.

HOKE-CHAPMAN CO., EUGENE, ORE. 97401

Barnton W. Holt
For: Sun Studs
Revised from
survey in 1974 -
M 49 -71
Revised June 20,
1979
M 70 - 72

1/4 Corner for Secs. 17 and 20
Set - Brass cap
BT's - 11" W. Fir bears N.89°W., 7.6 ft. scribed S 1/4 S17 BT.
11" Cedar bears S.13°W., 13.2 ft. scribed N 1/4 S20 BT
NOTE: SEE REN. #57 FOR PRIOR RENEWAL. THIS IS A REVISION.

RE-RENEWED, SEE CORNER NO. 120
See CS 631166 for 1998 BLM opinion 74

6/20/79

Section corner for Secs. 16, 17, 20 and 21
Set - Brass cap
BT's - 15" D. Fir bears S.72°W., 44.0 ft. scribed T32S R1 W S20 BT.
6" W. Fir bears S.53°E., 30.9 ft. scribed T32S R1W S21 BT
8" D. Fir bears N.19°E., 9.9 ft. scribed T32S R1W S16 BT.
7" Cedar bears N.79°W., 38.4 ft. scribed S17 BT.
NOTE: SEE REN. #58 FOR PRIOR RENEWAL. THIS IS A REVISION.

RE-RENEWED, SEE CORNER NO. #118
see C.S. 631166 for 1998 BLM opinion 75

6/20/79

1/4 Corner for Secs. 20 and 29, (Jackson County)
Set - Brass cap
BT's - 15" D. Fir bears N.9°W., 35.0 ft. scribed S1/4 S20 BT
8" D. Fir bears S.35°30'E., 57.0 ft. scribed N 1/4 S29 BT.
Note - 1/4 Cor. set by Jackson County 1975 bears N.21 1/2°E., 148.1 ft.

76

6/20/79

Section corner for Secs. 7 and 18; and Secs. 12, 13 of T.32-2
Found - A 1" iron pipe projecting 24" above the ground with a 1963
2 1/2" brass cap marked: "County Surveyors Office"

77

From which: Ren. #65

- A 35" D. fir rotted stump, bears N.58°E., 19.1 ft.
- a 6" Chinquapin snag with scribe marks "S12CS BT" visible, bears N.38°W., 48.7 ft.
- a 20" W. fir with healed blaze, bears N.22°E., 49.6 ft. #100
- a 36" fir wind thrown snag, bears S.50°E., 29.0 ft.
- a 12" D. fir with scribe marks "T32S R2W S13 BT" visible on a partially healed blaze, bears N.85°W., 23.3 ft.
- a 10" D. fir with scribe marks "T32S R1W S18 BT: visible on a partially healed blaze, bears S.34°E., 21.6 ft.
- a 10" W. fir with scribe marks "T32S R2W S12 BT" visible on a partially healed blaze, bears N15°W., 62.3 ft.
- New BT's - a 10" D. fir, bears S.72°W., 40.3 ft., I marked "T32S R2W S13 BT" on a double blaze and nailed a brass washer stamped "LS 536" into lower blaze.
- a 12" D. fir, bears N.85°W., 23.3 ft., marked by Baughman in 1976, I chopped out "S13" and remarked "S12"

7/79

78

1/4 Corner for Secs. 8 and 17.
Found - 10" Cedar with scribe marks visible on a partially healed blaze bears N.46°W., 92.0 ft. Ren. #28
22" Laurel with scribe marks "1/4 S17 CS BT" visible on a partially healed blaze bears S.78°W., 103.7 ft. Ren. #28
Set - a 2" x 30" iron pipe, 20" in the ground with a 3" brass cap marked: T32S R1W 1/4 S8 S17 1979 PLS 536

RE-RENEWED, SEE CORNER NO. #101

79

1/4 Corner for Secs. 16 and 17
Found - a 1" iron pipe projecting 4" above the ground, with a 2 1/2" brass cap marked: "T32S R1W 1/4 S17 S16 1968". Ren. #55
a 22" Fir stob, orig. BT, bears S.34°W., 2.6 ft.
a 14" Hemlock with scribe marks "1/4 S17 CS BT" visible on a partially healed blaze bears S.45°W., 26.8 ft.
a 14" D. Fir stump with scribe marks "1/4 S16 CS BT" visible on a partially healed blaze bears N.89°E., 65.1 ft.
New BT - an 8" D. Fir bears S.77°E., 52.1 ft. I marked "1/4 S17 BT" on a double blaze and nailed a brass washer stamped "LS 536" into lower blaze.

7/79

Glenn Baughman
For: U.S. Forest Service
July 1979
C.S. 58/176