

Douglas County Surveyor's Record of
Government Corners Renewed

T 32 T. S. R 1 R. W. W. M.

HOKE-CHAPMAN CO., EUGENE, ORE. 97401

80

1/4 Corner Secs. 4 and 3.

Found - 24" Madrone, orig. BT, with scribe marks "1/4" visible on a partially rotted blaze bears N.65°W., 2.6 ft. (Boyers record 4.0 ft.) Ren. #2

4" live Oak with scribe marks "1/4 S3" visible on an opened blaze bears N.82°E., 15.8 ft. (Boyers record 34.0 ft.)

12" live Oak, with scribe marks "1/4 S3 BT 1581" visible on a rotted blaze bears N.84°E., 5.0 ft. (Boyers record N.76°E., 4.5 ft)

Set - At the corner point set: a 2" x 30" iron pipe, 12" in the ground on solid rock, in a 3 foot diameter mound of stone with a 3" brass cap marked: T32S R1W 1/4 S4 S3 1979 PLS 536.

10/79

South 1/4 Corner Sec. 32 only, T. 31 S. R. 1 W. Ren #18

81

Found - Brass cap at corner.

D. Fir stump 12" dia. bears N.48°01'W, 57.3 ft. (Rec. N.48°W. 58.0 ft.)

W. Fir 13" dia. bears N.79°03'E., 54.0 ft. (Rec. N.78°E., 54.9 ft.)

Stump hole with dead and down W. Fir bears N.8°47'W., 16.5 ft. (Rec. N.10°W., 16.5 ft.)

New BT's - 6" dia. Yew Wood bears N.52°05'W., 47.1 ft.

7" dia. D. Fir bears N.57°45'E., 44.6 ft.

13" diameter W. Fir bears N.16°22'W., 62.5 ft.

Note - This corner lies 165 ft. east of the C.C. of Sections 5 and 6 of T. 32 S. R. 1 W.

North 1/4 Corner for Sec. 5 only.

Found - the 3/4" G.I.P. as set by Lovejoy Ren. #6
from which -

A 8" W. Fir bears S.39°03'W., 18.0 ft. (Rec. S.38°W., 16.6 ft.)

A 8" G. Fir bears S.31°00'E., 19.0 ft. (Rec. W. Fir S.28°E., 19.4 ft.) Ren. #19

A 2" G.I/P. with 2 1/2" BC at the Section corner for Secs. 32 and 33, T.31S., R.1W., bears S.89°52'48"E., 158.37 ft.

Set - I set a 2" x 30" G.I/P. with a 2 1/2" brass cap over found pipe, exposed 16" in a mound of stone and marked:

T31S R1W 1/4 T32S R1W LS 1679 1980

S5

Center 1/4 corner to Sec. 2

Set - I set a 2 1/2" x 30" Alum. pipe with alum. cap mkd. "T32S R1W WM C1/4 S2 1980 PLS 1035". Cap sits 6" above ground.

BT's - 6" D. Fir bears N.73°E., 5.0 ft.

9" D. Fir bears N.60°W., 14.4 ft.

Bearing trees have brass washer stamped "RS 1035" nailed to lower blaze.

8/80

North 1/4 Corner to Sec. 2

Set - 2 1/2" x 30" alum. pipe with alum. cap mkd. "T32S R1W WM 1/4 S2 1980 PLS 1035", exposed 20" above ground in large stone mound.

BT's - 60" D. Fir bears S.36°E., 31.1 ft.

26" D. Fir bears S.24°W., 13.0 ft.

Bearing trees have brass washer stamped "RS 1035" nailed to lower blaze.

8/80

1/4 Corner to Secs. 2 and 3

Fd. - No evidence found of corner set by A. Boyer in 1949.

See Ren. #4.

Set - 2 1/2" x 30" alum. pipe with alum. cap mkd. "T32S R1W WM 1/4 3*2 1980 PLS 1035" exposed 6" above ground set at prorated position.

BT's - 6" D. Fir bears N.79°E., 15.8 ft.

8" D. Fir bears S.51°W., 29.2 ft.

Bearing trees have brass washer stamped "RS 1035" nailed to lower blaze.

- OVER -

Glenn Baughman
L.S. #536
For: U.S. Forest Serv.
October 1979
C.S. 58/176

Kurt Weaver
For: U.S. Forest
Service
Dec. 1979
M 81 - 58
L.S. #1679

Kurt C. Weaver #1679
For: U.S. Forest
Service
February 1980
C.S. 58/176

Gerald V. Nygren LS# 1035
For: Umpqua National Forest
August 1980
M 79 - 53
C.S. 58/158N