

Douglas County Surveyor's Record of
Government Corners Renewed

T 32 S T. S. R 1 W R. W. W. M.

MOKE-CHAPMAN CO., EUGENE, ORE. 21891

86

1/4 Corner to Secs. 1 and 2
Fd. - No evidence of this corner found as set by Rufus Moore in 1883.
Set - 2 1/2" x 30" alum. pipe with alum. cap mkd. "T32S R1W WM 1/4 S2
S1 1980 PLS 1035" exposed 18" above ground in stone mound.
BT's - 10" D. Fir bears S. 11 1/2° W., 62.0 ft. #115
13" D. Fir bears N. 72° E., 61.4 ft.
Bearing trees have brass washer stamped "RS 1035" nailed to lower blaze.

8/80

87

1/4 Corner to Secs. 2 and 11 #99
Fd. - No evidence of this corner found as set by Rufus Moore in 1883.
Set - 2 1/2" x 30" alum. pipe with alum. cap mkd. "T32S R1W WM S2, S11
1980 PLS 1035" exposed 8" above ground set by proportionate
measurement.
BT's - 10" Hemlock bears S. 70° W., 26.5 ft.
6" Hemlock bears N. 39° W., 12.8 ft.
Bearing trees have brass washer stamped "RS 1035" nailed to lower blaze.

8/80

88

Sec. Corner to Secs. 1, 2, 11, and 12
Fd. - Orig. 30" Fir stump bears S. 80° W., 16.5 ft.
Orig. 44" Fir snag bears N. 8° W., 25.1 ft.
Orig. madrone stool bears N. 80° E., 30 ft.
Orig. live oak stool bears S. 37° E., 21 ft.
Set - 2 1/2" x 30" alum. pipe with alum. cap mkd. "T32S R1W WM 1,2,11
and 12 PLS 1035 1980" exposed 4" above ground set from original
evidence as noted above.
BT's - 16" D. Fir bears S. 48° W., 26.1 ft.
8" D. Fir bears N. 30° W., 3.5 ft.
16" D. Fir bears N. 34° E., 3.6 ft.
y" Live Oak bears S. 7° E., 22.8 ft. F.D.O.K. 9-93 BY M118-20
G. Nygren C.S. 6/13/84

8/80

89

1/4 Corner to Secs. 1 and 12
Fd. - 18" x 13" x 6" stone with 1/4 chisled on face which is not the
original corner.
Original 4" chinkapin stump bears S. 81° W., 15.2 ft.
Original 10" madrone snag bears N. 45° W., 4.6 ft.
Set - 2 1/2" x 30" alum. pipe with alum. cap mkd. "T32S R1W WM 1/4 S1
S12 1980 PLS 1035" exposed 4" above ground set by proportionate
measurement.
BT's - 18" D. Fir bears S. 32° E., 31.0 ft.
8" D. Fir bears N. 38° W., 14.5 ft.
Bearing trees have brass washer stamped "RS 1035" nailed to lower blaze.

8/80

90

1/4 Corner for Section 4 only. (north 1/4)
Set - Brass cap mkd. T31S R1W W.M. 1/4 S4 only, T32S R.L.S. 430 1980.
New BTs- 8" D. Fir BT, I scribed "1/4 S4 BT" bears S. 86° W., 8.7 ft.
8" W. Fir BT, I scribed "1/4 S4 BT" bears S. 11° E., 20.7 ft.

10/80

91

Center 1/4 Corner for Section 4 #104
Set - Brass cap mkd. "T32S R1W W.M. CC 1/4 S4 R.L.S. 430 1980"
New BTs- 6" D. Fir BT, I scribed "C 1/4 S4 BT" bears S. 35° W., 39.1 ft.
6" D. Fir BT, I scribed "C 1/4 S4 BT" bears S. 65° E., 37.0 ft.

10/80

92

Closing Corner for Sections 6 and 5.
Found - 1964 County brass Cap. Ren. #17
8" Oak, BT Scribes visible bears N, 55.6 ft.
8" Maple, BT, dead, scribes visible bears S. 1° E., 106.9 ft.
(Record S. 2° W.)
New BTs- 12" D. Fir, I scribed "T32S R1W S5 CC BT" bears S. 19° E., 138.0 ft.
8" D. Fir, I scribed "T32S R1W S6 CC BT" bears S. 34° W., 143.2 ft.

10/80

Gerald V. Nygren LS# 1035
For: Umpqua National Forest
Aug. 1980
M 79 - 53
C.S. 58/158N

Bruce Shaner
For: U.S. Forest
Service
October 1980
M 3 - 36

Bruce Shaner, For:
U.S. Forest Service
Oct. 1980
RM 3 - 37

RE-RENEWED SEE CORNER NO.

RE-RENEWED SEE CORNER NO.