

**Douglas County Surveyor's Record of
Government Corners Renewed**

T32

T. S.

R 1

R.W.W.M.

MOORE-CHAPMAN CO., EUGENE, ORE. 21881

FO. OK BY R. WYCHERLEY
MAY 2004 - M144-50

93

1/4 Corner for Sections 5 and 6
Found - 1968 County Brass cap . Ren. #30
12" x 10" x 8" original stone "1/4" lies alongside Brass cap.
16" D. Fir, orig. BT, blown down, healed face bears N.20°E.,
4.0 ft. to root hole
8" Yew, BT, scribes visible bears S.63°W., 14.8 ft.
New BT - 20" D. Fir BT, I scribed "1/4 S5 B.T." bears N.72°E., 35.4 ft

94

Section corner for Secs. 5, 6, 7 and 8.
Found - 1968 County Brass Cap. Ren. #26
22" D. Fir orig. BT, face visible bears N.43°E., 4.0 ft.
12" Falenn D. Fir orig. BT, scribes visible bears S.75°E., 4.6 ft
24" D. Fir stump, orig. BT bears N.38°W., 5.5 ft. to face,
(Record N.45°W., 4.0 ft.)
26" D. Fir BT, healed over face, bears S.29°W., 31.2 ft. (Record
S.25°W.)
12" D. Fir, BT healed over face bears S.3°E., 17.5 ft.
13" D. Fir stump scribes visible on down tree bears N.62°W., 20.6
(Record N.65°W.,)
New BT - 6" D. Fir BT, I scribed "T32S R1W S6 BT" bears N.66°W., 28.1 ft.

95

Center 1/4 Corner for Section 5
Set - Brass cap marked "T32S R1W W.M. C 1/4 S5 RLS 430, 1980".
From which:
12" Cedar BT, I scribed "C 1/4 S5 BT" bears N.84°E., 34.4 ft.
18" Cedar BT, I scribed "C 1/4 S5 BT" bears S.56°W., 15.3 ft.

96

1/4 Corner for Sections 5 and 8
Found - 3" square Yew post original corner
24" Cedar, orig. BT, scribes 1/4 visible bears N.80°W., 9.2 ft.
45" D. Fir stump, orig. BT., bears S.40°E., 25.7 ft. to face,
(Record, S.45°E.)
Set - Brass cap mkd. T32S R1W W.M. 1/4 S5 S8 R.L.S. 430, 1980
New BT's- 10" D. Fir BT. I scribed "1/4 S8 BT" bears S.46°W., 45.4 ft.
8" D. Fir BT., I scribed "1/4 S5 BT" bears N.32°E., 25.4 ft.
10/80

97

1/4 Corner for Sections 7 and 8
Set - Brass cap mkd. T32S R1W W.M. 1/4, S7, S8 RLS 430 1980
From which a:
34" White Fir, orig. BT. scribes visible bears S.35°W., 5.3 ft.
40" D. Fir stump, orig. BT bark scribes "BT visible bears
N.64°E., 20.5 ft. to face (Rec. N.11°E.)
New BTs-26" Cedar BT, I scribed "1/4 S8 BT" bears N.2°E., 22.1 ft.
10" Cedar BT, I scribed "1/4 S7 BT" bears S.63°W., 14.6 ft.
12/80

98

1/4 Corner for Sections 17 and 18
Set - Brass cap mkd. "T32S R1W W.M. 1/4 S18 S17 RLS 430 1980".
BT's- 10" D. Fir BT, I scribed "1/4 S18 BT" bears S.77°W., 17.9 ft.
8" D. Fir I scribed "1/4 S17 BT" bears S.24°E., 26.0 ft.
12/80

99

1/4 Corner for Sections 2 and 11
Found - Orig. Fir, now rotted Fir stump remains (by R. Moore in 1883)
with portions alongside containing old axe work and scribed
(partial) "BT" bears record S.20°W., 3.30 ft. to estimated
orig. position of scribed face. ~~RECORDED SITE CORNER NO. #117~~
Orig., rotted Fir root and stump remains, containing old axe work,
fd. at record location of orig. northwest bearing tree.
The orig. stone is now gone.
A fd. 2" diam. alum. pipe, projecting 5" with alum. cap mkd.
T32S R1W W.M. 1/4 2 1 1980 PLS 1035 (Ren. #87) set by
proportionate method, on survey No. 8498 (Jackson County) bears
S.86°24'E., 48.75 ft. **M79-53 (Douglas Co.)**
Set - From the above orig. evidence at the location described, SET
a 2 x 32 ins. galv. I.P. 28" in the ground, for the corner, with

Bruce Shaner, RLS #430
For: U.S. Forest Service, Tiller Ranger District
October 1980
R.M. #- 37

Bruce Shaner
For: U.S. Forest Serv.
December 1980
M 79 - 67

Bruce Shaner
For: U.S. Forest Serv
December 1980
M 79 - 68

Ed McGinty, Jackson
County Surveyor
R. Frost; R. Templin;
Witness: T.Newcomb,
U.S.F.S.
May 7, 1981
C.S. 58/183