

Douglas County Surveyor's Record of
Government Corners Renewed

T 32 T. S. R 1 R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97101

C O N T. - - -

(1/4 Cor. 2 and 11)

99

Ed McGinty, Jackson
County Surveyor
R. F. St; R. Templin;
Witness: T. Newcomb,
U.S.F.S.
May, 1981
C.S. 58/183

a 2 1/2" diam. brass cap mkd. T32S R1W 1/4S 2 11 C.S. 1981.
New BT's- Douglas fir, 9", bears S.27°54'W., 17.00 ft. (f.18m).
Hemlock, 13", bears N.63°50'W., 21.10 ft. (6.43m).
Mound stones around corner. Mark new trees "CS" "BT" and measurements
to center of trees at lower blaze.
Corner lies on steep (90%) north slope an estimated 400 ft. north of road
along top of Umpqua Divide ridge top.

5/7/81

Section corner for Secs. 7 and 18; and Secs. 12 and 13 of T.32-2

100

Found - 1963 County brass cap on a 1" iron pipe. Ren. #77

18" fir (dead) bears N.22°E., 49.6 ft. blazes healed.

14" fir bears S.34°E., 21.6 ft. scribe visible.

13" fir bears S.72°W., 40.3 ft. scribe visible.

15" fir bears N.85°W., 23.3 ft. scribe visible.

6" fir (dead) bears N.37°W., 48.7 ft. scribe visible.

(record, chinquapin).

New BT - 7" fir which bears N.01°E., 15.9 ft. scribed T32S R1W S7 BT.

6/7/85

Loyd R. Moffit
L.S. #944
For: U.S.F.S.
June, 1985
C.S. 63/8

1/4 Corner for Section 19; and Sec. 24 of T.32-2

100A

CORNER REPORT ONLY

Found - 2 1/2" dia. I.P. firmly set, flush with a 2 ft. mound of stone
with a 3" dia. brass cap set by Glenn Baughman in 1976. Ren.#60

A steel fence post bears east, 3.9 ft. with U.S.F.S. signs
#54-2 and 54-9 attached, as a guard post.

A 7" cedar, S.02°E., 3.1 ft. with scribe marks "T32S R1W 1/4
S19" visible on partially healed double blaze with a 3/4" brass
washer stamped "LS 536" nailed flush to lower blaze.

A 10" D. fir, N.29°W., 18.4 ft. with healed double blaze.

An unrecorded BT by Baughman in 1976: a 12" D. fir, S.51°E.,

20.2 ft. with scribe marks "T32S R1W S19 BT" visible on
partially healed double blaze with a 3/4" brass washer stamped
"LS 536" nailed flush to lower blaze.

7/15/85

Maurice Farr LS 1181
U.S.F.S.
Leonard Herzstein
Party Chief
Ran Lopez, witness
Jul 15, 1985
C.S. 52/26

1/4 Corner for Sections 8 and 17

101

Found - 2" I.P. with a 3" brass cap set in 1979. Ren. #78

24" Laurel which bears S.78°W., 103.7 ft. scribe visible. Ren. #28

Dead Cedar which bears N.46°W., 92.0 ft. scribe visible. Ren. #28

New BT - 8" Fir which bears N.46 3/4°W., 94.3 ft. scribed 1/4 S8 BT with
LS washer No. 944 nailed to BT scribe.

11/86

Loyd R. Moffit
For: U.S.F.S.
Nov. 1986
C.S. 62/30

1/4 Corner for Sections 8 and 9

102

Found - 1968 County 2 1/2" brass cap on 1" I.P. in rock mound. Ren. #34

Fir snag (down) which bears N.50°E., 3.1 ft. (Rec. 2.6 ft.)(orig.)

28" Fir which bears N.81°E., 35.8 ft. Scar visible.

Fir stump which bears S.54°W., 35.1 ft.

Fir stump which bears S.89°W., 6.6 ft. (Rec. 4.6 ft.) (Orig.)

New BT - 28" Fir which bears N.37°W., 3.1 ft. scribed 1/4 S8 BT with
L.S. washer No. 944 nailed to BT scribe.

11/86

Section Corner for Sections 2, 3, 10 and 11

103

Found - 1 1/2" iron pipe with 1955 GLO 2 1/2" brass cap.

48" fir snag, N.70°E., 34.8 ft. (healed blaze) (Rec. N.68°E, 58 lks)

36" fir, S.79°E., 67.8 ft. (healed blaze.) (?Rec. N.89°E, 106 lks)

63" fir stump, S.75°W., 11.2 ft. (healed blaze.) Orig.

30" fir, N.65°W., 82.5 ft. (healed blaze) (?Rec. N.73 1/4°W, 127 lks)

46" fir, N.50°W., 22.6 ft. (healed blaze) Orig.

Note: above monument (iron pipe) is badly bent.

New BT - A 7" fir, S.46°W., 6.0 ft. scribed "T32S R1W S10 BT". Nailed
1/2" dia. brass washer marked "LS 1035" to lower blaze.

7/89

Gerald Nygren
For: USFS
July 1989
C.S. 63/85

RECORDED CORNER NO. #117
RECORDED CORNER NO. #114