Douglas County Surveyor's Record of Government Corners Renewed

T 32 T. S. R 1 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

104

Center 1/4 Corner for Section 4
Found - 2" iron pipe with 3" brass cap extended 4" above stone mound
Mkd. "T32S R1W WM C1/4 S4 RLS 430 1980" Ren. #91
6" D. fir snag bears S.35°W., 39.1 ft. (vis. scribe)
14" D. fir bears S.65°E., 37.0 ft. (healed blaze)
New BT - A 5" D. fir, S.41°W., 43.7 ft. scribed "X" in small upper blaze and "BT" in small lower blaze with 1/2" dia. brass washer mkd. "LS 1035" nailed to lower blaze.

105

1/4 Corner for Sections 10 and 11
Found - 1" iron pipe with 1955 GLO 2½" brass cap extended 5" above ground.
18" D. fir bears N.85°E., 8.4 ft. (healed blaze) Orig.
26" D. fir bears S.8¼°E., 16.7 ft. (healed blaze) 1955
22" D. fir stump bears S.72°W., 16.6 ft. (healed blaze) 1955
New BT - A 6" D. fir bears N.64°W., 8.9 ft. scribed "1/4 S10 BT".
with 1/2" dia. brass washer mkd. "LS 1035" nailed to lower blaze.
7/89

106

Section Corner for Secs. 14, 15, 22 and 23
Found - 1½" iron pipe with 3" brass cap extended 4" above stone mound. Ren. No. 70
30" D. fir S.62¼°W., 92.5 ft. (healed blaze)
24" Fir snag S.84°E., 33.0 ft. (vis. scribe)
32" D. fir, N.35½°W., 57.8 ft. (vis. scribe)
8" D. fir N.70¼°E., 26.5 ft. (healed blaze)
12" D. fir S.1°E., 25.1 ft. (healed blaze)
New BT - A 8" D. fir S.84°E., 22.6 ft. scribed "T32S R1W S23 BT" with 1/2" dia. brass washer mkd. "LS 1035" nailed to lower blaze.

107

1/4 Corner for Sections 14 and 15
Found - 1" iron pipe with 1955 GLO 2½" brass cap flush with ground and properly marked.
28" W. fir bears S.39½°W., 67.7 ft. (healed blaze) Ren. No. 36
39" D. fir stump bears S.28½°E., 48.7 ft. 1955
New BT - 7" D. fir bears N.84°E., 20.5 ft. scribed "1/4 S14 BT" with 1/2" dia. brass washer mkd. "LS 1035" nailed to lower blaze.

108

1/4 Corner for Sections 15 and 16
Found - 1" iron pipe with 1955 GLO 2½" brass cap extended 7" above ground.
8" D. fir stump, N.76½°W., 16.9 ft. (N.77°W., 15.8 ft.) Ren. #68
34" D. fir stump, N.56¼°W., 17.9 ft.(N.55½°W. 17.2 ft.)
33" D. fir stump, S.55½°E., 36.2 ft. (S.55½°E., 36.3 ft.)
New BTs - 9" D. fir, N.89°E., 31.7 ft. scribed "1/4 S15 BT"
8" W. fir, S.72°W., 61.1 ft. scribed "1/4 S16 BT"
Nailed 1/2" dia. brass washers mkd. "LS 1035" to lower blaze of new BTs.
Found - 22" D.Fir dead & down, N.62°E., 23.7 ft. (vis. scribe)

109

1/4 Corner for Sections 11 and 14
Found - 1968 County 1" iron pipe with 2½" brass cap extended 9" abo ground. Ren. #35
29" dia. D. fir N.50°W., 4.7 ft. (healed blaze)(N.45°W,4.6)
11" dia. D. fir S.4°19'E., 16.6 ft. (vis. scribe)(S.5°W,16.6)
18" dia. D. fir snag S.58°54'W., 17.4 ft.(S.59°W,18.3 ft.)
New BT - 7" dia. D. fir, S.59°E., 35.1 ft. scribed "1/4 S14 BT". Nailed ½" brass washer marked "LS 1035" to lower blaze.
7/89

110

1/4 Corner for Sections 10 and 15
Found - USGLO 1955 1" iron pipe with 2½" brass cap extended 10" above stone mound and marked properly.
19" dia. D. fir stump, N.48¼°W., 72.3 ft.(N.48°W., 72.6 ft. Rec.)
50" dia. d. fir, S.16½°W., 30.5 ft. (healed blaze)(S.13½°W.,31.0ft)
(Note: above monument (iron pipe) has been bent.)
New BT - A 7" dia. D. fir N.2°E., 28.2 ft. scribed "1/4 S10 BT". Nailed ½" brass washer marked "LS 1035" to lower blaze.

Gerald Nygren, L.S. 1035
For: U.S.F.S.
July 1989
C.S. 63/85

Gerald Nygren
For: USFS
July 1989
C.S. 63/85

WITNESS CORNER NO. 121