

**Douglas County Surveyor's Record of
Government Corners Renewed**

T 32 T. S. R 1 R. W. W. M.

FOKE-CHAPMAN CO., EUGENE, ORE. 97301

Gerald Nygren
For: USFS
July 1989
C.S. 63/85

Don Bentz
For: US Forest Service
July 19, 1993
C.S. File 63/153

Gerald. Nygren, PLS #1035

For: United States Department of Agriculture
Umpqua National Forest

M 118-20 C.S. File 63/134 (N)
July 1991 thru Sept. 1993

1/4 Corner for Sections 3 and 10

111

CORNER REPORT ONLY

Found - 1955 GLO 2 1/2" brass cap on 1" iron pipe, extended 4" above
stone mound.
24" dia. W. fir, S.83°W., 68.0 ft. (Rec. 89.1 ft.) (healed blaze)
22" dia. W. fir, N.74 1/2°W., 89.1 ft. (Rec. 68.0 ft.) (healed blaze)
32" dia. W. fir, N.40°E., 82.0 ft. (healed blaze)
26" dia. W. fir, S.70°W., 16.5 ft. (vis. scribe) Ren. #3

Bearing tree signs and monument signs were placed on all BTs without them
and a 6" red band and face blazes were painted on all BTs.

Corner for Sections 18 & 19; 13 & 24 T.32-2.

112

Found - 8" Yew with visible scribing, bears N.50°E., 9.9 ft.
18" Yew with visible scribing, bears S.40°E., 18.3 ft.
24" W. Fir with healed blaze bears N.55°W., 82.7 ft.
12" Fir with healed blaze bears S.75°W., 22.6 ft. See Ren. # 59
Note - Found 1" Iron Pipe with Brass Cap lying on the ground, reset per
record bearing and distances from existing bearing trees.
Reset - 1" Iron Pipe with County Surveyor's Office Brass Cap, monument 16"
above ground with 24" dia. mound of stone.
Note - All bearing trees have a 6" red band painted around the tree and
the blazed face painted red. USFS sign 54-3 'Bearing Tree' and
sign 54-9 'Land Surveying Monument' are nailed to all bearing
trees.

1/4 Cor. Secs. 2 & 3

113

Set - 2 1/2"x30" aluminum pipe with aluminum cap stamped:
T32S R1W WM
C 1/4 S2
Reset 1993
1980
PLS 1035

New References -

Hemlock, 8" dia., bears S.16°E., 3.4', scribed "1/4 S2 BT"
Hemlock, 10" dia., bears N.26°E., 3.3', scribed "1/4 S2 BT"
Douglas Fir, 10" dia., bears N.36°W., 11.2', scribed "1/4 S3 BT"
Hemlock, 17" dia., bears S.30°W., 16.5', scribed "1/4 S3 BT"
A 5/8"x30" iron rod with yellow plastic cap mkd: "NYGREN LS 1035",
bears N.0°32'44"W., 275.07'. (Previous location of 1/4 cor.) (REN
#85)

114

Center 1/4 Sec. 2

Set - 2 1/2" dia., aluminum pipe with aluminum cap stamped:
T32S R1W WM
C 1/4 S2
RESET 1993
1980
PLS 1035

New references -

Douglas Fir, 6" dia., bears S.35°W., 12.8', scribed "C 1/4 S2 BT"
Douglas Fir, 11" dia., bears S.65°E., 37.7', scribed "C 1/4 S2 BT"
A 5/8"x30" iron rod with yellow plastic cap mkd: "NYGREN LS 1035"
bears N. 6°39'14"E., 256.86'. (Previous location of 1/4 cor. Ren#83)
Doug. Fir, 14" bears N. 7°40'E. 259.0' this tree was scribed and
used for BT in 1980 survey