

Douglas County Surveyor's Record of  
Government Corners Renewed

32

T. S.

1

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97501

Leonard Herzstein  
USFS  
9/9/2003  
Witness:  
Brandon Green  
C.S. File  
65/48-25A&B

1/4 Cor. Secs. 11 & 14

121

continued from previous page

New - From which new accessories for the corner:  
6" diam. W.Fir, bears N.42 $\frac{1}{4}$ °W., 18.6 feet, scribed " $\frac{1}{4}$   
S11 BT" on a single blaze.

A steel fence post, bears N.82 $\frac{1}{4}$ °W., 2.4 ft, project:  
4 ft above the ground with Forest Service sig  
"Boundary" (#54-'2) & "Attention" (#54-4) attach

Note - Bearing & distances were determined by a total station  
traverse from a property line post 575 ft West  
of the corner. I used a bearing of S.89°53'34"E.  
between the property line post & the corner,  
based on a 1978 property line survey. At the  
corner point, I determined the magnetic  
declination to be 15° E. Bearings are reported  
to the nearest  $\frac{1}{4}$ °. Trees are measured to the  
center of the root crown. Tree diameters are at  
breast height. A  $\frac{3}{4}$ " brass washer, marked "LS  
2150", is nailed flush to the lower portion of  
the blaze of the new bearing tree.

The corner is East, 305 ft, from Forest Service  
Road No. 1632 (at mile post 8.3) & West, approx.  
250 ft, from the Rogue-Umpqua Divide

Raymond  
Wytcherley  
May 7, 2004  
For: Boise  
Cascade Corp.

Center 1/4 Cor. Sec. 6

122

Found - Brass cap per RM 2-21 (Ren #53) from which:  
D.Fir 21" dia., bears (N.31°E., 72.0 ft) face  
healed over.

Cedar 33" dia., bears (S.80 $\frac{1}{2}$ °W., 74.0 ft.)  
face healed over.

New BOs - A steel "T" post bears North 5.04 ft. with BT  
sign.

A steel "T" post bears South 23.9 ft., with BT  
sign.

1/4 Cor. Secs. 6 & 7

123

Found - 1963 County brass cap (Ren. #25) from which  
A W.Fir stump bears N.60°W., 17.2 ft., face  
rotted.

A D.Fir snag, 5 ft. high bears S.72°W., 12.0 ft.  
face healed over.

New BTs - A fir 10" dia., bears N.1°28'W., 48.41 ft.,  
scribed " $\frac{1}{4}$  S 6 BT"

A Fir 7" dia., bears N.52°E., 14.24 ft., scribed  
" $\frac{1}{4}$  S 7 BT"

A Pine 8" dia., bears S.67°W., 24.60 ft., scribed  
" $\frac{1}{4}$  S 7 BT"

A Pine 9" dia., bears S.20°E., 39.24 ft., scribed  
" $\frac{1}{4}$  S 7 BT"

M 144-50

Center 1/4 Cor. Sec. 18

124

Set- 5/8"x30" I.Rod with Yel. plastic cap mkd: "LS 2724  
WYTCHERLY" from which:

Cedar 5" dia. bears N.14°E. 12.52 ft. scribed "C  $\frac{1}{4}$  BT"

Fir 9" dia. bears S.73°E. 11.20 ft. scribed "C  $\frac{1}{4}$  BT"

Fir 7" dia. bears N.66°W., 32.87 ft. scribed "C  $\frac{1}{4}$  BT"

Fir 6" dia., bears N.66°W., 4.12 ft. scribed "C  $\frac{1}{4}$  BT"

Raymond  
Wytcherly  
5/14/2004  
For:  
Boise  
Cascade Corp.  
M144-49