

Douglas County Surveyor's Record of
Government Corners Renewed

32

T. S.

1

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21921

Continued from previous pg.

Cor. Secs. 16, 17, 20, & 21

127

New - I add a mound of stone. The monument is now projecting 4" above a 2 ft dia mound of stone. I added new accessories to perpetuate the corner:
A 4" steel fence post projecting 4 ft above ground, bears N.2 $\frac{1}{4}$ °E., 3.1 feet, with Forest Service signs #54-4 "Attention" and #54-2 "Property Boundary" signs attached.

Leonard Herzstein
USFS
8/8/2005
C.S. File
65/54-35

An 11" incense cedar, bears S.70 $\frac{1}{4}$ °W., 71.7 ft, with scribed "T32S R1W S20 BT" and a 3/4" dia brass washer, stamped "LS 2150", nailed flush to a single blaze.

No trees are available in a recent clear cut in section 16. With a 1-second total station, I traversed the section line to the $\frac{1}{4}$ corner of sections 17 and 20 and I used the platted bearing of S.85°34'19"E. (M70-72) as my basis of bearings. Bearings for this renewal are rounded to the nearest 15 minutes. With a staff compass at the corner point, I determined the magnetic decl to be 17° East. Trees are measured to the center of the root crown. Tree diameters are at breast height.