

Douglas County Surveyor's Record of
Government Corners Renewed

T. 32 S. T. S. R. 2 W. R. W. W. M.

ROKE-CHAPMAN CO., EUGENE, ORE. 97198

7
 $\frac{1}{4}$ Corner to Sec. 1, T32-2W. & Sec. 6, T32-1W.
 Found - Orig. 6", now 14" Cedar N.21 $\frac{1}{2}$ °E. 2.0 ft., shows good scar.
 Orig. 40", now 46" Sugar Pine (snag), shows good scar,
 N.84°W. 20.1 ft.
 Also find stone as recorded.
 Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1963
 $\frac{1}{4}$ S1 / S 6 T32S
 R2W RLW
 New BT: 6" Cedar bears S.62°W. 56.0 ft. scribed $\frac{1}{4}$ S1 CS BT.

8
 Sec. Cor. To Secs. 13 & 24, T32-2W. & Secs 18 & 19, T32-1W.
 Found - Orig. 6", now 8" Yewwood N.50°E. 9.9 ft., shows good scribng.
 No other Orig. BT's. Find Stone as recorded. #82
 Set - Brass Cap at Cor. Mkd: County Surveyor's R2W S13 | S18 T32S
 S24 | S19 RLW
 New BT's: 18" Yewwood bears S.40°E. 18.3 ft. scribed S19 T32S RLW CS BT.
 19" W. Fir bears N.55°W. 82.7 ft. scribed S13 T32S R2W CS BT.
 No trees near to S.W.

9
 Section Corner to Secs. 1 & 12, T32-2W. & Secs. 6 & 7, T32-1W.
 Found - Stone at Cor. as recorded.
 Orig. 65", Now 65" Fir Snag, shows good bark scribing.
 Orig. 15", now 18" Fir N.36°W. 7.3 ft., shows good scar.
 Orig. N.E. & S.W. BT's. not found.
 Set - Brass Cap at Cor. Mkd: County Surveyor's S 1 | S 6 T32S
 Office, 1963 R2W S12 | S 7 RLW
 New BT's: 25" Cedar bears N.17°E. 44.0 ft. scribed S6 T32S RLW CS BT.
 12" Cedar bears S.57°W. 81.0 ft. scribed S12 T32S R2W CS BT.
 5" Fir bears S.86°E. 64.6 ft. scribed S 7 CS BT.

10
 Section Corner to Secs. 12 & 13, T32-2W. & Secs. 7 & 18, T32-1W.
 Found - Orig. 14", now 16" Fir Stump, shows good rev. scribing,
 N.29°W. 20.5 ft. #89
 Orig. 30", now 36" Fir Snag S.50°E. 29.0 ft., shows good scribng.
 Orig. S.W. BT. not found. Do find Stump of Orig. N.E. BT.
 Set - Brass Cap at Cor. Mkd: County Surveyor's S12 | S 7 T32W
 Office, 1963 R2W S13 | S18 RLW
 Note - Logging Road 75 feet South.
 New BT's: 5" Chinquapin bears N.38°W. 48.7 ft. scribed S12 CS BT.
 12" Hemlock bears N.22°E. 49.6 ft. scribed S7 T32S RLW CS BT.
 5" W. Fir bears S.86°E. 68.3 ft. scribed S18 CS BT.
 AUG. 1970 - FOUND. O.K. V.R.T. C.S. 54/117

11
 Sec. Cor. to Secs 36, T31-2W. & Sec. 31, T31-1W.
 Found - Orig. 30" Fir N. 30° E. 38.3 ft., shows good scar.
 14" Fir, now down, N. 33° W. 19.1 ft., scribe visible.
 Set - Brass Cap at Cor. Mkd: County Surveyor's R T 31 S #
 Office 2 S 36/S 31 1
 1966 W S 1 W
 New BT: 24" D. Fir N. 19° W. 34.6 ft. mkd. T31S R2W S36 CS BT.

12
 $\frac{1}{4}$ Corner to Section 36 only, T31-2W.
 Found - 16" Fir Stump N.55°E. 35.6 ft. (bear. Should Be N.50°E.) 35.6 ft.,
 faint scribe visible "S 3".
 14", now 24" D. Fir N. 75° W. 16.5 ft., shows a good scar.
 No trace of Corner Stone.
 Set - Brass Cap at Cor. Mkd: County Surveyor's T 31 S R 2 W
 Office $\frac{1}{4}$ S 36
 1966 T32S
 New BT: 4" D. Fir N. 27 $\frac{1}{2}$ ° E. 14.9 ft. mkd. $\frac{1}{4}$ S36 CS BT.

James W. Byron, Deputy County Surveyor
 Mike Darby and Wm. Stoffel
 March 1963
 C. S. File No. 53/15

John M. Powell
 Frank Jones & Terry Connell
 July, 1966
 C. S. File No. 54/28