

Douglas County Surveyor's Record of
Government Corners Renewed

T. 32 S. T. S. R. 2 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

John M. Powell
Frank Jones & Terry Connell
July 1966
C. S. File No. 54/28

1/4 Corner to Section 35 only, T31-2W. 13
Found - 12", now 24" D. Fir N. 50° W. 31.7 ft. Opened tree for scribe.
No trace of N.E. BT. nor Stone, ground very steep.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1/4 S 35 T32S
1966

New BT: 5" D. Fir N. 15 1/2° E. 27.8 ft. mkd. 1/4 S35 CS BT.

Sec. Cor. to Sections 35 and 36 only, T31-2W. 14
Found - Stone at corner, no marks legible.
30", now 38" D. Fir N. 45° W. 3.3 ft. shows good scar.
16" D. Fir N. 30° E. 19.8 ft. (bearing should be N. 65° E) This tree
down with buried face, scribe marks visible "B" & "S".
Set - Brass Cap at Cor. Mkd: County Surveyor's Office T 31 S R 2 W
1966 S 35 / S 36 T32S
S 2

New BT: 30" D. Fir N. 27° E. 55.0 ft. mkd. T31S R2W S36 CS BT.

Sec. Cor. to Sections 34 and 35 only, T31-2W. 15
Found - 15 x 6 x 6 Basalt Stone at Sec. Cor. Mkd: with notches & CC on
North Face.
36" D. Fir, now stump, N. 10° E. 33.0 ft. (This dist. should be
27.2 ft.) scribe visible "2W".
16", now 24" D. Fir N. 48° W. 21.8 ft. Had been opened but pitched over
Set Corner with 2 correct bearings & l. distance which fell at Corner Stone.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office T 31 S R 2 W
1966 S 34/S 35 T32S
S 3

New BT: 28" Cedar N. 1 1/2° W. 32.6 ft. mkd. T31S R2W S35 CS BT.
12" Yew Post at Fence Corner N. 31° W. 21.8 ft.

S. W. Corner Section 31 only, T31-2W. 16
Found - 1" Iron Pipe at Corner, See Ren. #20, T31-2W. (I.P. in good condition)
Orig. 36", now 40" D. Fir N. 43° E. 23.0 ft.
8" Hemlock, now dead, S. 44° E. 28.0 ft., scribe visible "S1 T32S".
16" D. Fir, now Snag, S. 6 1/2° E. 15.4 ft., bark scribed.
13", now 15" W. Fir N. 49° E. 45.0 ft., scribe visible.
Note - Road bears E. 75.0 ft., however, it lies in an old unit &
grown over with small alder. Best way to reach corner is by
walking down dam from main road.
New BT: 27" D. Fir S. 32 1/2° E. 34.7 ft. scribed T32S R2W S1 CS BT.
Aug. 29, 1966

Section Corner to Sections 31 and 32 only, T31-2W. 17
Found - 14 x 10 x 6 Stone, "CC" on N. face.
20", now 31", D. Fir N. 30° E. 50.8 ft., shows good scar.
12", now 17" Laurel, rotten face, N. 52 1/2° W. 35.6 ft., scribe visible.
Set - Brass Cap at Cor. Mkd: County Surveyor's R T 31 S
Office 2 S 31/S 32 T 32 S
1966 W S 6

New BT: 11" Laurel N. 32° W. 27.6 ft. mkd. T31S R2W S31 CS BT.
Note - Best way to Corner is on old trail from Neuman Gap. Location Tag on
Trail.

1/4 Corner to Section 31 only, T31-2W. 18
Found - 1" Iron Pipe at 1/4 Corner, See Ren. #21, T31-2W. #111
12", now 15" Alder Snag, S. 55° W. 3.0 ft. scribe visible "1/4 S".
10" Hemlock, now down, N. 27° W. 8.2 ft.
New BT's: 19" W. Fir N. 74° E. 104.4 ft. scribed 1/4 S31 CS BT. (in old Road)
52" Fir Stump N. 42° W. 73.3 ft. scribed 1/4 S31 CS BT.
Note - This corner lies in creek which runs S.14°W-N.14°E. Also, it is
in cut unit.