

Douglas County Surveyor's Record of
Government Corners Renewed

T. 32 S. T.S. R. 2 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

19

Sec. Cor. to Sections 5 & 6, only, T32-2W.
Found - 14" D. Fir, now 20" Stump 6.6' high, S. 44° E. 27.1 ft.
Tree had been opened & burnt. Faint scribe marks visible.
20" D. Fir, now stump, S. 31½° W. 10.6 ft., opened for scribing.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1966
T 31 S R 2 W
S 32
S 6/S 5
No new trees so tagged Orig. Stumps on top & sides. T 32 S
Reblzd. & Rescrbd: 20" D. Fir Stump S. 44° E. 27.1 ft. mkd. T32S R2W S5 CS BT.
Note - This corner lies in clear cut unit. Bearing Tree stumps are cut high. Corner lies on top of small ridge about 250.0 ft. S. & W. of cutting lines, & about 300 ft. N. of badly eroded area. Sept. 15, 1966

20

Sec. Cor. to Sections 4 and 3 only, T32-2W.
Found - Stone at Corner, 16 x 12 x 10, set firmly in ground, with "CC" on S. face-3 grooves on E. face-2 grooves on W. face.
Orig. 24", now 31", D. Fir S. 66° E. 25.1 ft., Tree opened for scribe. (Bearing S. B. S. 33° E.)
Orig. 12" D. Fir S. 36° W. 19.1 ft., opened for scribe, "4 BT". (Bearing Should be S. 60° W.)
Set Corner by using Stone and two distances.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1966
T 31 S R 2 W
S 34
S 4 / S 3
T 32 S
Orig. BT's. in good condition.

John M. Powell
Frank Jones & T. Connell
Aug. & Sept., 1966
C. S. File No. 54/28

21

¼ Corner to Section 32 only, T31-2W.
Found - No trace of Corner Stone.
20" D. Fir, now Stump, N. 30° E. 50.8 ft., scribe visible, "¼ S32 BT". By ring count this was done about 1900, Orig. date 1908. (Bearing S.B. N. 30° W.)
Parts of Laurel N. 57½° W. 35.6 ft. (Bearing S.B. N. 57½° E.)
Note - By chaining btwn. the ¼ Sec. 32 only, & Sec. Cor. to 5 & 6, I find distance to be 292.8 ft. Orig. notes call for 274.6, difference of 18.2 ft.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1966
T 31 S R 2 W
S 32
T 32 S
Note - This corner lies in clear-cut unit, not having anything to scribe, I tag Orig. Stump N. 30° W. 50.8 ft.
Cl. Corner to Sections 5 and 6, bears East 292.0 ft.

22

Found Only - ¼ Corner to Section 32 only, T31-2W.
Found - 39" D. Fir S. 70° E. 23.0 ft. scribed ¼ BT, other scribing not legible.
17" Laurel N. 5½° W. 31.8 ft. scribed T31S R2W S34 ¼ BT.
Tag on tree set by Williams 7/14/65.
No trace of any original bearing trees.
3" Brass Cap on ½" Iron Pipe mkd. 34 31-2 ¼

MICROFILM TO HERE 10/67

23

¼ Corner to Section 25 only, T32-3W.
Dependent resurvey of the E. Bdy. T32-3 as Surveyed by Fred Mensch, Aug. 1912.
Orig. Surv. states: Set a granite stone, 16x8x6 ins. for ¼ sec. cor. for sec. 25 only, mkd: "¼" on W. face, from which:
A fir, 50" diam., bears S. 77° W. 52 lks. dist. mkd: ¼ S25 BT, with open face, scribes in good condition.
A fir 36" diam., bears N. 21° W. 84 lks. dist. mkd: ¼ S25 BT, with open face, scribes in good condition.
Using record bear. & diat., Set 2"x30" Galv. I.P. with Brass Cap, 24" in the ground, stamped:

Glenn S. Baughman
For U.S. Forest Service
August, 1968
C. S. File No. 55/87

RE-RENEWED, SEE CORNER NO. #128
S25
1968
OLS536

From the Pipe Monument, the Orig. BT's. are:
42" Fir bears N. 21° W. 55.4 ft. mkd: ¼ S25 BT.
69" Fir bears S. 77° W. 34.3 ft. mkd: ¼ S25 BT.
Placed bearing tree tags on all bearing trees and facing the monument.