

Douglas County Surveyor's Record of
Government Corners Renewed

T. 32 S. T. S. R. 2 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97101

24

$\frac{1}{4}$ Corner Section 24 only, T32-3W.
Dependent resurvey of the E. Bdy. T32-3W, as surveyed by Fred Mensch, dated August, 1912. Original survey states: Set a slate stone, 18x12x4 ins., 12 ins. in ground, for $\frac{1}{4}$ sec. cor. of sec. 24 only, marked " $\frac{1}{4}$ " on W. face, from which:
A madrona, 12 ins., bears S.36°W. 83 lks. mkd: " $\frac{1}{4}$ S24 BT".
A fir, 6 ins., bears N.34°W. 40 lks. dist., mkd: " $\frac{1}{4}$ S24 BT".
Found - A Stone 18"x12"x4" marked " $\frac{1}{4}$ " on west face.
20" Madrona with open face scribes in poor condition, bears S.36°W. 54.9 ft.
Using record bearing & dist., I set 2"x30" I.P. with Brass Cap stamped:
T32S R3W WM
S 24
1968
OLS536

From the pipe monument, I marked the following trees:
A fir, 27 ins. diam., bears N.33°W. 25.5 ft. mkd: " $\frac{1}{4}$ S24 BT".
A fir, 12 ins. diam., bears S. 6°E. 15.3 ft. mkd: " $\frac{1}{4}$ S24 BT".
Placed bearing tree tags on all bearing trees and facing the monument.

25

$\frac{1}{4}$ Corner to Section 18 only, T32-2W.
Found - Orig. 24", now 38" Fir, S.20°W. 19.8 ft., opened face and found " $\frac{1}{4}$ S18 BT" in good condition.
Set - 2"x30" galv. I.P. with Brass Cap Stamped: T32S R2W
S18
1968
OLS536

From the Pipe Monument, the Orig. BT. is:
A fir, 38" diam., bears S.20°W. 19.8 ft. mkd: " $\frac{1}{4}$ S18 BT".
New BT: Marked 40" Fir bears S.27°E. 34.3 ft. mkd: " $\frac{1}{4}$ S18 BT".
Placed bearing tree tags on all bearing trees and facing the monument.

26

Section Corner to Sections 19 and 30 only, T32-2W.
Found - Stone 24"x12"x5" with 2 notches on south & 4 notches on north edges.
Orig. 24", now 34" Fir bears N.52°E. 4.0 ft., with scribes in poor condition.
Set - 2"x30" galv. I.P. with Brass Cap Stamped: R3W S24 | S 19 | R2W
S 30
1968
OLS536
SEE LETTER IN FILE

From the Pipe Monument, The Orig. BT. is:
34" Fir bears N.52°E. 4.0 ft. remkd: T32S R2W S19 BT.
New BT: 22" Fir bears S.38°E. 22.5 ft. mkd: T32S R2W S30 BT.
Placed BT tags on all BT's. and facing the monument.

27

Section Corner to Sections 24 & 25, T32-3W.
Found - Stone 15"x12"x6" with 2 notches on S. & 4 notches on N. edges.
Orig. 12", now 24" Fir, bears N.60°W. 29.7 ft. mkd: T32SR3WS24 BT.
Orig. 12", now 24" S. Pine, with closed face, bears S.82°W. 16.5 ft.
At the position of stone, Set 2"x30" Galv. I.P. with Brass Cap, 24" in the ground, & placed the stone alongside:
T32S
R3W CC S 24 | S30 R2W
S 25
1968
OLS536

From the Pipe Monument, The Orig. BT's. are:
24" Fir bears N. 60° W. 29.7 ft. mkd. T32S R3W S24 BT.
24" Sugar Pine bears S. 82° W. 16.5 ft. remarked: T32S R3W S25 CC BT.
Placed BT tags on all bearing trees and facing the monument.

28

Section Corner to Secs. 18 & 19, T32-2W.
Found - An Ironstone 24x14x8" with 3 notches on N. and S. edges.
Orig. 48", now 58" Fir, with open face & scribes in good condition, bears S. 8° E. 29.7 ft.
Set - 2"x30" Galv. I.P. with Brass Cap stamped:
T32S
R3W S 24 | S 18 | R2W
S 19
1968
OLS536
SEE LETTER IN FILE

From the Pipe Monument the Orig. BT. is:
58" Fir bears S. 8° E. 29.7 ft.
New BT! Mkd: 10" Madrona N.41°E. 51.3 ft. mkd: T32SR2W S18 CC BT.

Glenn S. Baughman
For U. S. Forest Service
August, 1968
C. S. File No. 55/87