

Douglas County Surveyor's Record of
Government Corners Renewed

T. 32 S. T. S. R. 2 W. R. W. W. M.

ROKE-CHAPMAN CO., EUGENE, ORE. 21881

29

Section Corner to Sections 12 & 13 only, T32S-R3W.

Found - A Stone 12x12x8 ins. with CC marked on the west face.

Orig. 16", now 18" Alder bears N.60°W. 45.5 ft. with open face, scribes in poor condition.

Set - 2"x30" galv. I.P. with Brass Cap stamped: R3W CC $\frac{S\ 12}{S\ 13}$ S 7 R2W

T 32 S
1968
OLS536

From the pipe monument, I marked:

6" Hemlock bears N. 57° W. 63.5 ft. mkd: T32S R3W S12 CC BT.

48" Fir bears S. 23° W. 60.6 ft. mkd: T32S R3W S13 CC BT.

Set BT tags on all bearing trees and facing the monument.

30

Section Corner to Sections 1 and 12, T32-3W.

Found - Stone 18x14x4" mkd. with 1 notch on N. & 5 notches on S. faces.

An Axel, 1 1/2" x 30", See Ren. #31, T32-3W.

16" Fir with open face, scribes in good condition N. 3° W. 6.8'.

12" Fir with closed face, bears S. 84° W. 14.6 ft.

At the position of the stone and axel, Set 2" x 30"

Galv. I.P. with Brass Cap stamped:

T 32 S
R3W $\frac{S\ 1}{S\ 12}$ S 6 R2W
1968
OLS536

From the pipe monument, the BT's. are:

16" Fir bears N. 3° W. 6.8 ft.

12" Fir bears S. 84° W. 14.6 ft.

Placed BT tags on all bearing trees & facing the monument.

31

Section Corner to Sections 6 and 7, T32-2W.

Found - An Ironstone 15x15x5 ins. with 1 notch on N. & 5 notches On S.

Orig. 20", now 32" Fir N.61°E. 18.5 ft. mkd: T32S R2W S6 BT.

Orig. 12", now 26" Fir bears S. 86°E. 24.5 ft. mkd: T32S R2W S7 BT.

Set - 2"x30" Galv. I.P. with Brass Cap stamped:

T 32 S
R3W S 12 $\frac{S\ 6}{S\ 7}$ R2W
1968
OLS536

Placed BT Tag on both Orig. Trees and facing monument.

32

1/4 Corner to Section 7 only, T32-2W.

Found - Orig. 12", now 16" Fir, marked $\frac{1}{4}$ S7 on East face.

Orig. 12", now 16" Fir bears N. 62°W. 13.7 ft. mkd: $\frac{1}{4}$ S BT.

Set - 2"x30" Galv. I.P. with Brass Cap Mkd:

T 32 S
R3W $\frac{S\ 7}{S\ 7}$ R2W
1968
OLS536

From the pipe monument, the orig. BT. is:

16" Fir bears N. 62°W. 13.7 ft. mkd: $\frac{1}{4}$ S BT.

New BT: 20" Fir bears S. 59° E. 26.0 ft. mkd: $\frac{1}{4}$ S BT.

Placed BT tags on all bearing trees and facing the monument.

33

Section Corner to Sections 15 - 16 - 21 - 22.

Found - Stone 24x12x10 ins. with 3 notches on S. and E. edges.

Orig. 14", now 27" Fir, with open face & in good condition, bears N. 74°E. 39.1 ft.

Orig. 10", now 14" Fir, with scribes in poor condition, bears S. 6° W. 7.9 ft.

Orig. 30" Fir, now stump with open face, bears N. 27 1/2°W. 20.5 ft.

Set - 2"x30" Galv. I.P. with Brass Cap, Stamped: T 32 S R 2 W

$\frac{S\ 16}{S\ 21}$ | $\frac{S\ 15}{S\ 22}$
1968 OLS536

From the pipe monument, the Orig. BT's. are:

27" Fir bears N. 74°E. 39.1 ft. mkd: T32S R2W S15 BT.

14" Fir bears S. 6° W. 7.9 ft. mkd: T32S R2W S21 BT. (remarked)

New BT's: 8" Fir bears N. 22 1/2°W. 11.5 ft. mkd: T32S R2W S16 BT.

9" W. Fir bears S. 31°E. 9.0 ft. mkd: T32S R2W S22 BT.

Glenn S. Baughman
For U. S. Forest Service
August, 1968
C. S. File No. 55/87

RE-RENEWED CORNER NO. 121