

Douglas County Surveyor's Record of
Government Corners Renewed

T. 32 S. T. S. R. 2 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

40

1/4 Corner to Sections 18 and 19.

Found - Stone 24x12x4 ins. marked "1/4" on N. face and
Mound of stone north of corner.

Set - 2"x30" galv. I.P. with Brass Cap, stamped: T 32 S R 2 W

1/4 S 18
S 19

From the Pipe Monument, I marked the following trees 1968 OLS 536

32" Fir bears N. 15° W. 41.8 ft. mkd: "1/4" S18 BT".

28" Fir bears S. 4° E. 23.9 ft. mkd: "1/4" S19 BT".

Placed BT tags on all bearing trees and facing the monument.

41

Section Corner to Sections 20 - 21 - 28 - 29.

Found - No Stone at Corner.

Orig. 48", now 52" Fir, bears S. 73° W. 25.2 ft. with open face,
scribes in good condition, mkd: T32S R2W S29 BT.

Set - 2"x30" galv. I.P. with Brass Cap, stamped: T 32 S R 2 W

S 20 | S 21
S 29 | S 28

From the Pipe Monument, the Orig. BT is: 1968 OLS 536

52" Fir bears S. 73° W. 25.2 ft.

New BT's: 6" Fir bears N. 79° W. 11.5 ft. mkd: T32S R2W S20 BT.

23" Fir bears N. 30° E. 66.8 ft. mkd: T32S R2W S21 BT.

No other trees within limits

Placed BT tags on all bearing trees and facing the monument.

42

Section Corner to Sections 19 - 20 - 29 - 30.

Found - Stone 18x12x6 ins. with 2 notches on S. & 3 notches on E. edges.

Orig. 28" Hemlock with open face, scribes in good condition N. 5° W. 29.3 ft.

Orig. 20", now 22" Hemlock, with open face, scribes in good condition,
bears S. 14° E. 42.2 ft.

Set - 2"x30" galv. I.P. with Brass Cap, stamped: T 32 S R 2 W

S 19 | S 20
S 30 | S 29

Marked the following bearing tree: 1968 OLS 536

54" Fir bears N. 69° E. 29.5 ft. mkd: T32S R2W S20 BT.

No other trees were within limits for sec. 30.

Placed BT tags on all bearing trees and facing the monument.

43

West 1/4 Corner Section 19.

Found - 22" Fir bears N. 44° E. 26 lks., scribe visible.

12x8x4" Stone "S" marked on top.

Set - 2"x30" Galv. I.P. with Brass Cap stamped:

1/4 Cor. S. 19, 1969 O.L.S. 536.

Found - 18" Fir bears S. 85° E. 12 lks., scribe visible.

Scribed: 12" Hemlock bears S. 80° E. 23.8 ft. Tagged.

Note - 1/4 Corner to Section 24, Brass Cap & Original Stone
bears S. 1° 03' 55" W. 612.95 ft.

44

1/4 Corner to Sections 19 and 30.

Set by proportionate measurement.

Set - 2"x30" Galv. I.P. & Brass Cap stamped "1/4 S 19/30

O.L.S. 536

Scribed: 10" Yew bears S. 52° E. 4.9 ft., Tagged.

45

1/4 Corner to Sections 19 and 20.

Set by proportionate measurement.

Set - 2"x30" Galv. I.P. with brass Cap stamp: 1/4 S 19/S 20

1969 OLS 536

Scribed: 14" Fir bears N. 65° W. 7.5 ft., tagged.

6" Fir bears N. 61° 30' E. 32.9 ft., tagged.

Glenn S. Baughman
August, 1968 - C. S. File No. 55/87

Glenn S. Baughman
For Ump. Nat'l. Forest
July, 1969 Map File M 38 - 38
and M 38 - 37

RE-RENEWED, SEE CORNER NO. #127
SEE CORNER NO. #113