

Douglas County Surveyor's Record of
Government Corners Renewed

T 32 S T. S. R 2 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

52

Section Corner to Sections 10 - 11 - 14 - 15.
Found - Orig. 40" now 50" Fir, alive, S. 10 1/2° W. 8.6 ft., blaze badly burned,
scribe "S 1" visible.

Orig. 24" Fir N. 40° W. 22.4 ft., only decayed remains found, no scribe.
No trace other Orig. BT's., due to fire many years ago.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 2 W
Office S 10 S 11
1970 S 15 S 14

New BT's: 12" W. Fir S. 86° W. 24.5 ft. mkd: "T32S R2W S15 CS BT".
15" W. Fir N. 65° W. 42.1 ft. mkd: "T32S R2W S10 CS BT".
40" Pine N. 42° E. 24.5 ft. mkd: T32S R2W S11 CS BT".
7" D. Fir S. 45° E. 38.5 ft. mkd: T32 S R2W S14 CS BT".

This corner lies on flat in extremely dense reproduction &
Rhododendron Brush.

8/4/70

53

1/4 Corner to Sections 14 and 15.

Found - 1970 C.S. Brass Cap Mkd: County Surveyor's T 32 S R 2 W
Office 1970 1/4 S 15 S 14

(This Brass Cap mkd. by W. Penley, see notes in C.S. File 54/117)
Old Corner Stone mkd: "1/4" alongside Brass Cap.

Orig. 36" now 48" Fir, alive, N. 52° E. 30.4 ft., shows good scar.

Orig. 24" Fir, now 30" S Mag, S. 60 1/2° W. 11.2 ft., shows good scar.

New BT's: 8" W. Fir N. 14° W. 46.0 ft. mkd: "1/4 S15 CS BT".
24" W. Fir S. 23° W. 67.6 ft. mkd: "1/4 S15 CS BT".
15" W. Fir S. 20° E. 30.3 ft. mkd: "1/4 S14 CS BT".

This corner lies approx. 200 ft. north of logging road, course SE & NW.

7/24/70

54

1/4 Corner to Sections 11 and 14.

Found - "X" on top of rock ledge, as called for in field notes,
15' x 10' x 8' above ground & "1/4" chiseled 3" to N. of "X".

Orig. 30" now 36" Fir, alive, N. 41° E. 56.1 ft., scribe visible on
rehealing blaze., good condition. We Tag.

Orig. 12" now 20" Fir, alive, S. 85° W. 46.9 ft. (Rec. S95W), scribe
visible on rehealing blaze. Good condition.

We are unable to set Standard Brass Cap at Corner Point so we
Drove, "PK" Nail in Center of "X" and Rechiseled old marks.

New BT: 8" W. Fir S. 23° W. 9.7 ft. mkd: "1/4 S14 CS BT".

Corner Point is located nearly verticle over Diamond Creek, course
N. 20° E. & old call to west of 118 ft. looks O.K. We do not measure.

Walls on both sides of creek are nearly verticle & composed of solid rock.

8/6/70

55

1/4 Corner to Sections 14 and 23.

Found - No trace of old Corner Stone.

Orig. 60" Fir, now 15 ft. high snag, S. 41 1/2° E. 56.1 ft., scribe visible.

Orig. 30" Fir, now decayed & burned stub, N. 44 1/2° W. 60.1 ft., no scribe.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 2 W
Office 1/4 S 14
1970 S 23

New BT's: 30" D. Fir N. 18° W. 52.5 ft. mkd: "1/4 S14 CS BT".
30" D. Fir S. 37° E. 89.7 ft. mkd: "1/4 S23 CS BT".

This corner lies on N. slope of Three Horn Mountain.

8/10/70

56

1/4 Corner to Sections 10 and 15.

Found - Corner Stone, in place, as called for with "1/4" mkd. on
N. side.

No trace of Orig. BT. to N.W. due to old fire. At a point
124.7 ft. S. 10° W., there is a hole & remains of old log. This matches
the location of other Orig. BT & the call dist. from summit of divide
to west fits this location, also.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 2 W
(Reset Stone alongside) Office 1/4 S 10
1970 S 15

New BT's: 12" D. Fir N. 72° W. 13.0 ft. mkd: "1/4 S10 CS BT".
10" Cedar N. 22° E. 18.4 ft. mkd: "1/4 S10 CS BT".
10" D. Fir S. 48° E. 12.5 ft. mkd: "1/4 S15 CS BT".
9" W. Fir S. 48° W. 9.0 ft. mkd: "1/4 S15 CS BT".

Mkd. 4 BT's. due to density of 2nd growth, this cor. lies on moderate northly slope
in very dense 2nd growth. Old Burn.

8/11/70

Vernon "Ray" Tracy
Vincent Perron
C. S. File No. 54/117

RE-RENEWED, FILED NO. #120