

Douglas County Surveyor's Record of  
Government Corners Renewed

32 T. S. 2 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

70

Vernon "Ray" Tracy  
J. Heritage  
C.S. 56/34  
7/2 73

1/4 Corner, Sections 11 and 14.  
Found - "X" on rock ledge as called for in orig. field notes, 15' x 10' x 9' and both orig. bt's, plus BT as recorded in Ren. No. 54  
PK nail was loose that was set in center of "X".  
Set - We drill hole in center of "X" and set Brass cap mkd.  
Douglas County T 32 S R 2 W  
Surveyors 1/4 S11 S14  
Office  
1973

Note - We do not mark new bt's as both orig's & ren. no. 54 BT are alive and in good cond.

7/23/73

Sec. Corner to Sec. 2, 3, 10 & 11  
Found: Weathered Basalt stone 6"x12"x18" with 4 recognizable notches on the south face.

O BT: 60" Fir stump bears S.18°W., 44.8 ft. (call: S.18°W., 40.3ft)  
Cut into scar and find "S" scribe.  
Find possible BT N.12°E., 72.0ft. (Call! N.20°E., 79.2 ft)  
No trace of original S.E. BT

New: At corner as determined from one recognizable BT we set a Brass cap on 1 1/2" Iron pipe marked

Douglas County Surveyor T 32 S  
1975 3/2  
10/11  
R 2 W

From Which: Original 60" Fir bears S.18°W., 40.3ft.  
Possible original 10" Fir now 12" stump bears N.13 1/2° E., 75.6 ft.

New: 9" Douglas fir scribed T32S R2W S11 CS BT in double scribe bears S 54°W., 11.2 Ft.  
9" Douglas Fir scribed T32S R2W S3 CS BT in double scribe bears N.30 1/2°W., 19.6 ft.  
11" Douglas fir scribed T32S R2W S2 CS BT in double scribe bears N.52°E., 27.8 ft.  
8" Cedar scribed T32S R2W S11 CS BT in double scribe bears S50 1/2°E., 29.7 ft.

We set stone beside cap compass Declination 20°

1/4 Corner Sec. 30 and 29  
Found - Original 50" Dia. sugar pine bears S 52°W., 29.7 ft. Scribed " 1/4 S BT" Bearing tree is a badly weathered snag.

No evidence of original hemlock at 1/4 corner or other bearing tree.

Set- Brass cap at 1/4 corner stamped

DOUGLAS COUNTY SURVEYORS OFFICE 1/4 S30 | S20  
1975

New BT's- D. Fir 35" diam, bears N65°W., 37°ft. scribed "1/4 S 30 CS BT"  
D Fir, 11" diam, bears N 11 1/2°E., 22.4 ft, scribed " 1/4 S 29 BT"

11/12/75

1/4 Corner to sec. 4 and 9  
Found-Ironstone 24"x10"x8" firmly in ground with "1/4" marked on North face, and orig. BT's

A fir stump was 24" now 32" that bears S89°W., and 29.7 distance. Blaze was open on arrival and there were visible scribe marks(BT) on face

A 40" now 44" fir tree with good scar bears N39°E., and 16.5 ft Dist.  
(record N 31 1/2°E) Tree is alive and in good condition.

At the corner point we set a 1"x30" IP with brass cap attached. We also set orig. stone on North side of Brass cap with "1/4" mark, facing north as per orig. notes. Brass cap reads

DOUGLAS COUNTY SURVEYOR T32S R2W  
1976 S4 1/4  
S9

1976

New BT's, 13" madrone scribed "1/4" S9 CSBT" in a double blaze bears S50°W., and 33.7 distance. 20°E Compass Declination 2/12/76

L.E. Monrean  
P.L.E.  
J.H.C.  
11/12/75  
CS 57/39

A Vic. Cangie  
Clell Goodwin  
Gary Langlitz  
Lenora Ladig  
S 59/2  
12/76

JAN 75

71

72

73

RE-OPENED WITH THE CORNER NO. #136