

Douglas County Surveyor's Record of  
Government Corners Renewed

T 32 T. S. R 2 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

78

M. Lenora Ladig,  
Co. Surveyors Office  
Gary L. Langlitz  
Debra L. Stewart  
Jul 3, 1976  
C.S. 59/18

1/4 Corner for Secs. 13 and 24.  
Found - A 24" x 15" x 10" Ironstone marked "1/4" on north face.  
From which:  
A 24" now 36" Fir bears S.60°E., 29.7 ft. Tree is alive with well  
healed blaze.  
A 60" now 72" Fir stump bears N.21°W., 28.4 ft. Fd. no trace of  
scribing.  
Set - At true corner point, A 1"x36" I. Pipe with brass cap stamped:  
DOUGLAS CO. SURVEYOR

RENEWED, SEE CORNER NO. 86

T 32 S R 2 W  
1/4 S 13  
S 24  
1976

Placed orig. stone north of brass cap.  
New BT - A 5" Hemlock bears S.73°W., 12.3 ft. scribed "1/4 S24 C.S. BT" in  
double blaze.

7/8/76

79

M. Lenora Ladig  
A. Vic Cangie  
Karen Cheney  
Aug. 5, 1976  
C.S. 59/18

1/4 Corner for Secs. 9 and 10  
Found - a 18" x 10" x 5" Ironstone with "1/4" mkd. on West face.  
From which:  
A 24" now 40" Fir, bears S.88°E., 17.2 ft. Tree is alive with  
well healed blaze.  
A 30" now 36" Fir, stump bears S.43°W., 27.7 ft. (Call S.43°W., 29.0)  
with well healed blaze.  
Set - At true corner point: A 1" x 36" I.P. with Brass cap stamped:  
"Douglas Co. Surveyor" T32S R2W  
1976 1/4 S 9 | S 10

Placed stone on West side of cap.  
New BT - A 9" Yew bears S.58° W., 29.4 ft. scribed "1/4 S9 CS BT" in  
single blaze.

8/5/76

80

May Queen No. 1 Lode, Corner #3 Mineral Survey No. 792 (Sec. 9)  
Found - An. orig. 7" now 18" Fir, alive and well healed which bears  
N.62°28'W., 5.5 ft.  
An orig. 6" now 7" Laurel down and rotten which bears S.81°08'E.,  
12.33 ft.  
Set - At true corner point, A 1" x 30" I. Pipe with brass cap mkd.  
"Douglas Co. Surveyor" T 32 S R 2 W  
1976 Cor. 3 May Queen 1  
M. S. 792

From which:  
An 8" D. Fir marked "MQ 3 792 CS BT" in double blaze bears  
N.21 1/2°E., 15.9 ft.

2/17/76

81

May Queen No. 1 Lode Corner #4 Mineral Survey 792 (Sec. 9)  
Found - Orig. 6" Hemlock, now a 17" snag, previously opened with scribing  
"BT MQ 4 792" visible, bearing S.70°20'E., 4.8 ft.  
An orig. 10" now 18" Hemlock, alive and well-healed bears N.58°58'E.,  
25.40 ft.  
We set - At the corner point as determined by record bearing and distance  
from the two found orig. BT's as mentioned above, we set a  
1" x 30" I. Pipe 24" in the ground, with brass cap attached mkd:  
Douglas Co. Surveyor T 32 S R 2 W  
1976

Cor 4 May Queen 1 M. S. 792

New BT - A 12" Yew bears S.42°E., 27.0 ft. scribed "MQ 4 792 CS BT"  
on a double blaze.

2/17/76

82

Glenn S. Baughman  
For: U.S. Forest  
Service  
Dec. 1976  
M 56 - 69

Section Corner For Secs. 13 and 24; and 18 and 19 of T32-1.  
Found - 1963 County Surveyors Brass cap. Ren. #8  
8" Yew, bears N.50°E., 9.9 ft.  
18" Yew, bears S.40°E., 18.3 ft.  
20" W. Fir bears N.55°W., 82.7 ft.

New BT - 6" Fir, bears S.75°W., 22.6 ft. scribed T32S R2W S24 BT.

RE-RENEWED, SEE CORNER NO. #135

12/76

Gary L. Langlitz  
A. Vic Cangie  
M. Lenora Ladig  
Feb. 17, 1976  
C.S. 59/24