

Douglas County Surveyor's Record of
Government Corners Renewed

T 32 T. S. R 2 R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

83

1/4 Corner for Sec. 24; and 19 of T.32-1
Set - 2 1/2" x 30" I.P. with brass cap stamped T32S R2W S24 R1W S19
1/4 S 1976 OLS 536.

BT's - 8" D. Fir bears N.29°W., 18.4 ft. scribed T32S R2W S24 BT. #124
6" Cedar bears S.2°E., 3.1 ft. scribed T32S R1W S19 BT.

RE-RENEWED, SEE CORNER NO.

84

Sec. Cor. for Secs. 24 and 25; and 19 and 30 of T.32-1.

Found - 1970 Brass cap set by Shaner Engineering

30" D. Fir bears S.24°W., 54.3 ft.

14" W. Fir bears S.30°E., 40.5 ft.

10" W. Fir bears S.54°W., 51.3 ft.

24" W. Fir bears N.41°W., 29.0 ft.

12" W. Fir bears N.24°W., 46.6 ft.

5" Yew bears N.10°30'E., 60.0 ft.

26" Cedar bears N.25°E., 47.7 ft.

Note: This corner lies in Jackson Co. Found: Sec. Cor. by Jackson CSO
lies S.64°41'19"W., 0.94 ft. from Shaner Corner.

(See also c.s. 63/82 for Jackson Co. DATA.) 12/76

85

Sec. Corner for Secs. 13, 14, 23 and 24.

Found - 1963 Doug. County Surveyors brass cap. Ren. #77

16" Fir, bears N.46°W., 45.4 ft.

24" Fir bears N.25°W., 84.0 ft.

8" Fir bears S.34°E., 26.0 ft.

New BT - 26" W. Fir bears S.44°W., 72.0 ft. scribed T32S R2W S23 BT.

No trees to the NE

RE-RENEWED, SEE CORNER NO. #122

86

1/4 for Secs. 13 and 24.

Found - 1976 Doug. County Surveyors brass cap. Ren. #78

36" W. Fir bears S.60°E., 29.7 ft.

72" Fir (stump) bears N.21°W., 28.4 ft.

5" Hemlock bears S.73°W., 12.3 ft.

New BT - 6" Fir bears S.75°W., 22.6 ft. scribed T32S R2W S24 BT.

87

Center 1/4 Corner For Sec. 24.

Set - 2 1/2" x 30" I.P. with brass cap stamped T32S R2W C 1/4 S24 OLS
536 1976

BT's - 16" W. Fir bears S.32°W., 51.8 ft. scribed C 1/4 S 24 BT.

16" W. Fir bears S.72°E., 36.8 ft. scribed C 1/4 S24 BT.

88

Center 1/4 Corner for Sec. 13.

Set - 2" x 30" I.P. with brass cap stamped T32S R2W C 1/4 S13 OLS
536 1976.

New BT's - 10" Fir bears S.9°W., 43.4 ft. scribed C 1/4 S13 BT with brass
washer stamped L.S. 536

12" Fir bears N.17°E., 11.4 ft. scribed C 1/4 S13 BT with brass
washer stamped L.S. 536

Corner falls 15 ft. South of small creek.

89

Sec. Cor. for Secs. 12 and 13; and 7 and 18 of T32-1

Found - 1963 Doug. Co. brass cap. Ren. #10

6" Chinquapin (dead) N.38°W., 48.7 ft.

20" W. Fir bears N22°E., 49.6 ft.

36" Fir (snag) bears S.50°E., 29.0 ft.

6" W. Fir (stob) bears S.86°E., 68.3 ft.

New BT's - 10" Fir bears N.85°W., 23.3 ft. scribed T32S R2W S13 BT w/br.
washer LS 536

9" Fir bears S.34°E., 31.6 ft. scribed T32S R1W S18 BT w/br.
washer LS 536

10" Fir bears N.15°W., 62.3 ft. scribed T32S R2W S12 BT w/br.
washer LS 536.

RE-RENEWED, SEE CORNER NO. #109

Glenn S. Baughman
For: U.S. Forest Service
December, 1976
M 56 - 69

Glenn S. Baughman
For: U.S. Forest Service
December 1976
M 56 - 69; M 56 - 70; M 56 - 68