

**Douglas County Surveyor's Record of
Government Corners Renewed**

T 32 T. S. R 2 R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Glenn S. Baughman
For: U.S. Forest
Service
December 1976
M 5 - 68

1/4 Corner for Sec. 13 and Sec. 18 of T32-1
Set - 2" x 30" I.P. with brass cap stamped T32S R2W 1/4 S13 S18 R1W
OLS 536 1976.
New BT's-12" Fir bears S.53°W., 31.2 ft. scribed 1/4 S13 BT.
24" Inc. Cedar bears N.35°E., 17.3 ft. scribed 1/4 S18 BT.

90

12/76

Glenn Baughman
For: U. S. Forest Ser.
Dec. 1976
M 56 - 72

Center 1/4 corner for Sec. 14
Set - 2 1/2" x 30" I.P. with brass cap stamped T32S R2W C 1/4 S14
OLS 536 1976.
BT's - 36" D. Fir bears N.20°W., 26.6 ft. scribed C 1/4 S14 BT.
10" W. Fir bears N.77°E., 41.3 ft. scribed C 1/4 S14 BT.

91

1/4 Corner for Secs. 2 and 11.
Set - 2 1/2" x 30" I.P. with brass cap stamped T32S R2W 1/4 S2 S11
OLS 536 1976.
BT's - 24" Sugar Pine bears N.59°E., 38.6 ft. scribed 1/4 S 2 BT.
18" D. Fir bears S.36°E., 14.0 ft. scribed 1/4 S11 BT.

92

Glenn Baughman
For: U. S. Forest
Service
December 1976
M 56 - 73

1/4 Corner for Secs. 10 and 11.
Set - 2 1/2" x 30" I.P. with brass cap stamped T32S R2W 1/4 S10 S11
OLS 536 1977.
BT's - 8" Cedar bears S.80°W., 10.8 ft. scribed 1/4 S10 BT.
14" D. Fir bears S.22°E., 18.2 ft. scribed 1/4 S11 BT.

93

Center 1/4 for Section 11.
Set - 2 1/2" x 30" I.P. with brass cap stamped T32S R2W C 1/4 S11
OLS 536 1976.
BT's - 8" D. Fir bears N.56°W., 20.0 ft. scribed C 1/4 S11 BT.
12" D. Fir bears S.1°W., 24.6 ft. scribed C 1/4 S11 BT.

94

Dec. 1976

R. B. Kimberling
M. W. Cline
Doug. Co. Surveyor
Office
Aug. 18, 1977
C.S. 59/38

Corner #4 - Yellow King #1, Mineral survey #792.
Found - A 14" Madrone (Rec. Laurel, 10") bears N.73°W., 36.3 ft. (Rec.
N.73°10'W., 27.4 ft.) with rotted out blaze.
A 12" Madrone (Rec. 5" Laurel) bears N.53°E., 2.9 ft. with pre-
viously chopped out blaze.

95

Set - A 1" x 36" Iron pipe with brass cap flush with ground marked:
"County Surveyors Office"
T 32 S R 2 W
S 4 Y.K. No.1-4
792
1977

New BT - A 9" D. Fir bears S.5 1/2°E. 17.1 ft. blazed and marked "CS BT
Y K No 1-4-792".

8/18/77

96

Corner #3 - Yellow King No. 2, Mineral Survey.
Found - A 8" now 19" Fir stump bears N.37 1/4°E., 27.6 ft. with healed
chopped open bottom sec. of blaze showing scribing "P 1 792".
A 4" now 14" Fir snag, 12 ft. tall bears S.59°E., 45.9 ft. with
healed chopped open double blaze showing faint scribe marks.
Set - A 1" x 36" I.P. with brass cap set 11" above ground marked:
"Douglas County Surveyor" T 32 S R 2 W
1977 Y.K. No. 2-3 | S.P.-1
Y.K. No. 1-2 | T.B.-3

I erect a 2 ft. dia. mound of stone to top of cap.
New BT's- A 18" D. Fir bears S.80°E., 39.5 ft. double blazed and scribed
"TB 3 SP 1 YK No.1-2 YK No2-3 792 CS BT".
A 12" D. Fir bears S.6°E., 28.0 ft. double blazed and scribed
"TB 3 SP-1 YK No. 1-2 YK No 2-3 792 CS BT"

Corner is 8 ft. north of creek.

11/1/77

Douglas County Surveyor's Office
R. B. Kimberling
S. J. Flause-W. Stewart
Nov. 1, 1977
C.S. 59/42