

Douglas County Surveyor's Record of
Government Corners Renewed

T 32 T. S. R 2 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97101

109

Section corner for Secs. 12 and 13; and Secs. 7 and 18 of T.32-1
Found - A 1" iron pipe projecting 24" above the ground with a 2 1/2" brass cap marked "County Surveyors Office" (1963) Ren. #89
a 35" D. fir rotted stump, bears N.58°E., 19.1 ft.
a 6" Chinquapin snag with scribe marks "S12CSBT" visible, bears N.38°W., 48.7 ft.
a 20" W. fir with healed blaze, bears N.22°E., 49.6 ft. #123
a 36" fir, wind thrown snag, bears S.50°E., 29.0 ft.
a 12" D. fir with scribe marks "T32S R2W S13 BT" visible on a partially healed blaze, bears N.85°W., 23.3 ft.
a 10" D. fir with scribe marks "T32S R1W S18 BT" visible on a partially healed blaze, bears S.34°E., 21.6 ft.
a 10" W. fir with scribe marks "T32S R2W S12 BT" visible on a partially healed blaze, bears N.15°W., 62.3 ft.
New BT's - a 10" D. fir bears S.72°W., 40.3 ft. I marked "T32S R2W S13 BT" on a double blaze and nailed a brass washer stamped "LS 536" into lower blaze.
a 12" D. fir, bears N.85°W., 23.3 ft. marked by Baugh-an in 1976, I chopped out "S13" and remarked "S12".

Glenn Baughman
For: U.S. Forest
Service
July 1979
C.S. 58/176

RE-REVIEWED, SEE CORNER NO. #123

7/79

110

Section corner for Secs. 6 and Sec. 1 of T.32-3
Found - 3/4" Iron pipe next to 10" x 10" x 9" stone. See Ren. #1
Set - Alum. cap at location of pipe stamped: T31S R2W S31 S1 S6 R3W R2W T32S 1980 RLS 601".
Found BT's -
5" Madrone bears N.38°25'W., 15.8 ft.
6" Madrone bears S.83°55'E., 9.8 ft.
10" Madrone bears S.26°35'E., 34.1 ft.
17" D. Fir bears S.19°35'W., 33.6 ft.

Malcolm Clark
Fof: U. S. Forest Service
M 83 - 53 C.S. 58/227
April 1980

1/4 Corner for Sec. 31 only, T.31-2
Found - 12" x 18" x 8" stone with "1/4" clearly chiseled on N. face. Ren. #121
52" Fir stump bears N.40°30'W., 75.3 ft. scribing visible.
19" White Fir bears N.72°15'E., 111.0 ft. scribing visible.
A 1" iron pipe bears N.33°W., 4.15 ft. See Ren. #21, C.S. 42/392
Set - An alum. cap in the position of the stone stamped: T31S R2W 1/4 S31 T32S R3W 1980 RLS 601.
New BT- 6" Madrone bears N.26°15'W., 65.3 ft. scribed "T31S R2W 1/4 S31 BT".

732-2
REN. #18
T31-2

112

Section corner for Secs. 29, 30, 31 and 32
Found - 10" x 12" x 8" stone with 5 notches on south side and 1 notch on east side, loosely set under old log.
30" rotted windfall bears N.12°W., 8.1 ft. to stump
18" windfall bears N.72°E., 40.0 ft. approx. with rotted face
Rotted stump bears S.69°E., 24.7 ft. no face.
36" snag bears S.56°W., 7.8 ft. marked "EX" on bark.
Set - a 2" x 30" alum. pipe with a 2 1/2" alum. cap marked: T32S R2W S30 S29 S31 S32 PLS 866 1980" at the position of the stone. Constructed a mound of stones around pipe. Place orig. stone in mound.
New BT's- 8" D. Fir bears N.11° 10'W., 15.2 ft. scribed "T32S R2W S30 BT".
7" D. Fir bears N.8° 15'E., 16.1 ft. scribed "T30S R2W S29 BT"
6" D. Fir bears S.81°20'E., 11.8 ft. scribed "T30S R2W S32 BT"
17" Pine bears S.32°20'W., 6.4 ft. scribed "T30S R2W S31 BT"
6" Fiberglass post with USFS signs 54-4 and 54-2 set 4 ft. north of pipe. with a brass washer marked "LS 866" nailed to each lower blaze.

William Ruppert
For: U.S. Forest
Service
June 1980
C.S. 58/229

113

Section corner for Secs. 19, 20, 30 and 29.
Found - 2" Galv. I.P. with 3" brass cap marked T32S R2W S19 S20 S30 S29 1968 PLS 536. Original stone is in mound around cap. Ren. #42
22" snag, S.14°43'E., 42.35 ft. "T32S R2W S29 BT" visible. "X" in bark.
53" D. Fir, N.70°00'E., 31.3 ft. "T32S R2W S20 BT" visible.
28" Hemlock N.6°10'W., 27.7 ft. "W" visible.
36" Uproot, S.17°35'W., 18.0 ft. "T32S R2W S30 BT" visible.

RE-REVIEWED, SEE CORNER NO. #132

William Ruppert
For: U.S. Forest
Service
May 1980
M 84 - 5
C.S. 58/143 (n)