

Douglas County Surveyor's Record of  
Government Corners Renewed

T 32

T. S.

R 2

R. W. W. M.

KONE-CHAPMAN CO., EUGENE, ORE. 21881

120

1/4 Corner for Sections 14 and 23.

Found - 1970 County brass cap properly marked, on 1" I.P. firmly set protruding 6" from soil.

An orig. 60" D. Fir now an approx. 15 ft. tall, 67" DBH D. Fir snag bears S.43 1/2°E., 56.1 ft. (Rec. S.41 1/2°E., 56.1 ft.)

Tree has opened blaze with scribing "1/4 S23 B" visible.

An orig. 30" D. Fir now a 20" DBH x 8 ft. (approx.) tall Fir stub bears N.44 1/2°W., 60.1 ft. No scribing remains on this tree.

A 34" now a 35" DBH D. Fir bears N.18°W., 52.5 ft. partially healed single blaze has the scribing "1/4 S14 CS BT" visible  
Ren. # 55

A 30" now a 31" DBH D. Fir bears S.39 1/2°E., 89.7 ft. (Rec. S.37°E., 89.7 ft.) Tree has partially healed single blaze with "1/4 S23" scribing visible.

Set - Because distance measurements to all BT's agree with the record the monument position is accepted as good.

New BT - A 7" DBH D. Fir bears S.42 1/2°W., 28.6 ft. Tree is scribed "1/4 S23 CS Bt" on a double blaze.

All trees are tagged with new DCSO BT tags.

9/22/80

121

West 1/4 Cor. to Sec. 7 only.

Found - From a 1902 survey, the corner tree marking the West 1/4 of Sec. 7 only, originally a fir, 10" diam., now a 16" (d.b.h.) D. Fir. This tree has an opened blaze on its East face, with the scribing "S7" visible. Also on this face is nailed a bronze washer with the markings "2741". From this tree, a 2 1/2" Brass Cap on a 2 1/2" iron pipe (o.d.) protruding 21" from the ground & firmly set bears S83°E, 2.5' (as per record Garret survey...M 44 - 62. The found B.C. is marked "1/4 S7 1968 OLS 536" & is recorded set in renewal# 32.

Accessories Found -

Original Fir, 12" is now 16" diam. bears N72°W, 16.2' (record per renewal # 32 is N62°W, 13.7'), recorded from B.C. monument to bearing tree. Partially healed blaze has fragmentary scribing visible... "45". From ren.# 32, a 20" diam. Fir with healed blaze bears S59°E, 26.5' (Rec...26.0').

New Accessories -

A D. Fir, 11" diam. scribed "WC 1/4 S7 CS BT" bears N40°E, 22.6'.

122

Section corner for Secs. 13, 14, 23 and 24.

Found - A 2 1/2" brass cap on a 1 1/2" iron pipe. Ren. #85

A 16" fir bears N.46°W., 46.4 ft. scar visible.

A 14" fir bears S.34°E., 26.0 ft. scribe visible.

A 24" fir bears S.44°W., 72.0 ft. scribe visible.

New BT - A 6" fir which bears N.12°E., 23.5 ft. marked T32S R2W S13 BT.

(add'tl info added 6/7/85) Found - 27" fir bears N.25°W., 84.0 ft. scar visible.

123

Section corner for 12 and 13; and Secs. 7 and 18 of T.32-1

Found - A 1963 County Surveyors brass cap on a 1" iron pipe. Ren. #109

18" fir (dead) bears N.22°E., 49.6 ft. blazes healed.

14" fir bears S.34°E., 21.6 ft. scribed visible.

13" fir bears S.72°W., 40.3 ft. scribe visible.

15" fir bears N.85°W., 23.3 ft. scribe visible.

6" fir (dead) bears N.37°W., 48.7 ft. scribe visible. (rec. chingquapin)

New BT - 7" fir which bears N.01°E., 15.9 ft. scribed T32S R1W S7 BT.

6/7/85

Stephen J. Flause  
Deputy, Doug. Co.  
Surveyors Office  
Bill Stewart  
Sept. 22, 1980  
C.S. 16/11

Stephen Flause  
Deputy, Doug. Co.  
Surveyors Office  
C. Plouff  
Feb. 26, 1981  
C.S. 61 / 24

Loyd R. Moffit  
L.S. #944  
For: U.S.F.S.  
April 1985  
C.S. 63/8

Loyd R. Moffit  
L.S. #944  
For: U.S.F.S.  
June, 1985  
C.S. 63/8

N E X T P A G E