

Douglas County Surveyor's Record of  
Government Corners Renewed

T 32 T. S. R 2 R. W. W. M.

KORE-CHAPMAN CO., EUGENE, ORE. 91881

127

Jackson County  
Surveyors Office  
Edward McGinty  
Sept. 7, 1988  
C.S. 63/82

Section corner common to sections 20, 21, 29 and 28.  
Found - 2" dia. galv. I.P. projecting 10 ins. with 3" dia. brass cap, properly mkd. Ren. #41  
The single remaining 1902 orig. BT, A D. fir, now 54", containing scribe marks including "S, 2 & W" in partly exposed face, bears Record S.73°W., 25.08 ft. to center of tree at base.  
The original stone could not be found.  
32" D. fir with healed blazes, bears N.30°E., 67.95 ft. to center of tree at lower blaze. (Rec. 66.8 ft.) Ren. #41  
9" W. fir with healed blazes bears N.79°W., 11.95 ft. to center of tree at lower blaze. (Rec. 11.5 ft.) Ren. #41  
New BTs - Marked "CS" "BT" and take measurements to center of trees at lower blaze:  
9" white fir bears S.36°E., 15.70 ft.  
7" D. fir bears S.46½°W., 22.10 ft.  
Corner lies about 150 ft. S.25°E. of old Richter cabin.

Edward McGinty  
Jackson County  
Surveyor  
R. Frost and  
S. Beecher, Techs.  
Sept. 29, 1988  
C.S. 63/82

1/4 Corner for Section 25 only of T32-3  
Found - Flush with the ground, the orig. 6z8z16 granite stone mkd. with cross on top & "¼" on West side of F. Mensch in 1912. Sawed fir stump, 60" dia., bears S.77°W., 35.6 ft. to center, (Record 34.32 ft.)  
Burned, sawed fir stump shell, 42" diam., containing reverse impression of scribe mks, in small segment of exposed (reverse) face, bears N.21°W., 54.9 ft. to center. (Rec. 55.44 ft.)  
2" dia. I.P. projecting 10" with 3" dia. brass cap bears S.23°E., 1.15 ft. (Ren. #23 C.S. 55/87)  
Set - Replace said stone with and deposit it alongside a 1z36 in. gal. I.P. set flush, with a 2½ in. dia. brass cap mkd. "T32S R3W R2W 1/4s 25 | C.S 1988"  
New BTs - 13" D. fir bears S.14½°W., 55.94 ft.  
8" Chinquapin bears S.55 3/4°W., 27.24 ft.  
New BTs mkd. "CS" "BT" and take measurements to center of trees at lower blaze. Note: No other available trees in Section 25. All appear to be dead or dying. Corner lies near top of West sloping ridge about 300 ft. S.30°W., of end of logging road and an estimated 350 ft. West (downhill) of landing alongside USFS road.

128

9/29/88

129

1/4 Corner for Sections 22 and 23  
Found - Firmly set, the 20x12x10 ins. sandstone, 5" above the ground mkd. "¼" on west face.  
Set - Replaced found stone with and deposit it alongside a 1x36 ins. galv. I.P. 30" in the ground, with a 2½ ins. dia. brass cap mkd. "T32S R2W 1/4S 22 | 23 C.S. 1986".  
Found original bearing trees recorded by C.L. Campbell in 1902:  
D. fir snag, 28" diam., with single healed blaze bears record S.35°W., 6.6 ft. to center of tree at base.  
The stump hole of tipped over D. fir, 39" diam., with single healed blaze, bears record S.25°E., 22.44 ft. to center.  
Mound stones around corner, mark new trees "CS" "BT" and take measurements to center of trees at lower blaze:  
10" D. fir bears N.76°E., 28.4 ft.  
20" W. fir bears S.8°W., 9.9 ft.  
An original (1902) line tree, D. fir 32" diam., with two blazes on the north and south sides bears North, 79.3 ft. (Rec. 82.5 ft.)  
Corner lies on south slope in heavy fir timber and along orig. blazed line. Posted location tag on a D. fir, 48" diam., at south edge of road approx. 20 chains north of quarter corner.

8/11/86

130

1/4 Corner for Sections 21 and 22  
Found - Projecting 15", the 2" diam. galv. I.P. with 3" diam. brass cap set for the corner on survey C.S. 55/87 dated 1968. Ren. #35  
The orig. 18x10x7 ins. stone mkd. "¼" as recorded by C.L. Campbell in 1902 lying alongside.

Edward McGinty, Jackson County Surveyor  
R. Frost and S. Beecher, Techs.  
C.S. 63/82

8/11/86

9/1/88