

Douglas County Surveyor's Record of
Government Corners Renewed

T 32 T. S. R 2 R.W.W.M.

KORE-CHAPMAN CO., EUGENE, ORE. 97101

130

C O N T - - -

9/1/88

An orig. BT, A D. fir now 28" diam., with axed out partial face fd. inside tree, containing partial scribed "4,S&BT", bears record S.19½°W., 31.68 ft. to estimated original position of scribed face. This tree was reported "remarked" on the above noted survey and this scribed face is now healed. Remeasure: S.21°W., 32.5 ft. to center of tree at base. (Record, C.S. 55/87, S.24°W., 31.0 ft. Ren. #35

The record location of the original southeast bearing tree falls in old skid trail.

A BT mkd. in 1968, now a fir stump, 20" diam., scribed "BT" in partially exposed face, bears N.68°E., 20.95 ft. to center. Record, 20.7 ft.

Set - Add marks T32S R2W" C.S. 1988 to said brass cap.
New BTs - 6" Incense cedar, bears S.23°E., 9.0 ft mkd. CS BT.
15" W. fir bears N.76°W., 46.4 ft. mkd. CS BT.

Note: The orig. "line tree" recorded to be 1.12 chains North is now a sawed fir stump, 66" diam., with no line blazes visible. Corner lies on small logged over bench about 20 ft. North of skid trail.

9/1/88

131

1/4 Corner on West line Section 30 only.

Found - Projecting 10" in ring of stone, the 2" diam. galv. I.P. with 2½" diam. brass cap set on M 84-6. Ren. #118

An orig. BT mkd. by C. Campbell in 1902, now a sawed madrone stump, 18" diam., containing partial scribed "3" & "BT" in rotted face bears N.3°E., 27.41 ft. to center of stump. (Record, N.1½°E., 29.70 ft.)

An orig. BT, subsequently relegated to a "former bearing tree" on a 1913 GLO resurvey; now a burnt fir snag, 48" diam., containing old axe work, bears S.15½°W., 47.63 ft. to center of tree. (Rec. S.17°W., 50.16 ft.)

The orig. stone could not be found, nor the yew bearing tree reported in 1913.

As all trees in the vicinity of the corner have been destroyed by recent (1987) forest fire; Set references as follows:

5/8" x 24" rebar set 22" in the ground with yellow plastic cap mkd. "Jackson C.S. bears N.665E., 8.19 ft.

5/8" x 24" rebar set 22" in the ground with yellow plastic cap mkd. "Jackson C.S. bears S.50°E., 6.45 ft. located at the base of a 48" diam. fir stump.

Corner lies on steep (65%) southwest slope, about 225 ft. southwest of rd.

11/3/88

132

Section Corner for Secs. 19, 20, 29 and 30

Found - Projecting 6" in mound of stone, the 2" diam. galv. I.P. with 3" diam. brass cap as recorded on C.S. 55/87. Ren. #42

Original BTs recorded by C. Campbell in 1902 Fd. as follows:

22" hemlock snag, with complete set of scribing visible, bears S.14½°E., 42.4 ft. to center of tree at base. (Rec. S.14°E., 42.24 ft.)

28" hemlock withaxed into and partly rehealed single face bears N.6½°W., 26.90 ft. to center of tree at base. (Record 44.88 ft.)

The orig. southwest BT, a tipped over hemlock has slid (northeasterly) down hill.

Bearing trees mkd. on C.S. 55/87 Ren. #42:

52" D. fir containing scribe marks including "32SR2W" in partially exposed face bears N.71½°E., 31.4 ft. to center of tree at base. (Rec. N.69°E., 29.5 ft.)

Bearing trees mkd. on M84-5, Ren. #113 dated 1980 found:

11" yew scribed as recorded bears S.34°E., 32.1 ft. to center of tree at lower blaze. (Rec. S.31°40'E., 32.0 ft.)

6" madrone scribed as recorded bears S.7°W., 4.8 ft. to center of tree at lower blaze. (Rec. S.6°52'W., 5.5 ft.)

Set - Add the marks "CS 1988" to brass cap.

New BT - 7" hemlock bears N.55°E., 11.8 ft. to center of tree at lower blaze mkd. "CS" "BT".

Corner lies on northeast (45%) slope about 40 ft. south of dry branch, course East.

9/15/88

Edward McGinty, Jackson County Surveyor
R. Frost and S. Beecher, Technicians.
C.S. 63/82

11/3/88

9/15/88