

Douglas County Surveyor's Record of
Government Corners Renewed

T 32

T. S.

R 2

R. W. W. M.

FOX-CHAPMAN CO., EUGENE, ORE. 97401

133

1/4 Corner common to Sections 20 and 21.

Found - Projecting 15", the 2" diam. galv. I.P. in mound of stone with 3" diam. brass cap mkd. as recorded on survey dated 1968. C.S. 55/87. Ren. #37

The orig. 18x8x8 ins. stone mkd. "1/4" by C. Campbell in 1902, is found lying alongside the brass cap.

Orig. BT, Fir stump remains found at record location of orig. northeast BT. Nearby is fd. axed out (fir) face scribed "1/4S2 B"

Sawed fir stump, 42" diam. scribed "1/4S2" in partly exposed face bears record S.23°W., 27.06 ft. to center of stump.

BT mkd. in Ren. #37 now a sawed fir stump, 10" diam., containing partial scribed "BT" in partly exposed face bears S.49°E., 7.6 ft. (Rec. S.48°E., 7.3 ft.)

12" D. fir scribed "1/4S21 CS" and "BT" bears S.34 1/2°E., 5.4 ft. Ren.

9" D. fir scribed "1/4S20 CS" and "BT" bears S.56°W., 23.0 ft. #125

13" Chinquapin scribed "1/4S20 CS" and "BT" bears N.57°W., 17.3 ft. Ren. #125.

The center of found spike, thru bearing tree tag, atop a 68 ins. diam. sawed fir stump bears N.43°E., 34.3 ft. Ren. #125

Set - Add marks "T32SR2W CS 1988" to above noted brass cap.

The peak of Mt. McLaughlin an estimated 40 miles distant bears S.65°E. Corner lies near the Northeast edge of standing timber at the corner of southerly and westerly edge of large clear cut.

9/7/88

Edward McGinty
Jackson County
Surveyor
R. Frost and
S. Beecher Techs.
C.S. 63/82
9/7/88

Gerald Nygren
For: U.S.F.S.
July 1989
C.S. 63/85

Don Bentz
For: US Forest Serv.
July 19, 1993
C.S. 63/153

Section Corner for Sections 35 and 36 only of T.31-2

134

Found - A 1" iron pipe with 2 1/2" brass cap extended 12" above ground and properly marked. Ren. #14 (1966 County BC)

A 46" D. fir bears N.45°W., 3.3 ft. healed blaze. (dist. is to face)

A 16" D. fir (dead and down) bears N.65°E., 19.8 ft. (Rec. N.30°E)

A 32" D. fir stump bears N.27°E., 54.4 ft.

New BT - A 4" D. fir bears N.75°E., 44.0 ft. scribed "X" in small upper blaze and "BT" in small lower blaze with brass washer stamped "LS 1035" nailed to lower blaze.

Corner for Sections 13 & 24; 18 & 19 T.32-1

135

Found - 8" Yew with visible scribing, bears N.50°E., 9.9 ft.

18" Yew with visible scribing, bears S.40°E., 18.3 ft.

24" W. Fir with healed blaze bears N.55°W., 82.7 ft.

12" Fir with healed blaze bears S.75°W., 22.6 ft. See Ren. # 82

Note - Found 1" Iron Pipe with Brass Cap lying on the ground, reset per record bearing and distances from existing bearing trees.

Reset - 1" Iron Pipe with County Surveyor's Office Brass Cap, monument 16" above ground with 24" dia. mound of stone.

Note - All bearing trees have a 6" red band painted around the tree and the blazed face painted red. USFS sign 54-3 'Bearing Tree' and sign 54-9 'Land Surveying Monument' are nailed to all bearing trees.

136

cont. next PG