

Douglas County Surveyor's Record of
Government Corners Renewed

32

T. S.

3

R. W. W. M.

Renewed by Ben. B. Irving.
County Surveyor.
January 1945.
C.S. 38/41

SECTION CORNER COMMON TO SECTIONS 3-4-9 & 10.

Set a 2"x54" Pipe 48" in ground.
Location set from old bearing trees.

- 30" Fir N. 70°E. 14 lks.
- 20" Fir N. 65°W. 48 lks.
- 30" Fir S. 64° W. 69 lks. (Snag)

Set new trees.

- 27" W. Fir S. 64°W. 50.5 Ft.
- 14" W. Fir S. 56°E. 53.0 Ft.

SEE CORNER NO. 30

Remarked OBT
NE & NW

1

SECTION CORNER COMMON TO SECTIONS 9 - 10- 15 & 16.

Granite stone set for corner as original 15x15x12" 10" in the ground.

Found original B.T. as follows,

- 20" Fir S. 1°E. 57 lks.
- 18" Fir N. 43°W. 59 lks.

Set the following new trees,

- 5" Sugar pine S. 75°E. 6 lks.
- 6" Madrona N. 77°W. 29 lks.

T 325 R 3 W 515 CSBT
T 325 R 3 W 59 CSBT

1/4 CORNER BETWEEN SECTIONS 15 & 16.

Granite stone set for corner as original 20x15x12" 15" in the ground.

Found original B.T. as follows.

- 40" Fir N. 25°E. 67 lks. Remarked in bark.
- 48" Fir N. 30°W. 15 lks. Scrib marks not legible.

Marked new B.T. as follows.

- 38" Fir S. 77°W. 92 lks.

1/4 CORNER BETWEEN SECTIONS 9 & 16.

Granite stone set for corner in place.

Original B.T. A 30" Cedar N. 1° E. 14.5 ft.
Scrib A 5" Sugar Pine S. 53° 55' E. 18.7 ft.

1/4 CORNER SOUTH SIDE SECTION 16.

Granite stone set for corner in place.

Both old B.T.'S standing but dead.
Scribe A 6" Yew N. 33° 43' W. 76.7 ft.
A 16" Fir N. 62° 55' E. 58.1 ft.

1/4 CORNER BETWEEN SECTIONS 20 & 21

Found old B.T. 24" Fir N. 9° W. 21.2 ft. dead.

Drive 5/8" Bolt for Corner.
Scribe A 36" fir N. 75° E. 50.2 ft.
A 40 " Fir N. 25° 04' W. 54.4 ft.

Geo. J. Wenderoth
Dep. Co. Surveyor
October 1946.
Witness Clifford Worley.

Geo. Wenderoth
Dep. Cnty. Surv.

Wenderoth
C.S. 38/41A

NORTH SEC. COR. 20-21

Renew on account of new road, Set new B. T.
5" Yew bearing S 73° 30' E 68.4 ft. dist.
16" Hemlock bearing S 80° 45' W 111.5 ft. dist.

1/4 COR. NORTH SIDE OF SEC. 20

Set halfway between Sec. Cors., Drove 1 1/2" I. Pipe
6" Yew bearing S 77° 40' W 45.0 ft. dist.
8" Fir bearing S 25° 02' W 40.5 ft. dist.

RE-RENEWED, SEE CORNER NO. 182

FOUND O.K.
JMP C.S. 54/91

2

3

4

5

6

7

8

PT