

Douglas County Surveyor's Record of  
Government Corners Renewed

32

T. S.

3

R. W. W. M.

~~RE-NEWED SEE CORNER NO. 104~~  
COR. BET. 6-7  
Found 36" Fir N 80° W 9.9 ft.  
Drive 1" I. Pipe  
Scribe 12" Yew S 26° 40' E 31.8 ft.

9

Geo. Wenderoth  
D.C.S.

H. Foreman  
Witness  
June, 1950

COR. 5-6-7-8  
Find 24" Fir S 10° W 27.7 ft.  
18" Fir N 45° W 9.2 ft. O.B.T. - Corrected to N 54° 45' W  
30" Fir S 22° 30' E 27.0 ft.  
Scribe 10" Hemlock N 36° 30' E 12.4 ft.  
Drive 1 1/4" Pipe for corner.

10

~~RE-NEWED SEE CORNER NO. 13~~  
COR. 3-10  
1" I. Pipe  
18" W. Fir S 15° W 7.2 ft. O.B.T.  
14" W. Fir N 70° 33' W 62.9 ft.

11

Wenderoth Dep  
D.C.S.

Sept. 1947

7CS45/22

~~RE-NEWED SEE CORNER NO. #86~~  
COR. 3-4  
1" I. Pipe  
O.B.T. fallen  
6" New S 44° W 54.8 ft.  
6" Madrone S 76° 24' E 26.5 ft.

12

~~RE-NEWED SEE CORNER NO. #11~~  
COR. 3-10  
Found corner pipe and 2 B.T.s Ren. #11  
Marked new B.T. and scribed  
W. Fir S 22° W 19.4 ft. marked 1/4 S - 10 - C.S.B.T.

13

~~RE-NEWED SEE CORNER NO. #62~~  
COR. 10-15  
Set 3/8 in. iron rod by proportionate measurement at root of new B.T.  
A 72 in. Fir - face bears South 3.2 ft. Marked 1/4 S 15 - C.S.B.T.  
30 in. Fir N 59° E, 24.6 ft. Marked 1/4 S 10 - C.S.B.T.

14

SEC. COR. 10-11-14-15  
Found granite rock with cross  
80 in. Fir S 65° E, 36.8 ft. (No record)  
Cut into 16 in. Fir S 60° W 10.2 ft. Marked S 15 - T 32 S, R 3 W  
Tree rings indicate was scribed 80 yrs. ago  
Blaze and scribe new B.T.s  
24 in. Fir N 50° E, 18.2 ft. Marked T 32 S R 3 W S 11 C S B T.  
16 in. Fir N 55° W, 67.4 ft. Marked T 32 S R 3 W S 10 C S B T  
14 in. Fir S 85° W, 34.9 ft. Marked T 32 S R 3 W S 15 C S B T.

15

~~RE-NEWED SEE CORNER NO. #71~~  
SEC. COR. 2-3-10-11  
Found granite and stone with cross  
2 O. B.T.s 10 in. Fir (now 20 in.) S 30° W 9 lks. (chopped out)  
15 in. Cedar (now 24 in.) S 30° E, 64 lks. (Rescribe)  
Blaze and scribe new B.T.s  
14 in. Fir N 83° E, 31 ft. Marked T 32 S R 3 W S 2 C S B T  
60 in. Fir N 23° W 54.0 ft. Marked T 32 S R 3 W S 3 C S B T.

16

Closing Corner Sections 13 and 14 or S.E. Corner Sec. 14,  
as det. by O. B. T.'s:  
14" Fir Stump, logged, bears N.18°W. 19.0 ft. dist. O.B.T.,  
I rescribed S14 B.T. I rescribed S14 B.T. #87  
12" W. Fir Stump, logged, bears S.10°E. 17.2 ft. dist. O.B.T.  
15" Hemlock Stump S.82°W. 31.7 ft. O.B.T.  
At Corner Point found Original Stone & Set 1"x50" drill steel from which:  
30" Hemlock Stump, logged, bears North 7.8 ft. dist. mkd. S13 B.T.  
13" W. Fir Stump, logged, bears South approx. 60.0 ft. mkd. S23B.T.  
Logging road bears South 50.0 ft. East end of 30" Metal Culvert thru  
Road bears North 153.0 ft. on slope distance.  
Corner lies in clear cut high lead logging and no green trees left.

17-A

South 1/2 Corner Section 14, only, as det. by O.B.T.'s:  
28" Fir Stump, logged, bears N.22°E. 15.8 ft. dist. O.B.T.,  
I rescribed 1/4 S14 B.T.  
24" Fir Stump bears N.22°W. 22.4 ft. O.B.T., I rescribed 1/4 S14 B.T.  
At Corner Point found Orig. Stone & Set 2" x 30" Iron Pipe from which:  
26" Fir Stump, logged, bears S.22°W. 15.5 dist. mkd. 1/4 S B.T.  
End of Spur Road and Landing bears S.44°W. approx. 450.0 ft. distance.

18-A

A. R. Evans - D. C. S.  
R. G. Irving - Witnesses  
J. I. Clinton  
February, 1951

18-2  
CS 44/92  
VS PG 39

John H. Markham, Jr.  
For M. & B. Logging  
Witness: H. C. Stokes  
Oct. 7, 1959  
C. S. FILE No. 42/356

79