

Douglas County Surveyor's Record of
Government Corners Renewed

32 S T. S. 3 W R. W. W. M.

KOTE-CHAPMAN CO., EUGENE, ORE. 97196

H. W. Lawrence
May 10, 1951
June 21, 1951
C.S. 40/343

S.W. COR. SEC. 4 **RE-RENEWED, SEE CORNER NO. 26** 17
Sec. Cor. stake being prone and too rotten to withstand re-driving.
Drove $\frac{3}{8}$ in. o.d. iron pipe 30" long, 24" into the ground in the
place of the wooden stake.

South $\frac{1}{4}$ Corner (Secs. 4 and 9) **RE-RENEWED, SEE CORNER NO. 23** 18
Difficult to recognize, stake gone and both bearing trees down.
Drove a 4 ft. fir post squared to 4 ins. at the top end, firmly
into the ground at the point S 20° E 7.92 ft. from the hole
made by the down, scribed 10" Fir, as given in the original
survey notes, from which
A fir 33" dia. bears S 50° W 14.2 ft., marked $\frac{1}{4}$ S B T
A fir 26" dia. bears N 51° E 6.1 ft., marked $\frac{1}{4}$ S B T

Geo. Wenderoth
File 45/226

Section corner to 3 and 4 (T32S, R3W) and 34 and 33 (T31S, R3W.) 19
1 inch iron pipe.
30" Fir S. 42° 55' E., 15.2.
10" Chinquapin S. 26° 42' W., 14.1.
12" Fir N. 75° 05' E., 20.7.
12" Hemlock N. 59° 18' E., 29.4. \rightarrow may be gone?

George J. Wenderoth,
Deputy County Surveyor
May, 1955.
C. S. File No. 46/134.

$\frac{1}{4}$ sec. corner to section 6, T 32 S, R 3 W., and section 1, T 32 S, R 4 W.
1 inch iron pipe.
20 inch Fir, N. 68° E., 5.3 feet.
20 inch Fir, N. 48° W., 12.0 feet. **RE-RENEWED, SEE CORNER NO. 175** 20

Section corner to secs. 6 & 7, T 32 S, R 3 W., and secs. 1 & 12,
T 32 S, R 4 W.
1 inch iron pipe.
38" Fir, N. 22° E., 13.2 feet.
30" Fir, S. 8° E., 141.2 feet.
42" Fir, S. 8° 30' W., 109.5 feet.
36" Fir, N. 18° W., 71.3 feet.

FD OK, NYGREN, 11/96 M129-34

George Wenderoth
Dep. Co. Sur.
May, 1955.
C. S. File No. 46/134.

Township corner to sec. 6, T 32 S, R 3 W., sec. 1, T 32 S, R 4 W.,
sec. 36, T 31 S, R 4 W., and sec. 31, T 31 S, R 3 W. 22
 $1\frac{1}{2}$ inch iron pipe.
8" Thorn, S. 77° E., 48.8 feet.
10" Hemlock, S. 33° 40' W., 185.5 feet.
24" Fir, N. 12° 20' W., 142.0 feet. **RE-RENEWED, SEE CORNER NO. #44**

George J. Wenderoth, Deputy County Surveyor.
October, 1955.
See C. S. File No. 47/17. M 41-10

$\frac{1}{4}$ corner S. side Sec. 4, 23
Found 30" Fir, N. 47° 30' E., 6.3 feet. Ren. # 18
36" Fir, S. 53° 45' W., 14.4 feet. Rescribed both trees.
Set $\frac{3}{8}$ inch I. Pipe. **RE-RENEWED, SEE CORNER NO. 122**

$\frac{1}{4}$ corner N. side sec. 4. 24
Set from measurement from section corners.
1 inch iron pipe.
Scribe:
7" Fir, N. 1° 37' E., 24.1 feet.
14" Fir, S. 42° 05' W., 11.8 feet.
Old corner is gone.

$\frac{1}{4}$ corner between secs. 4 and 5. 25
Found pine stump S. 50° E., 25.7 feet, scribe marks showing.
Drive 1 inch iron pipe.
Scribe:
14" Hawthorne, S. 40° W., 91.3 feet. **RE-RENEWED, SEE CORNER NO. 123**
26" Fir stump, N. 52° 46' E., 97.7 feet.
No other trees near.