

Douglas County Surveyor's Record of
Government Corners Renewed

T. 32 S. T. S. R. 3 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

45

~~Sec. Cor. to Sec. 31, T32-3; Sec. 30, T31-3; Sec. 25, T31-4; Sec. 36, T32-4.
Found - 24" Cedar, now dead Snag, S. 7° W. 20.6 ft., scribe vis. "CS BT".
18" D. Fir S. 19° E. 47.5 ft., Gone. (All BT's. Rec. Ren. #19, T31-3W)
20" D. Fir, now 25", N. 13½° E. 22.7 ft. This tree in slope bank of road.
14" D. Fir, now 17", N. 13° W. 19.4 ft., shows good scar.
Set - Brass Cap at Sec. Cor. Mkd: County Surveyor's Office, 1966~~

T 31 S	R	S 25	S 30	R
4	4	S 36	S 31	3
W	T 32 S	W		

New BT's: 19" D. Fir S. 16° E. 80.1 ft. scribed T32S R3W S31 CS BT.
8" D. Fir S. 83° W. 17.5 ft. scribed T32S R4W CS BT.
Note - This corner is on edge of new Road.

46

Sec. Cor. to Secs. 3 & 4, T32-3W. & Secs. 33 & 34, T31-3W.
Found - 1" Iron Pipe at Sec. Corner, See Ren. #19
30", now 34" Fir S. 43° E. 15.2 ft. Opened but patched over
Distance to the face.
10" Chinq., now dead, S. 26½° W. 14.1 ft., scribe visible.
12", now 14" Fir, N. 75° W. 20.7 ft., shows good scar.
12", now blown down Hemlock, N. 59° E. 29.4 ft., scribe visible.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966

T 31 S	R	S 33	S 34	3
S 4	S 3	W		
T 32 S				

New BT's: 8" D. Fir S. 60½° W. 42.9 ft. scribed T32S R3W S4 CS BT.
13" D. Fir N. 35° E. 52.0 ft. scribed T31S R3W S34 CS BT.
Note - This corner lies on the top of small, side ridge in bottom of ravine.

FO OK 10/94 - M121-13

47

¼ Corner to Sec. 3, T32-3W. & Sec. 34, T31-3W.
Found - Iron Pipe at ¼ Corner, See Ren. #13, T31-3W.
12" Fir, now dead, N. 39½° E. 18.9 ft., scribe visible "¼".
10" Fir, now blow down, S. 71½° E. 12.3 ft.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966

T 31 S	R	¼ S 34	3
S 3	W		
T 32 S			

New BT's: 18" D. Fir N. 28° W. 23.8 ft. scribed ¼ S34 CS BT.
7" W. Fir S. 71½° W. 18.8 ft. scribed ¼ S 3 CS BT.

RE-RENEWED, SEE CORNER NO. #210

RE-RENEWED, SEE CORNER NO. #200

48

Sec. Cor. to Secs. 3 & 2, T32-3W. & Sec. 34 & 35, T31-3W.
Found - No trace of Iron Pipe as recorded in Ren. #12, T31-3W.
28", now 28" Hemlock, N. 38° E. 12.5 ft. Tree almost dead #200
28" W. Fir Snag S. 31° W. 14.5 ft., scribe visible "T32S".
6" Hemlock, down, S. 36° E. 33.0 ft., scribe visible "S2 CS BT."
10" Fir N. 11° W. 11.5 ft. no trace.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966

T 31 S	R	S 34	S 35	3
S 3	S 2	W		
T 32 S				

New BT's:
49" D. Fir west 66.3 ft. scribed T31S R3W S34 CS BT.
10" Hemlock S. 9° W. 27.0 ft. scribed T23S R3W S 3 CS BT.
20" Hemlock N. 86° E. 25.2 ft. scribed T31S R3W S35 CS BT.

49

Sec. Cor. to Secs. 2 and 1, T32-3W. and
Secs. 35 and 36, T31-3W.
Found - No trace of Corner Stone.
No trace of 10" Laurel S. 50° W.
30" Pine, now 53", N. 42° W. 75.9 ft., scribe visible "35".
12" Pine, now 38", S. 12½° E. 178.2 ft., shows scar.
14" Pine, now 31", S. 31° W. 105.6 ft., scribe visible "2".
Set - Brass Cap at Sec. Cor. Mkd: County Surveyor's Office, 1966

T31S	S 35	S 36
R3W T32W	S 2	S 1

New BT's: 8" Laurel S. 42° E. 26.9 ft. scribed T31S R3W S1 CS BT.
6" Laurel N. 68° E. 5.2 ft. scribed T31S R3W S36 CS BT.
Reblazed & Rescribed : 53" Pine N. 42° W. 75.9 ft. scribed T31S R3W S35 CS BT
April 11, 1966

John M. Powell
Frank Jones & Joe Brady
January 1966
C. S. File No. 52/63